

1655S LACQUER CLEARS

MSDS Number

BBNGV

National Stock Number

8010-00F003553

Product Name

1655S LACQUER CLEARS

Manufacturer

DU PONT E I DE NEMOURS AND CO INC

Product Identification

Product ID:1655S LACQUER CLEARS

MSDS Date:01/01/1991

FSC:8010

NIIN:00F003553

MSDS Number: BBNGV

Responsible Party

DU PONT E I DE NEMOURS & CO INC

1007 MARKET ST

WILMINGTON , DE 19899

US

Emergency Phone: 800-441-3637

Info Phone: 800-441-7515

Cage: 90227

Contractor

DU PONT E I DE NEMOURS & CO FABRICATED PROD DEPT

WILMINGTON, DE 19898

US

800-441-3637

Cage: 90227

Ingredients

HEXONE, METHYL ISOBUTYL KETONE (MIBK), 4-METHYL-2-PENTANONE

CAS: 108-10-1

RTECS: SA9275000

Fraction By Weight: 9%

OSHA PEL100 PPM/75 STEL

ACGIH TLV: 50 PPM/75 STEL; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

BUTANOL, N-BUTYL ALCOHOL, PROPYL CARBINOL, BUTYL ALCOHOL

CAS: 71-36-3

RTECS: EO1400000

Fraction By Weight: 3%

OSHA PEL100 PPM

ACGIH TLV: S, C 50 PPM; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

WET NITROCELLULOSE, NITROCELLULOSE, NITRATE CELLULOSE

CAS: 9004-70-0

RTECS: QW0975200

TOLUENE

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 23%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

LIGHT ALIPHATIC NAPHTHA, VM & P NAPHTHA, LACOLENE *92/4*

CAS: 64742-89-8

OSHA PEL300 PPM

ACGIH TLV: 300 PPM

XYLENE, DIMETHYLBENZENE, XYLOL

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 11%

OSHA PEL100 PPM

ACGIH TLV: 100 PPM, SKIN

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

7.02-7.81

RTECS: 9999999WG

COCONUT OIL, ETHYLENE GLYCOL, PHTHALIC ANHYDRIDE POLYMER

CAS: 67922-75-2

DI-SEC-OCTYL PHTHALATE, BIS (2-ETHYLHEXYL) PHTHALATE (DOP),

CAS: 117-81-7

RTECS: TI0350000

Fraction By Weight: 1%

OSHA PEL5 MG/CUM

ACGIH TLV: 5 MG/CUM

EPA Report Quantity: 100 LBS

DOT Report Quantity: 100 LBS

ETHANOL (ETHYL ALCOHOL), TECSOL, ALCOHOL

CAS: 64-17-5

RTECS: KQ6300000

OSHA PEL1000 PPM

ACGIH TLV: 1000 PPM

ISOPROPANOL (ISOPROPYL ALCOHOL), 2-PROPANOL, DIMETHYL

CAS: 67-63-0

RTECS: NT8050000

OSHA PEL400 PPM

ACGIH TLV: 400 PPM

METHANOL (METHYL ALCOHOL), COLUMBIAN SPIRITS

CAS: 67-56-1

RTECS: PC1400000

Fraction By Weight: 4%

OSHA PELS,200PPM/250STEL

ACGIH TLV: S,200PPM/250STEL; 93

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

METHYL ISOAMYL KETONE, MIAK, 5-METHYL-2-HEXANONE

CAS: 110-12-3

RTECS: MP3850000

OSHA PEL100 PPM

ACGIH TLV: 50 PPM; 9293

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:YES IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INGESTION: GASTROINTESTINAL DISTRESS.

INHALATION: NOSE/THROAT IRRITATION, EYE WATERING, HEADACHES,

NAUSEA, DIZZINESS, LOSS OF COORDINATION. EYES: IRRITATION/BURNING.

VM&P NAPHTHA MAY CAUSE TEMPORARY U PPER RESPIRATORY & LUNG

IRRITATION W/COUGH, DIFFICULT BREATHING, & SHORTNESS OF BREATH.

Explanation of Carcinogenicity:SEE INGREDIENTS.

Effects of Overexposure:INHALATION: PERMANENT BRAIN & NERVOUS SYSTEM

DAMAGE. SKIN: IRRITATION W/DISCOMFORT & DERMATITIS. HARMFUL

ABSORPTION LEADING TO LIVER & KIDNEY DAMAGE. MAY CAUSE ABNORMAL

BLOOD FORMING FUNCTION W/ANEMIA . ABNORMAL LIVER FUNCTION

W/JAUNDICE. FATIGUE/HEADACHE/ANAESTHETIC/NEUROLOGIC EFFECT/VISUAL

DIFFICULTY/BLINDNESS/DEATH.

Medical Cond Aggravated by Exposure:DISEASE OF LIVER, CENTRAL NERVOUS SYSTEM, GASTROINTESTINAL TRACT, REPRODUCTIVE ORGANS

First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. IF BREATHING DIFFICULTY PERSISTS/OCCURS LATER, CONSULT PHYSICIAN. SKIN: WASH W/SOAP & WATER. EYES: FLUSH W/PLENTY OF WATER FOR AT LEAST 15 MINS. OBTAIN MEDICAL ATTENTI ON IN ALL CASES.

Fire Fighting

Flash Point Method:CC
Flash Point:-73F
Lower Limits:0.2%
Upper Limits:36.5%
Extinguishing Media:WATER SPRAY, FOAM, CO2, DRY CHEMICAL
Fire Fighting Procedures:FULL PROTECTIVE EQUIPMENT/SCBA. WATER SPRAY MAY BE INEFFECTIVE. WATER FROM FOG NOZZLES MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD UP.
Unusual Fire/Explosion Hazard:WHEN HEATED >20F, EMITS FLAMMABLE VAPORS, WHICH WHEN MIXED W/AIR, CAN BURN/BE EXPLOSIVE. FINE MISTS/SPRAYS MAY BE FLAMMABLE AT TEMPS

Accidental Release

Spill Release Procedures:VENTILATE AREA. REMOVE SOURCES OF IGNITION. PREVENT SKIN CONTACT/BREATHING OF VAPOR. CONFINE AND REMOVE WITH INERT ABSORBANT. WEAR PROTECTIVE EQUIPMENT.

Handling

Handling and Storage Precautions:CLOSE CONTAINER AFTER EACH USE. GROUND CONTAINERS WHEN POURING. OBSERVE LABEL PRECAUTIONS. KEEP AWAY FROM HEAT, SPARKS, & FLAME. DON'T STORE >120F.
Other Precautions:DON'T SAND, FLAME CUT, BRAZE OR WELD DRY COATING W/OUT PROTECTIVE EQUIPMENT. AVOID BREATHING VAPORS OR MISTS.

Exposure Controls

Respiratory Protection:WEAR PROPERLY FITTED VAPOR/PARTICULATE RESPIRATOR (NIOSH/MSHA TC-23C) FOR USE W/PAINTS DURING APPLICATION & UNTIL ALL VAPORS & SPRAY MISTS ARE EXHAUSTED. WEAR POSITIVE PRESSURE SUPPLIED-AIR RESPIRATOR (TC-19C) IN CONFINED AREAS.
Ventilation:SUFFICIENT IN VOLUME & PATTERN TO KEEP CONTAMINANTS BELOW APPLICABLE LIMITS.
Protective Gloves:NEOPRENE
Eye Protection:SPLASH GUARDS, SIDESHIELDS
Other Protective Equipment:NEOPRENE COVERALLS
Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING & BEFORE EATING OR SMOKING.
Supplemental Safety and Health
PERCENT BY WEIGHT: 67-97.

Chemical Properties

Boiling Pt:B.P. Text:129-727F
Vapor Density:>1
Evaporation Rate & Reference:SLOWER THAN ETHER
Solubility in Water:MISCIBLE
Percent Volatiles by Volume:73-98%

Stability

Stability Indicator/Materials to Avoid:YES
AIR
Stability Condition to Avoid:HEAT, SPARKS, FLAME, TEMPS >120F, & OTHER SOURCES OF IGNITION
Hazardous Decomposition Products:CO, CO2, SMOKE, & FLAMMABLE VAPORS ABOVE FLASH POINT

Disposal

Waste Disposal Methods:DON'T ALLOW MATERIAL TO CONTAMINATE GROUND WATER SYSTEMS. INCINERATE ABSORBED MATERIAL IN ACCORDANCE WITH FEDERAL,

STATE AND LOCAL REQUIREMENTS. DON'T INCINERATE IN CLOSED CONTAINERS. FLAMMABLE LIQUID PAINT UN 1263.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.