

DULUX ALKYD ENAMEL 43D

MSDS Number

BBNJN

National Stock Number

8010-00F003593

Product Name

DULUX ALKYD ENAMEL 43D

Manufacturer

E I DUPONT DE NEMOURS

Product Identification

Product ID:DULUX ALKYD ENAMEL 43D

MSDS Date:01/01/1987

FSC:8010

NIIN:00F003593

MSDS Number: BBNJN

Responsible Party

E.I. DUPONT DE NEMOURS/WILMINGTON, DE 19898

Emergency Phone: (800) 441-3637

Cage: 19898

Contractor

E.I. DUPONT DE NEMOURS & CO., INC.

1635

WILMINGTON, DE 19898

US

800-441-3637

Cage: 19898

Ingredients

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: SE7555000

OSHA PEL100 PPM

AROMATIC HYDROCARBONS (VAPOR PRESSURE = 5)

ACGIH TLV: 50 PPM

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: SE7555000

OSHA PEL100 PPM

ALKYD RESIN

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

Hazards

Effects of Overexposure:NOSE/THROAT IRRITATION. HEADACHE, DIZZINESS, NAUSEA, STAGGERING GAIT, CONFUSION, UNCONSCIOUSNESS.

First Aid

First Aid:IN CASE OF EYE CONTACT, IMMEDIATELY FLUSH W/PLENTY OF WATER FOR AT LEAST 15 MINUTES; CALL A PHYSICIAN. IN CASE OF SKIN CONTACT WASH W/SOAP & WATER. IF IRRITATION OCCURS, CONTACT A PHYSICIAN. IF AFFECT ED BY INHALATION OF VAPOR, REMOVE TO FRESH AIR

Fire Fighting

Flash Point:20-73F (CC)

Lower Limits:1.1%

Upper Limits:14%

Extinguishing Media:FOAM, CO2, DRY CHEMICAL

Fire Fighting Procedures:WEAR SCBA. WATER COOL CONTAINERS PREVENT PRESSURE BUILD UP.

Unusual Fire/Explosion Hazard:FINE MISTS OR SPRAYS MAY BE FLAMMABLE AT TEMPERATURES BELOW THE FLASH POINT.

Accidental Release

Spill Release Procedures:VENTILATE AREA. REMOVE SOURCES OF IGNITION. PREVENT SKIN CONTACT AND BREATHING OF VAR. CONFINE AND REMOVE WITH INERT ABSORBANT.

Handling

Handling and Storage Precautions:OBSERVE LABEL PRECAUTIONS. KEEP AWAY FROM HEAT, SPARKS & FLAME. CLOSE CONTAINER AFTER EACH USEGROUND CONTAINERS WHEN POURING.

Other Precautions:WASH THOROUGHLY AFTER HANDLING & BEFORE EATING OR SMOKING. DON'T STORE ABOVE 120F. DON'T SAND/FLAME CUT/BRAZE OR WELD DRY COING W/OUT A NIOSH/MSHA APPROVED RESP/APPROPRIATE VENTILATION.

Exposure Controls

Respiratory Protection:WEAR A PROPERLY FITTED NIOSH/MSHA APPROVED PAINT SPRAY RESPIRATOR.

Ventilation:PROVIDE VENTILATION TO KEEP BELOW TLV

Protective Gloves:NEOPRENE

Eye Protection:SPLASH GUARDS/SIDE SHIELD

Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:176-426F

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:SLIGHT

Percent Volatiles by Volume:68.0

Stability

Stability Indicator/Materials to Avoid:YES

NONE REASONABLY FORESEEABLE

Hazardous Decomposition Products:CO, CO2, SMOKE

Disposal

Waste Disposal Methods:DON'T ALLOW MATERIAL TO CONTAMINATE GROUND WATER

SYSTEMS. INCINERATE ABSORBED MATERIAL IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REQUIREMENTS. DON'T INCINERATE IN CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.