

548U IMRON POLYURETHANE ENAMEL

MSDS Number

BBNJS

National Stock Number

8010-00F003597

Product Name

548U IMRON POLYURETHANE ENAMEL

Manufacturer

EI DUPONT AUTOMOTIVE PRODS DEPT

Product Identification

Product ID:548U IMRON POLYURETHANE ENAMEL

MSDS Date:02/01/1989

FSC:8010

NIIN:00F003597

MSDS Number: BBNJS

Responsible Party

EI DUPONT/AUTOMOTIVE PRODS DEPT

1007 MARKET ST BRANDYWINE BLDG 3332

WILMINGTON , DE 19898

US

Emergency Phone: (800) 441-3637

Info Phone: (800) 441-7515

Cage: EO478

Contractor

EI DUPONT/AUTOMOTIVE PRODS DEPT

WILMINGTON, DE 19898

US

(800) 441-7515

Cage: EO478

Ingredients

TOLUENE

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 2%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

ETHYL ACETATE

CAS: 141-78-6

RTECS: AH5425000

OSHA PEL1400 MG/CUM

ACGIH TLV: 1400 MG/CUM

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

PROPYLENEGLYCOL MONOMETHYL ETHER ACETATE,

CAS: 108-65-6

RTECS: AI8925000

Fraction By Weight: 44%

LEAD SULFOCHROMATE YELLOW, CHROME YELLOW LIGHT *92-2*

CAS: 1344-37-2

Fraction By Weight: 21%

OSHA PEL0.05 MG/CUM PB

ACGIH TLV: 0.05 MG/CUM CR

2-PROPENOIC ACID 2-METHYL-METHYL ESTER, POLYMER

CAS: 80010-53-3

8.25-11.19

RTECS: 9999999WG

3.5-6

RTECS: 9999999VO

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INGESTION: GASTROINTESTINAL DISTRESS.

INHALATION: NOSE/THROAT IRRITATION, EYE WATERING, HEADACHES,

NAUSEA, DIZZINESS, COORDINATION LOSS, ASTHMA-LIKE REACTIONS

W/SHORTNESS OF BREATH, WHEEZING, COUGH OR LUNG SENSITIZATION.

EYES: IRRITATION OR BURNING. SKIN: IRRITATION W/DISCOMFORT &

DERMATITIS.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:INGESTION: GASTROINTESTINAL DISTRESS.

INHALATION: PERMANENT BRAIN & NERVOUS SYSTEM DAMAGE. EYES:

IRRITATION OR BURNING. SKIN: IRRITATION W/DISCOMFORT & DERMATITIS.

Medical Cond Aggravated by Exposure:LUNG OR BREATHING PROBLEMS

First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. EYES: FLUSH W/PLENTY OF

WATER FOR AT LEAST 15 MINS. SKIN: WASH THOROUGHLY W/SOAP & WATER.

INGESTION: OBTAIN MEDICAL ATTENTION IN ALL CASES.

Fire Fighting

Flash Point Method:CC

Flash Point:20-73F

Lower Limits:0.9%

Upper Limits:23%

Extinguishing Media:WATER SPRAY, FOAM, CO2, DRY CHEMICAL

Fire Fighting Procedures:USE FULL PROTECTIVE EQUIP & SCBA. USE WATER
FROM FOG NOZZLES TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE

BUILD UP.

Unusual Fire/Explosion Hazard:WHEN HEATED ABOVE FLASH POINT, EMITS FLAMMABLE VAPORS, WHEN MIXED W/AIR, CAN BURN/EXPLODE. FINE MISTS/SPRAYS MAY BE FLAMMABLE AT TEMPS BELOW FLASH POINT.

Accidental Release

Spill Release Procedures:VENTILATE AREA. REMOVE SOURCES OF IGNITION. CONFINE & REMOVE W/INERT ABSORBENT. DEACTIVATE ISOCYANATE CONTAINING SPILLS WITH: 20% SURFACTANT (TERGITOL TMN-10) & 80% WATER OR 0-10% AMMONIA, 2-5% DETERGENT, BALANCE WATER. Neutralizing Agent:20% SUFACTANT & 80% WATER OR 0-19% AMMONIA, 2-5% DETERGENT, BALANCE WATER

Handling

Handling and Storage Precautions:OBSERVE LABEL PRECAUTIONS. KEEP AWAY FROM HEAT, SPARKS & FLAME. CLOSE CONTAINER AFTER EACH USE. GROUND CONTAINERS WHEN POURING. DON'T STORE >120F. Other Precautions:DON'T SAND, FLAME CUT, BRAZE OR WELD DRY COATING W/OUT A NIOSH/MSHA APPROVED RESPIRATOR OR APPROPRIATE VENTILATION. DON'T BREATHE VAPORS OR MITS. DON'T PERMIT ANYONE W/OUT PROTECTION IN THE PAINTING A REA. AVOID CONTACT W/SKIN.

Exposure Controls

Respiratory Protection:WEAR A POSITIVE PRESSURE SUPPLIED AIR RESPIRATOR (NIOSH/MSHA TC-19C) WHILE MIXING ACTIVATOR W/ENAMEL, DURING APPLICATION & UNTIL ALL VAPORS & SPRAY MISTS ARE EXHAUSTED. Ventilation:SUFFICIENT VENTILATION IN VOLUME & PATTERN TO KEEP Protective Gloves:NEOPRENE Eye Protection:SPLASH GUARDS OR SIDESHIELDS Other Protective Equipment:COVEALLS Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING & BEFORE EATING OR SMOKING. Supplemental Safety and Health BOILING RANGE: 169-374F. PERCENT VOLATIVE BY WEIGHT: 42.8-64.2%

Chemical Properties

Boiling Pt:B.P. Text:SEE SUPP Vapor Density:>AIR Evaporation Rate & Reference:SLOWER THAN ETHER Solubility in Water:MISCIBLE Percent Volatiles by Volume:61-69%

Stability

Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAME, TEMPS >120F OR OTHER SOURCES OF IGNITION Hazardous Decomposition Products:CO, CO2, SMOKE, OXIDES OF HEAVY METALS

Disposal

Waste Disposal Methods:DON'T ALLOW MATERIAL TO CONTAMINATE GROUND WATER SYSTEMS. INCINERATE ABSORBED MATERIAL IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REQUIREMENTS. DON'T INCINERATE IN CLOSED CONTAINERS. FLAMMABLE LIQUID UN1263

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.