

# **FREON 11 PRESSURIZED**

#### **MSDS Number**

**BBNJW** 

#### **National Stock Number**

6830-00F003606

## **Product Name**

FREON 11 PRESSURIZED

#### Manufacturer

E I DUPONT DE NEMOURS

#### **Product Identification**

Product ID:FREON 11 PRESSURIZED MSDS Date:01/01/1987 FSC:6830 NIIN:00F003606 MSDS Number: BBNJW

# **Responsible Party**

E.I. DUPONT DE NEMOURS/WILMINGTON, DE 19898

Emergency Phone: (800) 441-3637

Cage: 19898

## Contractor

E.I. DUPONT DE NEMOURS & CO., INC.

1635

WILMINGTON, DE 19898

302-773-5676 Cage: 19898

#### **Ingredients**

TRICHLOROFLUOROMETHANE

RTECS: PB1625000

Fraction By Weight: 100% ACGIH TLV: 1000 PPM

NITROGEN

CAS: 7727-37-9 RTECS: QW9700000

Fraction By Weight: 100% ACGIH TLV: ASPHYXIANT; 9192

#### **Hazards**

Effects of Overexposure: INHALATION: VAPOR IS > AIR. LIGHT-HEADEDNESS/GIDDINESS/SHORTNESS OF BREATH/UNCONSCIOUSNESS OR DEATH

# First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR, CALL A PHYSICIAN. SKIN: FLUSH W/WATER. GET MEDICAL ATTENTION IF IRRITATION IS PRESENT. IF BREATHING IS DIFFICULT, GIVE OXYGEN. CONSULT A PHYSICIAN IF NECESSARY. DON'T INDUCE VOMITING.



## **Fire Fighting**

Flash Point:NONE Lower Limits:NONE Upper Limits:NONE

Extinguishing Media: NONFLAMMABLE

Fire Fighting Procedures: SCBA MAY BE REQUIRED IF A SPILL OCCURS. Unusual Fire/Explosion Hazard: CYLINDERS MAY RUPTURE UNDER FIRE

CONDITIONS. DECOMPOSITION MAY OCCUR.

#### **Accidental Release**

Spill Release Procedures: VENTILATE AREA. DON'T FLUSH INTO SEWERS. DIKE SPILL. COLLECT ON ABSORBENT MATERIAL &RANSFER TO STEEL DRUMS FOR RECOVERY OR DISPOSAL.

## Handling

Handling and Storage Precautions: AVOID BREATHING VAPORS AND PROLONGED SKIN EXPOSURE. USE ONLY IN WELL-VENTILATED AREAS.

#### **Exposure Controls**

Respiratory Protection: NO RESPIRATORY PROTECTION IS REQUIRED WHEN USING THIS PRODUCT.

Ventilation:LOCAL EXHAUST AND MECHANICAL

Protective Gloves:BUTYL Eye Protection:GOGGLES Supplemental Safety and Health

# **Chemical Properties**

Boiling Pt:B.P. Text:75F

Vapor Pres:120 Vapor Density:1.48

Evaporation Rate & Reference:0.1

Solubility in Water: 0.1%

Appearance and Odor: CLEAR, SLIGHT ETHEREAL ODOR.

Percent Volatiles by Volume:100%

## Stability

Stability Indicator/Materials to Avoid:YES ALKALI OR ALKALINE EARTH METALS - POWDERED AL, ZN, BE, ETC. Stability Condition to Avoid:HOWEVER, AVOID OPEN FLAMES AND HIGH TEMPERATURES

Hazardous Decomposition Products: HYDROCHLORIC/HYDROFLUORIC ACIDS POSSIBLE CARBONYL HALIDES.

## **Disposal**

Waste Disposal Methods: COMPLY WITH FEDERAL, STATE, AND LOCAL REGULATIONS ON REPORTING RELEASES. RECLAIM BY DISTILLATION OR REMOVE TO A PERMITTED WASTE DISPOSAL FACILITY.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.