https://msdsreport.com/msds/BBNKM

# **RP 802 GREEN SEALER**

# **MSDS Number**

BBNKM

# **National Stock Number**

8010-00F003620

### **Product Name**

**RP 802 GREEN SEALER** 

### Manufacturer

CIBA GEIGY CORP

# **Product Identification**

Product ID:RP 802 GREEN SEALER MSDS Date:01/01/1987 FSC:8010 NIIN:00F003620 MSDS Number: BBNKM

# **Responsible Party**

CIBA-GEIGY CORPORATION/EAST LANSING, MI 48823

Emergency Phone: (517) 351-5900

Cage: CIBAG

# Contractor

CIBA-GEIGY CORPORATION, FURANE PRODUCTS

LOS ANGELES, CA 90039

US

818-247-6210

Cage: CIBAG

### Ingredients

METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III) CAS: 78-93-3 RTECS: EL6475000 OSHA PEL200 PPM/300 STEL ACGIH TLV: 200 PPM/300STEL 9192 EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

TOLUENE (SARA III) CAS: 108-88-3 RTECS: XS5250000 OSHA PEL200 PPM/150 STEL ACGIH TLV: 50 PPM; 9293 EPA Report Quantity: 1000 LBS DOT Report Quantity: 1000 LBS



https://msdsreport.com/msds/BBNKM

•

CAS: 7429-90-5

RTECS: BD0330000 OSHA PEL15MG/M3 DUST/5 FUME ACGIH TLV: 10MG/M3 DUST; 9192

GREEN PIGMENT RTECS: BD1430000

METHYL ISOBUTYL KETONE (SARA III)

CAS: 108-10-1

RTECS: SA9275000

OSHA PEL100 PPM/75 STEL

ACGIH TLV: 50 PPM/75 STEL; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

### Hazards

Effects of Overexposure:SKIN/EYE IRRITATION. INHALATION: HEADACHE/DIZZINESS/STAGGERING GAIT/CONFUSION/UNCONSCIOUSNESS/COMA

### **First Aid**

First Aid:EYES: FLUSH W/WATER FOR AT LEAST 15 MINUTES. CALL A PHYSICIAN. SKIN: WASH W/SOAP & WATER. REMOVE LAUNDER BEFORE RE-USE. INGESTION: IF CONSCIOUS, GIVE PLENTY OF WATER. DON'T INDUCE VOMITING. INHALATION : REMOVE TO FRESH AIR. GIVEN OXYGEN. CALL A PHYS

# **Fire Fighting**

Flash Point:37F (TCC) Extinguishing Media:CO2, DRY CHEMICAL, FOAM, WATER Fire Fighting Procedures:USE SCBA. WATER COOL CONTAINERS. Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

# **Accidental Release**

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. REMOVE SPILLAGE BY ABSORBING IN ABSORBANT MATERIAL.

# Handling

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS AND FLAME. KEEP CONTAINER CLOSED. USE WITH ADEQUATE VENTILATION. D'T GET IN EYES, SKIN OR CLOTHING. Other Precautions:AVOID BREATHING VAPOR OR MIST. WASH THOROUGHLY AFTER HANDLING. CAUSES SKIN AND EYES IRRITATION.

# **Exposure Controls**

Respiratory Protection:USE NIOSH APPROVED ORGANIC VAPOR CARTRIDGE RESPIRATOR Ventilation:GENERAL MECHANICAL/LOCAL EXHAUST Protective Gloves:IMPERMEABLE Eye Protection:GOGGLES Supplemental Safety and Health

# **Chemical Properties**

Boiling Pt:B.P. Text:170-240F Vapor Pres:70 Spec Gravity:0.91



#### Solubility in Water:NIL

Appearance and Odor:GREEN LIQUID, W/CHARACTERISTIC KETONE ODOR. Percent Volatiles by Volume:87%

# Stability

Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:STORAGE ABOVE 100F, MOISTURE. Hazardous Decomposition Products:COMBUSTION MAY FORM TOXIC MATERIALS, SUCH AS CO2, CO.

#### Disposal

Waste Disposal Methods:CONSULT QUALIFIED LOCAL OR CORPORATE PERSONNEL FOR METHOD THAT WILL COMPLY WITH LOCAL, STATE AND FEDERAL HEALTH AND ENVIRONMENTAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.