

## **BR 53 PRIMER 5% SOLIDS**

### **MSDS Number**

BBNLW

### **National Stock Number**

8010-00F003651

### **Product Name**

BR 53 PRIMER 5% SOLIDS

### **Manufacturer**

AMERICAN CYANAMID COMPANY

### **Product Identification**

Product ID: BR 53 PRIMER 5% SOLIDS

MSDS Date: 08/24/1989

FSC: 8010

NIIN: 00F003651

MSDS Number: BBNLW

### **Responsible Party**

AMERICAN CYANAMID COMPANY

1 CYANAMID PLAZA

WAYNE, NJ 07470

Emergency Phone: (201) 835-3100

Info Phone: (201) 835-3100

Preparer: MARVIN A FRIEDMAN

Cage: 70361

### **Contractor**

AMERICAN CYANAMID CO

CLIFTON, NJ 07015

US

973-683-2000

Cage: 70361

### **Ingredients**

METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight: 60.13%

OSHA PEL200 PPM/300 STEL

ACGIH TLV: 200 PPM/300 STEL 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

TETRAHYDROFURAN (SARA III)

CAS: 109-99-9

RTECS: LU5950000

Fraction By Weight: 19.1%

OSHA PEL200 PPM/250 STEL  
ACGIH TLV: 200 PPM/250STEL;9192  
EPA Report Quantity: 1000 LBS  
DOT Report Quantity: 1000 LBS

DIACETONE ALCOHOL (4-HYDROXY-4-METHYL-2-PENTANONE)  
CAS: 123-42-2  
RTECS: SA9100000  
Fraction By Weight: 14.35%  
OSHA PEL50 PPM  
ACGIH TLV: 50 PPM; 9192

METHYL ALCOHOL (METHANOL) (SARA III)  
CAS: 67-56-1  
RTECS: PC1400000  
Fraction By Weight: 1.42%  
OSHA PELS,200PPM/250STEL  
ACGIH TLV: S,200PPM/250STEL; 93  
EPA Report Quantity: 5000 LBS  
DOT Report Quantity: 5000 LBS

CALCIUM CHROMATE (SARA III)  
CAS: 13765-19-0  
RTECS: GB2750000  
Fraction By Weight: 0.68%  
OSHA PEL0.05 MG CR/M3  
ACGIH TLV: 0.001 MG/M3;A2, 9394  
EPA Report Quantity: 10 LBS  
DOT Report Quantity: 10 LBS

## Hazards

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:INHALATION: IRRITATION OR INJURY OF THE RESPIRATORY TRACT, HEADACHE, NAUSEA, DIZZINESS, STAGGERING GAIT, SLEEPINESS, CORROSION OF THE SCEPTUM OF THE NOSE, HARMFUL. SKIN: LOW-HEALING LESIONS & ALLERGIC REACTIONS & IRRITATION. EYES: DAMAGE, BLINDNESS, IRRITATION.  
Explanation of Carcinogenicity:CALCIUM CHROMATE IS A CONSIDERED TO BE A1 CARCINOGEN BY RECOMMENDED LIMIT.  
Effects of Overexposure:INHALATION: RESPIRATORY IRRITATION, CENTRAL NERVOUS SYSTEM DEPRESSION, HEADACHE, NAUSEA, DIZZINESS, STAGGERING GAIT, SLEEPINESS, CORROSION OF THE SCEPTUM OF THE NOSE, HARMFUL. EYES: DAMAGE, IRRITATION , BLINDNESS. SKIN: IRRITATION, SLOW-HEALING LESIONS & ALLERGIC REACTIONS.

## First Aid

First Aid:SKIN: WASH AFFECTED AREAS W/SOAP & WATER. EYES: IRRIGATE W/PLENTY OF WATER FOR 15 MINS. INHALATION: REMOVE FROM EXPOSURE. ADMINISTER OXYGEN IF THERE IS DIFFICULTY IN BREATHING. OBTAIN

MEDICAL ATTENTION IN ALL CASES.

## Fire Fighting

Flash Point Method:CC  
Flash Point:15F  
Lower Limits:1.8%  
Upper Limits:10.0%  
Extinguishing Media:USE WATER SPRAY, ALCOHOL FOAM, CO2 OR DRY CHEMICAL  
Fire Fighting Procedures:WATER SPRAY MAY BE INEFFECTIVE. USE WATER TO KEEP CONTAINERS COOL. WEAR SELF-CONTAINED BREATHING APPARATUS & FULL PROTECTIVE CLOTHING.  
Unusual Fire/Explosion Hazard:AUTOIGNITION TEMP: 960F. VAPOR MAY CAUSE FLASH FIRE. DANGER: EXTREMELY FLAMMABLE LIQUID & VAPOR.

## Accidental Release

Spill Release Procedures:COVER SPILLS W/SOME INERT ABSORBENT MATERIAL; SWEEP UP & PLACE IN A WASTE DISPOSAL CONTAINER. FLUSH AREA W/WATER. REMOVE SOURCES OF IGNITION. REPORTABLE QUANTITY OF PRODUCT) IS 8,141 LBS-61.4%) (5,294 LBS-18.9%).

## Handling

Handling and Storage Precautions:DON'T USE AIR PRESSURE OR APPLY HEAT W/OPEN FLAME TO REMOVE CONTENTS OF CONTAINER. DON'T USE FOR OTHER PURPOSES. WASH THOROUGHLY AFTER HANDLING.  
Other Precautions:VAPOR PRESSURE OF ORGANIC LIQUIDS INCREASE W/TEMPERATURE. AFTER EMPTIED, CONTAINER MAY RETAIN SOLID, LIQUID/VAPOR RESIDUES. DON'T CUT, PUNCTURE, TORCH, OR WELD ON OR NEAR EMPTIED CONTAINER. AVOID BREATHING VAPOR, CONTACT W/SKIN & EYES.

## Exposure Controls

Respiratory Protection:WEAR NIOSH APPROVED POSITIVE PRESSURE SELF-CONTAINED RESPIRATOR.  
Ventilation:USE MECHANICAL EXHAUST VENTILATION WHEN HEAT-CURING ADHESIVE.  
Protective Gloves:IMPERVIOUS  
Eye Protection:CHEMICAL SPLASH PROOF GOGGLES/FACESHIELD  
Other Protective Equipment:EYEWASH EQUIPMENT, SAFETY SHOWER, APRON, PROTECTIVE CLOTHING, IMPERVIOUS BOOTS, WORKPANTS, DISPOSABLE COVERALLS.  
Work Hygienic Practices:REMOVE CONTAMINATED CLOTHING & SHOES BEFORE REUSE. DON'T REUSE CONTAMINATED CLOTHING W/O LAUNDERING.  
Supplemental Safety and Health  
BEFORE EATING, DRINKING, OR SMOKING, WASH FACE & HANDS W/SOAP & WATER. CUTTING, GRINDING, OR SANDING OF PARTS FABRICATED AFTER CURING OF THIS MATERIAL MAY CREATE RESPIRABLE DUST PARTICLES.

## Chemical Properties

Boiling Pt:B.P. Text: 174F  
Vapor Pres:0.85  
Vapor Density:2.42  
Spec Gravity:0.85  
Solubility in Water:NEGLIGIBLE  
Appearance and Odor:YELLOW LIQUID; METHYL ETHYL KETONE ODOR.  
Percent Volatiles by Volume:95%

## Stability

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZING AGENTS & ACIDS  
Stability Condition to Avoid:STORE AT OR STATIC SPARK, FLAMES, SOURCE OF HEAT, SOURCES OF IGNITION.  
Hazardous Decomposition Products:CO, CO2, CHROMIUM OXIDE, AMMONIA & OXIDES OF NITROGEN.  
Conditions to Avoid Polymerization:POLYMERIZATION MAY OCCUR SLOWLY AT TEMPERATURE.

## Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE W/LOCAL, STATE, &

FEDERAL REGULATIONS. FLAMMABLE LIQUIDS, UN1993.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.