

KRYLON 1307 BATTERY PROTECTOR

MSDS Number

BBNNN

National Stock Number

8010-00F003683

Product Name

KRYLON 1307 BATTERY PROTECTOR

Manufacturer

BORDEN INC

Product Identification

Product ID:KRYLON 1307 BATTERY PROTECTOR

MSDS Date:01/01/1987

FSC:8010

NIIN:00F003683

MSDS Number: BBNNN

Responsible Party

BORDEN INC/COLUMBUS, OHIO 43215

Emergency Phone: (614) 457-5200

Cage: EO732

Contractor

KRYLON PRODUCTS

SOLON, OH 44139

US

800-832-2541/216-566-2917

Cage: 87187

Ingredients

ACETONE (SARA III)

CAS: 67-64-1

RTECS: AL3150000

Fraction By Weight: 11.2%

OSHA PEL1000PPM

ACGIH TLV: 750PPM/1000STEL;9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

PROPANE

CAS: 74-98-6

RTECS: TX2275000

Fraction By Weight: 12.9%

OSHA PEL1000 PPM

ACGIH TLV: ASPHYXIAN; 9192

N-HEPTANE

CAS: 142-82-5

RTECS: MI7700000

Fraction By Weight: 22.4%

OSHA PEL500 PPM/500 STEL

ACGIH TLV: 400 PPM/500STEL;9293

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 15.8%

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 11.1%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

Hazards

Effects of Overexposure:HEADACHE, DIZZINESS, NAUSEA, VOMITING, UNCONSCIOUS AND EVEN ASPHYXIATION. SKIN/EYES: IRRITATION.

First Aid

First Aid:INTERNAL: IF SWALLOWED, DON'T INDUCE VOMITING. INHALATION: REMOVE TO FRESH AIR. SKIN: FLUSH W/WATER. EYE: FLUSH W/WATER FOR AT LEAST 15 MINUTES. CALL A PHYSICIAN.

Fire Fighting

Fire Fighting Procedures:EXPOSURE TO HIGH TEMP MAY CAUSE BURSTING. Unusual Fire/Explosion Hazard:DON'T PUNCTURE OR INCINERATE CONTAINER. DON'T SPRAY NEAR OPEN FLAME.

Accidental Release

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. SOAK UP WITH ABSORBENT MATERIAL AND REMOVE TO A CHEMAL DISPOSAL AREA. PREVENT ENTRY INTO NATURAL BODIES OF WATER.

Handling

Handling and Storage Precautions:INHALATION: AVOID BREATHING VAPOR OR MIST. USE WITH ADEQUATE VENTILATION. SKIN/EYES: AVOID CONCT WITH SKIN/EYES.

Other Precautions:DON'T STORE AT TEMPERATURES OVER >120F.

Exposure Controls

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATORY PROTECTION IF >TLV

Ventilation:PROVIDE VENTILATION TO KEEP BELOW TLV.

Protective Gloves:IMPERVIOUS
Eye Protection:GOGGLES/FACESHIELD/GLASSE
Other Protective Equipment:WEARING SAFETY GLASSES/SAFETY SHOES/HARD
HATS/SUIT CLOTHING.
Supplemental Safety and Health
ALSO CONTAINS: ISOBUTANE (TZ4300000) 17.1%, HEAVY AROMATIC SOLVENT
NAPHTHA (PETROLEUM) (DE3030000) 2.1%.

Chemical Properties

Vapor Pres:60
Vapor Density:>AIR
Spec Gravity:Evaporation Rate & Reference:FASTER THAN BU AC
Solubility in Water:SLIGHT
Percent Volatiles by Volume:94%

Stability

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:AVOID RADIATORS/STOVES/DIRECT SUNLIGHT OR
OTHER HEAT SOURCE.
Hazardous Decomposition Products:CO, CO2.

Disposal

Waste Disposal Methods:DISPOSE OF ACCORDING TO LOCAL, STATE AND FEDERAL
REQUIREMENTS. EMPTY CONTAINER: MAY CONTAIN EXPLOSIVE VAPORS. DON'T
CUT, PUNCTURE OR WELD ON OR NEARBY.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.