

HYTHANE 4648A, EXTRA DEEP BASE, PART A

MSDS Number

BBNQL

National Stock Number

8010-00F003722

Product Name

HYTHANE 4648A, EXTRA DEEP BASE, PART A

Manufacturer

PORTER PAINT CO

Product Identification

Product ID:HYTHANE 4648A, EXTRA DEEP BASE, PART A

MSDS Date:01/01/1987

FSC:8010

NIIN:00F003722

MSDS Number: BBNQL

Responsible Party

PORTER PAINT CO/LOUISVILLE, KY 40203

Emergency Phone: (502) 588-9200

Cage: EO738

Contractor

PORTER PAINT CO/LOUISVILLE, KY 40203

LOUISVILLE, KY 40203-1714

US

502-588-9651

Cage: EO738

Ingredients

METHYL N-AMYL KETONE

CAS: 110-43-0

RTECS: MJ5075000

Fraction By Weight: 20%

OSHA PEL100 PPM

ACGIH TLV: 50 PPM; 9192

2-ETHOXYETHYL ACETATE (CELLOSOLVE ACETATE) (EGEEA)

CAS: 111-15-9

RTECS: KK8225000

Fraction By Weight: 15%

OSHA PELS,100 PPM

ACGIH TLV: S, 5 PPM; 9192

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: SE7555000

Fraction By Weight: 5%

OSHA PEL100 PPM

ETHYL BENZENE (SARA III)

CAS: 100-41-4

RTECS: DA0700000

Fraction By Weight: 5%

OSHA PEL100 PPM/125 STEL

ACGIH TLV: 100 PPM/125STEL 9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

Hazards

Effects of Overexposure: INHALATION: VAPORS ARE IRRITATING TO NOSE/THROAT/NAUSEA/DIZZINESS/VOMITING.

First Aid

First Aid: VAPORS: REMOVE FROM EXPOSURE. KEEP WARM/QUIET. NOTIFY PHYSICIAN. EYES: FLUSH WITH WATER FOR AT LEAST 15 MINUTES. TAKE A PHYSICIAN FOR MEDICAL TREATMENT. SKIN: WASH AFFECTED AREAS WITH WATER. REMOVE CONTAMINATED CLOTHING.

Fire Fighting

Flash Point: 79F

Lower Limits: 0.75

Extinguishing Media: FOAM, CO2, DRY CHEMICAL

Fire Fighting Procedures: WATER SPRAY TO COOL CONTAINERS. WEAR SCBA. Unusual Fire/Explosion Hazard: KEEP CONTAINERS TIGHTLY CLOSED. CLOSED CONTAINER MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

Accidental Release

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION (FLAMES/HOT SURFACES/ELECTRICAL/STATIC/FRICTIONAL SPARK). AVOID BREATHING VAPORS, WEAR APPROVED (NIOSH/MHSA) RESPIRATOR/VENTILATION. REMOVE WITH INERT ABSORBENT SUCH AS SAND, KITTY LITTER/USE NONSPARKING TOOLS

Handling

Handling and Storage Precautions: SECURE CLOSURES/KEEP CONTAINERS UPRIGHT TO PREVENT LEAKAGE. STORE LARGE QUANTITIES ONLY IN BUILDING DESIGNED TO COMPLY WITH OSHA.

Other Precautions: DON'T STORE ABOVE 120F. DON'T TAKE INTERNALLY. BEFORE SMOKING OR EATING, WASH HANDS THOROUGHLY. DON'T STORE OR USE NEAR HEATSPARKS OR OPEN FLAME. AVOID BREATHING VAPORS OR SPRAY MIST.

Exposure Controls

Respiratory Protection: IN CONFINED AREAS, USE NIOSH/MHSA AIR-LINE RESPIRATOR OR HOOD.

Ventilation: PROVIDE LOCAL EXHAUST VENTILATION TO KEEP BELOW TLV/LEL

Protective Gloves: RUBBER/NEOPRENE

Eye Protection: SAFETY EYEWEAR/SIDESHIELD

Other Protective Equipment: AS NEEDED-USE BODY PROTECTION, SUCH AS RUBBER APRON, ETC.

Supplemental Safety and Health

USES 4646B, CONVERTER FOR ALL PART A'S. IF THIS PRODUCT IS TINTED WITH A LEAD-CONTAINING COLORANT, IT WILL BE SO STATED ON THE LABEL OF THE PAINT CAN. MSDS DATED 25 NOV 85.

Chemical Properties

Boiling Pt: B.P. Text: 270-400F

Vapor Density: >AIR
Evaporation Rate & Reference: FASTER THAN ETHER
Percent Volatiles by Volume: 64%

Stability

Stability Indicator/Materials to Avoid: YES
NONE
Hazardous Decomposition Products: FUMES MAY PRODUCE CO₂/CO/OXIDES OF NITROGEN.

Disposal

Waste Disposal Methods: DISPOSE OF IN A SAFE MANNER IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS THAT APPLY TO INCINERATION OR SECURE LANDFILL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.