
KRYLON FLUORESCENT SPRAY PAINT, 3106

MSDS Number

BBNQV

National Stock Number

8010-00F003730

Product Name

KRYLON FLUORESCENT SPRAY PAINT, 3106

Manufacturer

BORDEN INC

Product Identification

Product ID:KRYLON FLUORESCENT SPRAY PAINT, 3106

MSDS Date:01/01/1987

FSC:8010

NIIN:00F003730

MSDS Number: BBNQV

Responsible Party

BORDEN, INC/COLUMBUS, OHIO 43215

Emergency Phone: (614) 457-5200

Cage: EO431

Contractor

KRYLON PRODUCTS

SOLON, OH 44139

US

800-832-2541/216-566-2917

Cage: 87187

Ingredients

PROPANE

CAS: 74-98-6

RTECS: TX2275000

Fraction By Weight: 12.0%

OSHA PEL1000 PPM

ACGIH TLV: ASPHYXIAN; 9192

ISOBUTANE

CAS: 75-28-5

RTECS: TZ4300000

Fraction By Weight: 16.0%

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 12.0%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293
EPA Report Quantity: 1000 LBS
DOT Report Quantity: 1000 LBS

HEXANE (N-HEXANE)
CAS: 110-54-3
RTECS: MN9275000
Fraction By Weight: 18.0%
OSHA PEL500 PPM
ACGIH TLV: 50 PPM; 9293
EPA Report Quantity: 1 LB
DOT Report Quantity: 1 LB

N-HEPTANE
CAS: 142-82-5
RTECS: MI7700000
Fraction By Weight: 17.0%
OSHA PEL500 PPM/500 STEL
ACGIH TLV: 400 PPM/500STEL;9293

Hazards

Effects of Overexposure:INHALATION: MAY BE HARMFUL IF INHALED. LIQUID OR CAUSE IRRITATION NOSE, THROAT AND LUNGS.

First Aid

First Aid:INGESTION: IF SWALLOWED, DON'T INDUCE VOMITING. INHALATION: REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT, GIVE OXYGEN. SKIN: FLUSH W/WATER. EYE: FLUSH W/WATER FOR AT LEAST 15 MINUTES. CALL A PHYSICI AN.

Fire Fighting

Extinguishing Media:USE DRY CHEMICAL, FOAM OR CO2
Fire Fighting Procedures:WATER MAY BE INEFFECTIVE. WATER COOL CONTAINERS.
Unusual Fire/Explosion Hazard:EXPOSURE TO HIGH TEMP CAUSE BURSTING. DON'T PUNCTURE OR INCINERATE CONTAINER. DON'T SPRAY NEAR FLAME

Accidental Release

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. SOAK UP WITH ABSORBENT MATERIAL AND REMOVE TO A CHEMAL DISPOSAL AREA. PREVENT ENTRY INTO NATURAL BODIES OF WATER.

Handling

Handling and Storage Precautions:DON'T STORE AT TEMPERATURES >120F.

Exposure Controls

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATORY PROTECTION EQUIPMENT IF >TLV.
Ventilation:PROVIDE VENTILATION TO KEEP BELOW TLV.
Protective Gloves:IMPERVIOUS
Eye Protection:GOGGLES
Other Protective Equipment:WEAR IMPERVIOUS GLOVES AS REQUIRED TO PREVENT SKIN CONTACT.
Supplemental Safety and Health
ALSO CONTAINS: VM&P NAPHTHA (SE7555000) 300 PPM, 8%.

Chemical Properties

Vapor Pres:50
Vapor Density:>AIR
Spec Gravity:Evaporation Rate & Reference:FASTER THAN BU AC
Solubility in Water:SLIGHT
Percent Volatiles by Volume:83%

Stability

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:AVOID RADIATORS/STOVES/DIRECT SUNLIGHT OR
OTHER HEAT SOURCE.
Hazardous Decomposition Products:CO, CO2.

Disposal

Waste Disposal Methods:DISPOSE OF ACCORDING TO LOCAL, STATE AND FEDERAL
REQUIREMENTS. EMPTY CONTAINER: MAY CONTAIN EXPLOSIVE VAPORS. DON'T
CUT, PUNCTURE OR WELD ON OR NEARBY. INCINERATION WILL CAUSE
CONTAINER TO BURST VIOLE NTLY.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.