

## **KRYLON FLUORESCENT SPRAY PAINT, 3107**

### **MSDS Number**

BBNQW

### **National Stock Number**

8010-00F003731

### **Product Name**

KRYLON FLUORESCENT SPRAY PAINT, 3107

### **Manufacturer**

BORDEN INC

### **Product Identification**

Product ID:KRYLON FLUORESCENT SPRAY PAINT, 3107

MSDS Date:01/01/1987

FSC:8010

NIIN:00F003731

MSDS Number: BBNQW

### **Responsible Party**

BORDEN, INC/COLUMBUS, OHIO 43215

Emergency Phone: (614) 457-5200

Cage: EO431

### **Contractor**

KRYLON PRODUCTS

SOLON, OH 44139

US

800-832-2541/216-566-2917

Cage: 87187

### **Ingredients**

PROPANE

CAS: 74-98-6

RTECS: TX2275000

Fraction By Weight: 12.0%

OSHA PEL1000 PPM

ACGIH TLV: ASPHYXIAN; 9192

ISOBUTANE

CAS: 75-28-5

RTECS: TZ4300000

Fraction By Weight: 16.0%

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 12.0%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293  
EPA Report Quantity: 1000 LBS  
DOT Report Quantity: 1000 LBS

HEXANE (N-HEXANE)  
CAS: 110-54-3  
RTECS: MN9275000  
Fraction By Weight: 18.0%  
OSHA PEL500 PPM  
ACGIH TLV: 50 PPM; 9293  
EPA Report Quantity: 1 LB  
DOT Report Quantity: 1 LB

N-HEPTANE  
CAS: 142-82-5  
RTECS: MI7700000  
Fraction By Weight: 17.0%  
OSHA PEL500 PPM/500 STEL  
ACGIH TLV: 400 PPM/500STEL;9293

## Hazards

Effects of Overexposure:INHALATION: MAY BE HARMFUL IF INHALED. LIQUID OR CAUSE IRRITATION NOSE, THROAT AND LUNGS.

## First Aid

First Aid:INGESTION: IF SWALLOWED, DON'T INDUCE VOMITING. INHALATION: REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT, GIVE OXYGEN. SKIN: FLUSH W/WATER. EYE: FLUSH W/WATER FOR AT LEAST 15 MINUTES. CALL A PHYSICI AN.

## Fire Fighting

Extinguishing Media:USE DRY CHEMICAL, FOAM OR CO2  
Fire Fighting Procedures:WATER MAY BE INEFFECTIVE. WATER COOL CONTAINERS.  
Unusual Fire/Explosion Hazard:EXPOSURE TO HIGH TEMP CAUSE BURSTING. DON'T PUNCTURE OR INCINERATE CONTAINER. DON'T SPRAY NEAR FLAME

## Accidental Release

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. SOAK UP WITH ABSORBENT MATERIAL AND REMOVE TO A CHEMAL DISPOSAL AREA. PREVENT ENTRY INTO NATURAL BODIES OF WATER.

## Handling

Handling and Storage Precautions:DON'T STORE AT TEMPERATURES >120F.

## Exposure Controls

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATORY PROTECTION EQUIPMENT IF >TLV.  
Ventilation:PROVIDE VENTILATION TO KEEP BELOW TLV.  
Protective Gloves:IMPERVIOUS  
Eye Protection:GOGGLES  
Other Protective Equipment:WEAR IMPERVIOUS GLOVES AS REQUIRED TO PREVENT SKIN CONTACT.  
Supplemental Safety and Health  
ALSO CONTAINS: VM&P NAPHTHA (SE7555000) 300 PPM, 8%.

## Chemical Properties

Vapor Pres:50  
Vapor Density:>AIR  
Spec Gravity:Evaporation Rate & Reference:FASTER THAN BU AC  
Solubility in Water:SLIGHT  
Percent Volatiles by Volume:83%

## Stability

Stability Indicator/Materials to Avoid:YES  
Stability Condition to Avoid:AVOID RADIATORS/STOVES/DIRECT SUNLIGHT OR  
OTHER HEAT SOURCE.  
Hazardous Decomposition Products:CO, CO2.

## Disposal

Waste Disposal Methods:DISPOSE OF ACCORDING TO LOCAL, STATE AND FEDERAL  
REQUIREMENTS. EMPTY CONTAINER: MAY CONTAIN EXPLOSIVE VAPORS. DON'T  
CUT, PUNCTURE OR WELD ON OR NEARBY. INCINERATION WILL CAUSE  
CONTAINER TO BURST VIOLE NTLY.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.