

KRYLON HIGH HEAT SPRAY PAINT 1618 BLACK

MSDS Number

BBNQY

National Stock Number

8010-00F003733

Product Name

KRYLON HIGH HEAT SPRAY PAINT 1618 BLACK

Manufacturer

BORDEN INC

Product Identification

Product ID:KRYLON HIGH HEAT SPRAY PAINT 1618 BLACK

MSDS Date:01/01/1987

FSC:8010

NIIN:00F003733

MSDS Number: BBNQY

Responsible Party

BORDEN INC/COLUMBUS, OHIO 43215

Emergency Phone: (614) 457-5200

Cage: EO732

Contractor

KRYLON PRODUCTS

SOLON, OH 44139

US

800-832-2541/216-566-2917

Cage: 87187

Ingredients

ACETONE (SARA III)

CAS: 67-64-1

RTECS: AL3150000

Fraction By Weight: 37%

OSHA PEL1000PPM

ACGIH TLV: 750PPM/1000STEL;9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

PROPANE

CAS: 74-98-6

RTECS: TX2275000

Fraction By Weight: 18%

OSHA PEL1000 PPM

ACGIH TLV: ASPHYXIAANT; 9192

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 36%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

Hazards

Effects of Overexposure: INHALATION: MAY BE HARMFUL IF INHALED. LIQUID OR VAPOR CAN CAUSE IRRITATION OF NOSE/THROAT/LUNGS.

First Aid

First Aid: INGESTION: IF SWALLOWED, DON'T INDUCE VOMITING. INHALATION: REMOVE TO FRESH AIR. IF BREATHING IS DIFFICULT, GIVE OXYGEN. SKIN: FLUSH W/WATER. EYE: FLUSH W/WATER FOR AT LEAST 15 MINUTES. CALL A PHYSICIAN.

Fire Fighting

Extinguishing Media: USE DRY CHEMICAL, FOAM OR CO2, WATER

Fire Fighting Procedures: WATER MAY BE INEFFECTIVE. WATER COOL CONTAINERS.

Unusual Fire/Explosion Hazard: EXPOSURE TO HIGH TEMP CAUSE BURSTING. DON'T PUNCTURE OR INCINERATE CONTAINER. DON'T SPRAY NEAR FLAME

Accidental Release

Spill Release Procedures: ELIMINATE ALL IGNITION SOURCES. SOAK UP WITH ABSORBENT MATERIAL AND REMOVE TO A CHEMICAL DISPOSAL AREA. PREVENT ENTRY INTO NATURAL BODIES OF WATER.

Handling

Handling and Storage Precautions: DON'T STORE AT TEMPERATURES >120F.

Exposure Controls

Respiratory Protection: NIOSH/MSHA APPROVED RESPIRATORY PROTECTION IF >TLV.

Ventilation: PROVIDE VENTILATION TO KEEP BELOW TLV.

Protective Gloves: IMPERVIOUS

Eye Protection: GOGGLES

Other Protective Equipment: WEAR IMPERVIOUS GLOVES AS REQUIRED TO PREVENT SKIN CONTACT.

Supplemental Safety and Health

Chemical Properties

Vapor Pressure: 60

Vapor Density: >AIR

Specific Gravity: Evaporation Rate & Reference: FASTER THAN BUTYL AC

Solubility in Water: SLIGHT

Appearance and Odor: WHITE

Percent Volatiles by Volume: 85%

Stability

Stability Indicator/Materials to Avoid: YES

Stability Condition to Avoid: AVOID RADIATORS/STOVES/DIRECT SUNLIGHT OR OTHER HEAT SOURCE.

Hazardous Decomposition Products: CO, CO2.

Disposal

Waste Disposal Methods: DISPOSE OF ACCORDING TO LOCAL, STATE AND FEDERAL REQUIREMENTS. EMPTY CONTAINER: MAY CONTAIN EXPLOSIVE VAPORS. DON'T CUT, PUNCTURE OR WELD ON OR NEARBY. INCINERATION WILL CAUSE CONTAINER TO BURSTING VIOLENTLY.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.