

NEW COLOR HORIZONS 470/473/1020/1030

MSDS Number

BBNRD

National Stock Number

8010-00F003737

Product Name

NEW COLOR HORIZONS 470/473/1020/1030

Manufacturer

RUST OLEUM CORP

Product Identification

Product ID:NEW COLOR HORIZONS 470/473/1020/1030

MSDS Date:01/01/1987

FSC:8010

NIIN:00F003737

MSDS Number: BBNRD

Responsible Party

RUST-OLEUM CORP/VERNON HILLS, IL 60061

Emergency Phone: (312) 367-7700

Cage: 08882

Contractor

RUST-OLEUM CORP

VERNON HILLS, IL 60061-1583

US

847-367-7700

Cage: 08882

Ingredients

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: SE7555000

Fraction By Weight: 50%

OSHA PEL100 PPM

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: SE7555000

Fraction By Weight: 10%

OSHA PEL100 PPM

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 2%

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

Hazards

Effects of Overexposure:HEADACHE, DIZZINESS, STAGGERING GAIT, CONFUSION, UNCONSCIOUSNESS OR COMA.

First Aid

First Aid:FUMES: REMOVE FROM EXPOSURE, RESTORE BREATHING/NOTIFY A PHYSICIAN. EYES: FLUSH WITH WATER FOR AT LEAST 15 MINUTES. NOTIFY A PHYSICIAN. SKIN: WASH AFFECTED AREA W/SOAP & WATER. REMOVE CONTAMINATED CLOTHING.

Fire Fighting

Flash Point:104F (TOC)

Lower Limits:0.9

Extinguishing Media:CO2, DRY CHEMICAL OR FOAM

Fire Fighting Procedures:WEAR SCBA. WATER COOL CONTAINERS TO PREVENT PRESS. BUILD-UP.

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION, VENTILATE AREA AND REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

Handling

Handling and Storage Precautions:DON'T STORE ABOVE 120F. GROUND CONTAINERS WHEN POURING. STORE LARGE QUANTITIES IN BUILDING DESIGNED FOR NFPA CLASS II FLAMMABLE LIQUIDS.

Other Precautions:DON'T TAKE INTERNALLY. EMPTY CONTAINERS MAY BE HAZARDOUS.

Exposure Controls

Respiratory Protection:IN CONFINED AREA: USE B OR M APPROVED AIR LINE TYPE RESP OR HOODS

Ventilation:PROVIDE LOCAL EXHAUST VENTILATION TO KEEP BELOW TLV/LEL.

Protective Gloves:RUBBER

Eye Protection:SAFETY EYEWEAR

Supplemental Safety and Health

WT/GAL: 7.8-8.0 LBS. THESE METALLIC TOPCOATS _

Chemical Properties

Boiling Pt:B.P. Text:245-386F

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:68%

Stability

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

Hazardous Decomposition Products:CO AND CO2

Disposal

Waste Disposal Methods:DISPOSE OF ACCORDING TO LOCAL, STATE AND FEDERAL REGULATIONS. DON'T INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their particular situation.