



HEAVY DUTY EPOXY TOPCOATS-VISTA GREEN/9335

MSDS Number

BBNRS

National Stock Number

8010-00F003750

Product Name

HEAVY DUTY EPOXY TOPCOATS-VISTA GREEN/9335

Manufacturer

RUST OLEUM CORP

Product Identification

Product ID:HEAVY DUTY EPOXY TOPCOATS-VISTA GREEN/9335

MSDS Date:01/01/1987

FSC:8010

NIIN:00F003750

MSDS Number: BBNRS

Responsible Party

RUST-OLEUM CORP/VERNON HILLS, IL 60061

Emergency Phone: (312) 367-7700

Cage: 08882

Contractor

RUST-OLEUM CORP

VERNON HILLS, IL 60061-1583

US

847-367-7700

Cage: 08882

Ingredients

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 30%

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

PROPYLENE GLYCOL METHYL ETHER (VAPOR PRESSURE = 10.9)

Fraction By Weight: 15%

ACGIH TLV: 100 PPM

N-BUTYL ALCOHOL (SARA III)

CAS: 71-36-3

RTECS: EO1400000

Fraction By Weight:



OSHA PEL100 PPM
ACGIH TLV: S, C 50 PPM; 9293
EPA Report Quantity: 5000 LBS
DOT Report Quantity: 5000 LBS

LEAD CHROMATE (VI) OXIDE (OSHA PEL FOR LEAD FROM 29CFR
CAS: 18454-12-1
RTECS: OF9800000
Fraction By Weight: 1%
OSHA PEL0.05 MG/M3 (PB)
ACGIH TLV: 0.05MG/M3(CR)A2;8990

LEAD (SARA III)
CAS: 7439-92-1
RTECS: OF7525000
Fraction By Weight: 3%
OSHA PEL0.05 MG/M3;1910.1025
ACGIH TLV: 0.15 MG/M3;DUST 9192
EPA Report Quantity: 1 LB
DOT Report Quantity: 1 LB

Hazards

Effects of Overexposure:HEADACHE, DIZZINESS, STAGGERING GAIT,
CONFUSION, UNCONSCIOUSNESS OR COMA. SKIN/EYE: IRRITANT.

First Aid

First Aid:FUMES: REMOVE FROM EXPOSURE, RESTORE BREATHING AND NOTIFY A
PHYSICIAN. EYES: FLUSH WITH WATER FOR AT LEAST 15 MINUTES. NOTIFY A
PHYSICIAN. SKIN: WASH AFFECTED AREA WITH SOAP/WATER, REMOVE
CONTAMINATED CLOTHING. WASH HANDS BEFORE EATING OR SMOKING

Fire Fighting

Flash Point:84.5F (SETA)
Lower Limits:1.0%
Extinguishing Media:CO, DRY CHEMICAL OR FOAM
Fire Fighting Procedures:WEAR SCBA. WATER COOL CONTAINERS TO PREVENT
PRESS BUILD-UP.
Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. CLOSED
CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION, VENTILATE AREA
AND REMOVE WITH INERT ABSORBENT AND N-SPARKING TOOLS.

Handling

Handling and Storage Precautions:DON'T STORE ABOVE 120F. STORE LARGE
QUANTITIES IN BLDGS DESIGNED/PROTECTED FOR STORAGE OF NFPALASS II
FLAMMABLE LIQUIDS.
Other Precautions:CONTAINERS SHOULD BE GROUNDED WHEN POURING. DON'T
TAKE INTERNALLY. EMPTY CONTAINERS MAY BE HAZARDOUS.

Exposure Controls

Respiratory Protection:IN CONFINED AREAS: USE B OF M APPROVED AIR LINE
TYPE RESP OR HOODS.



Ventilation:PROVIDE LOCAL EXHAUST VENTILATION TO KEEP BELOW TLV/LEL.
Protective Gloves:RUBBER
Eye Protection:SAFETY EYEWEAR
Other Protective Equipment:USE GLOVES TO PREVENT PROLONGED SKIN CONTACT.
Supplemental Safety and Health
WT/GAL; 8.9 LBS. MSDS DATE 23 OCT 85.

Chemical Properties

Boiling Pt:B.P. Text:243-284F
Vapor Density:>AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:62%

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Hazardous Decomposition Products:CO AND CO2

Disposal

Waste Disposal Methods:DISPOSE OF ACCORDING TO LOCAL, STATE AND FEDERAL REGULATIONS. DON'T INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.