

HARD HAT ZINC RICH GALVANIZ COMPD 2185

MSDS Number

BBNRW

National Stock Number

8010-00F003753

Product Name

HARD HAT ZINC RICH GALVANIZ COMPD 2185

Manufacturer

RUST OLEUM CORP

Product Identification

Product ID:HARD HAT ZINC RICH GALVANIZ COMPD 2185

MSDS Date:01/01/1987

FSC:8010

NIIN:00F003753

MSDS Number: BBNRW

Responsible Party

RUST-OLEUM CORP/VERNON HILLS, ILL 60061

Emergency Phone: (312) 367-7700

Cage: 08882

Contractor

RUST-OLEUM CORP

VERNON HILLS, IL 60061-1583

US

847-367-7700

Cage: 08882

Ingredients

METHYLENE CHLORIDE (SARA III)

CAS: 75-09-2

RTECS: PA8050000

Fraction By Weight: 5 - 10%

OSHA PEL500 PPM/C,1000; Z2

ACGIH TLV: 50 PPM, A2; 9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

PROPANE

CAS: 74-98-6

RTECS: TX2275000

Fraction By Weight: 25%

OSHA PEL1000 PPM

ACGIH TLV: ASPHYXIAANT; 9192

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: SE7555000

Fraction By Weight:

OSHA PEL100 PPM

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 5 - 10%

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 20 - 25%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

Hazards

Effects of Overexposure:HEADACHE, DIZZINESS, STAGGERING GAIT, CONFUSION, UNCONSCIOUSNESS OR COMA. SKIN/EYES: IRRITANT.

First Aid

First Aid:FUMES: REMOVE FROM EXPOSURE, RESTORE BREATHING, AND NOTIFY A PHYSICIAN. EYES: FLUSH WITH WATER FOR AT LEAST 15 MINUTES. NOTIFY A PHYSICIAN. SKIN: WASH AFFECTED AREA WITH WATER/SOAP AND REMOVE CONTAMINATED CLOTHING.

Fire Fighting

Flash Point:Lower Limits:1.0%

Extinguishing Media:CO2, DRY CHEMICAL OR FOAM

Fire Fighting Procedures:WEAR SCBA. WATER COOL CONTAINERS TO PREVENT PRESS BUILD-UP.

Unusual Fire/Explosion Hazard:EXPOSURE TO HEAT/PROLONGED EXPOSURE TO THE SUN MAY CAUSE BURSTING. DON'T PUNCTURE/INCINERATE.

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION, VENTILATE AREA, AND REMOVE WITH INERT ABSORBENT AND N-SPARKING TOOLS.

Handling

Handling and Storage Precautions:DON'T STORE ABOVE 120F. DON'T PUNCTURE.

Other Precautions:INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS CAN BE HARMFUL OR FATAL.

Exposure Controls

Respiratory Protection:IN CONFINED AREAS: USE B OF M APPROVED AIRLINE

TYPE RESP OR HOODS.
Ventilation:PROVIDE LOCAL EXHAUST VENTILATION TO KEEP BELOW TLV/LEL.
Protective Gloves:RUBBER
Eye Protection:SAFETY EYEWEAR
Other Protective Equipment:USE GLOVES TO PREVENT PROLONGED SKIN CONTACT.
Supplemental Safety and Health
WT/GAL: N/A. MSDS DATE 31 OCT 1985.

Chemical Properties

Boiling Pt:B.P. Text:0F
Vapor Density:>AIR
Evaporation Rate & Reference:SLOWER THAN ETHER

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Hazardous Decomposition Products:CO AND CO2

Disposal

Waste Disposal Methods:DISPOSE OF ACCORDING TO LOCAL, STATE AND FEDERAL REGULATIONS. DON'T INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.