

## **HEAVY DUTY RUST INHIB. PRIMERS 1060/1069**

### **MSDS Number**

BBNTF

### **National Stock Number**

8010-00F003781

### **Product Name**

HEAVY DUTY RUST INHIB. PRIMERS 1060/1069

### **Manufacturer**

RSUT OLEUM CORP

### **Product Identification**

Product ID:HEAVY DUTY RUST INHIB. PRIMERS 1060/1069

MSDS Date:01/01/1987

FSC:8010

NIIN:00F003781

MSDS Number: BBNTF

### **Responsible Party**

RSUT-OLEUM CORP/VERNON HILLS, IL 60061

Emergency Phone: (312) 367-7700

Cage: EO740

### **Contractor**

RUST-OLEUM CORP

VERNON HILLS, IL 60061-1583

US

847-367-7700

Cage: 08882

### **Ingredients**

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: SE7555000

Fraction By Weight: 20%

OSHA PEL100 PPM

LEAD (SARA III)

CAS: 7439-92-1

RTECS: OF7525000

Fraction By Weight: 35%

OSHA PEL0.05 MG/M3;1910.1025

ACGIH TLV: 0.15 MG/M3;DUST 9192

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

### **Hazards**

Effects of Overexposure:HEADACHE, DIZZINESS, STAGGERING GAIT,  
CONFUSION, UNCONSCIOUSNESS OR COMA. SKIN/EYES: IRRITANT.

## First Aid

First Aid:FUMES: REMOVE FROM EXPOSURE, RESTORE BREATHING AND NOTIFY A PHYSICIAN. EYES: FLUSH WITH WATER FOR AT LEAST 15 MINUTES. NOTIFY A PHYSICIAN. SKIN: WASH AFFECTED AREA WITH SOAP AND WATER, REMOVE CONTAMINATED CLOTHING.

## Fire Fighting

Flash Point:104F (TCC)  
Lower Limits:1.0%  
Extinguishing Media:CO2, DRY CHEMICAL OR FOAM  
Fire Fighting Procedures:WEAR SCBA. WATER COOL CONTAINERS TO PREVENT PRESS BUILD-UP.  
Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

## Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION, VENTILATE AREA AND REMOVE WITH INERT ABSORBENT AND N-SPARKING TOOLS.

## Handling

Handling and Storage Precautions:DON'T STORE ABOVE 120F. STORE LARGE QUANTITIES IN BLDGS DESIGNED/PROTECTED FOR STORAGE OF NFPA CLASS II FLAMMABLE LIQUIDS.  
Other Precautions:CONTAINERS SHOULD BE GROUNDED WHEN POURING. DON'T TAKE INTERNALLY. EMPTY CONTAINERS MAY BE HAZARDOUS.

## Exposure Controls

Respiratory Protection:IN CONFINED AREAS: USE B OF M APPROVED AIRLINE TYPED RESP OR HOODS.  
Ventilation:PROVIDE LOCAL EXHAUST VENTILATION TO KEEP BELOW TLV/LEL.  
Protective Gloves:RUBBER  
Eye Protection:SAFETY EYEWEAR  
Other Protective Equipment:USE GLOVES TO PREVENT PROLONGED SKIN CONTACT.  
Supplemental Safety and Health  
WT/GAL: 13.8-14.0 LBS. MSDS DATE: 8 NOV 85.

## Chemical Properties

Boiling Pt:B.P. Text:313-386F  
Vapor Density:>AIR  
Evaporation Rate & Reference:SLOWER THAN ETHER  
Percent Volatiles by Volume:45%

## Stability

Stability Indicator/Materials to Avoid:YES  
WITH STRONG OXIDIZING AGENTS  
Hazardous Decomposition Products:CO AND CO2

## Disposal

Waste Disposal Methods:DISPOSE OF ACCORDING TO LOCAL, STATE AND FEDERAL REGULATIONS. DON'T INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.