

OVERALL TOPCOATS 2402/03/05/07/08/09/10/11

MSDS Number

BBNYD

National Stock Number

8010-00F003861

Product Name

OVERALL TOPCOATS 2402/03/05/07/08/09/10/11

Manufacturer

ROC SALES INC

Product Identification

Product ID:OVERALL TOPCOATS 2402/03/05/07/08/09/10/11

MSDS Date:01/01/1987

FSC:8010

NIIN:00F003861

MSDS Number: BBNYD

Responsible Party

ROC SALES INC/EVANSTON, IL 60204

Emergency Phone: (312) 367-7700

Cage: 00266

Contractor

ROC SALES INC/EVANSTON, IL 60204

(312) 367-7700

Cage: 00266

Ingredients

ACETONE (SARA III)

CAS: 67-64-1

RTECS: AL3150000

Fraction By Weight: 35 - 40%

OSHA PEL1000PPM

ACGIH TLV: 750PPM/1000STEL;9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 20%

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight: 10 - 20%

OSHA PEL200 PPM/300 STEL

ACGIH TLV: 200 PPM/300STEL 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 0-5%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

PROPANE

CAS: 74-98-6

RTECS: TX2275000

Fraction By Weight: 25%

OSHA PEL1000 PPM

ACGIH TLV: ASPHYXIAN; 9192

Hazards

Effects of Overexposure:ANESTHETIC. HEADACHE, DIZZINESS, STAGGERING, CONFUSION, UNCONSCIOUSNESS OR COMA.

First Aid

First Aid:FUMES: REMOVE FROM EXPOSURE, RESTORE BREATHING. NOTIFY A PHYSICIAN. EYES: FLUSH W/WATER FOR AT LEAST 15 MINUTES. NOTIFY A PHYSICIAN. SKIN: WASH AFFECTED AREA WITH SOAP AND WATER. REMOVE CONTAMINATED C LOTHING.

Fire Fighting

Flash Point:Extinguishing Media:CO2, DRY CHEMICAL OR FOAM

Fire Fighting Procedures:SCBA. WATER COOL CONTAINERS TO PREVENT PRESSURE BUILDUP.

Unusual Fire/Explosion Hazard:EXPOSURE TO HEAT OR PROLONGED EXPOSUREE TO THE SUN MAY CAUSE BURSTING. DON'T PUNCTURE OR INCINERATE.

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION, VENTILATE AREA AND REMOVE WITH INERT ABSORBENT AND N-SPARKING TOOLS.

Handling

Handling and Storage Precautions:DON'T STORE ABOVE 120F. DON'T PUNCTURE.

Other Precautions:INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING AND INHALING THE CONTENTS CAN BE HARMFUL OR FATAL.

Exposure Controls

Respiratory Protection:IN CONFINED AREAS: USE B OF M APPROVED AIRLINE

RESPIRATORS OR HOODS.
Ventilation:PROVIDE LOCAL EXHAUST VENTILATION TO KEEP BELOW TLV.
Protective Gloves:RUBBER
Eye Protection:SAFETY EYEWEAR
Supplemental Safety and Health
MSDS DATED: 1 NOV 1985. ALSO OVERALL TOPCOAT 2413..

Chemical Properties

Boiling Pt:B.P. Text:0F
Vapor Density:Evaporation Rate & Reference:SLOWER THAN ETHER

Stability

Stability Indicator/Materials to Avoid:YES
WITH STRONG OXDIZING AGENTS
Hazardous Decomposition Products:CO AND CO2

Disposal

Waste Disposal Methods:DISPOSE OF ACCORDING TO LOCAL, STATE AND FEDERAL
REGULATIONS. DON'T INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.