•



BAR & CHAIN OIL MOBC-1/MOBC-4

MSDS Number

BBNYX

National Stock Number

9150-00F003877

Product Name

BAR & CHAIN OIL MOBC-1/MOBC-4

Manufacturer

HARRISON OIL CORP

Product Identification

Product ID:BAR & CHAIN OIL MOBC-1/MOBC-4 MSDS Date:01/01/1987 FSC:9150 NIIN:00F003877 MSDS Number: BBNYX

Responsible Party

HARRISON OIL CORP/MILWAUKEE, WI 53212

Emergency Phone: (414) 962-4000

Cage: 5X833

Contractor

HARRISON OIL CORP

MILWAUKEE, WI 53211

414-962-4000

US

Cage: 5X833

Ingredients

PETROLEUM OIL

Hazards

Effects of Overexposure:BREATHING MISTS MAY CAUSE DIZZINESS OR PULMINARY IRRITATION. INGESTION: CAUSE CRAMPS OR DIARRHEA.

First Aid

First Aid: EXTERNAL: WIPE FROM EXPOSED AREA, THEN WASH THOROUGHLY WITH SOAP/WARM WATER. INTERNAL: DON'T INDUCE VOMTING. CONSULT PHYSICIAN IMMEDIATELY. EYE CONTACT: FLUSH WITH LARGE VOLUMES OF WATER. SEE PHYSICIA N.

Fire Fighting

Flash Point:>250F COC

Extinguishing Media: FOAM, DRY CHEMICAL, WATER SPRAY, WATER FOG, CO2. Fire Fighting Procedures: USE WATER SPRAY COOL SURFACES EXPOSED TO FIRE/PROTECT PERS.

Unusual Fire/Explosion Hazard: AVOID BREATHING PRODUCTS OF COMBUSTION WHICH INCLUDE FUMES, SMOKE, CO AND CO2.

Accidental Release

Spill Release Procedures: NORMAL PRECAUTIONARY MEASURES FOR HANDLING LUBRICATING OILS ARE SATISFACTORY. REMOVEPARKS, FLAME AND HOT SURFACES. COLLECT ON ABSORBANT.

Handling



Handling and Storage Precautions: AVOID TEMPS ABOVE 50C (120F) FOR PROLONGED PERIODS. AVOID/CONTAIN OIL MISTS. KEEP FROM HEAT/FLES. DON'T STORE NEAR FLAMES/HEAT/STRONG OXIDANTS.

Other Precautions: PERSONS EXPOSED TO OIL MISTS WEAR APPROVED BREATHING DEVICES. AVOID PROLONGED/REPEATED SKIN CONTACT. DON'T GET IN EYES. WASHHOROUGHLY AFTER HANDLING. NEVER WEAR OIL SOAKED CLOTHING.

Exposure Controls

Respiratory Protection: NOT USUALLY REQUIRED.

Ventilation:LOCAL EXHAUST: USUALY NOT REQUIRED IN UNCONFINED AREAS.

Protective Gloves:OIL RESISTANT

Eye Protection: GOGGLES

Other Protective Equipment: AN OIL RESISTANT APRON PROTECT AGAINST OIL

SOAKED CLOTHING.

Supplemental Safety and Health MSDS DATED: 01 NOV 85.

Chemical Properties

Boiling Pt:B.P. Text:500F Vapor Pres:Vapor Density:>1.0 Spec Gravity:0.9

Evaporation Rate & Reference: NEGLIGIBLE

Solubility in Water: NEGLIGIBLE

Appearance and Odor: FLUID, MINERAL OIL ODOR, DARK COLOR.

Percent Volatiles by Volume: NEGL

Stability

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS Stability Condition to Avoid:OVERHEATING FOR EXTENDED PERIODS CAUSE OXIDATIVE DEGRADATION

Disposal

Waste Disposal Methods: MUST BE DISPOSED OF ACCORDING TO LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.