

# **CHROMEL 70/30**

# **MSDS Number**

**BBPBL** 

## **National Stock Number**

6850-00F003903

# **Product Name**

CHROMEL 70/30

#### Manufacturer

**HOSKINS** 

## **Product Identification**

Product ID:CHROMEL 70/30 MSDS Date:01/01/1987 FSC:6850 NIIN:00F003903 MSDS Number: BBPBL

# **Responsible Party**

HOSKINS/HAMBURG, MICHIGAN 48139 Emergency Phone: (800) 424-9300

Cage: EO749

# Contractor

HOSKINS/HAMBURG, MICHIGAN 48139

HAMBURG, MI 48139

US

313-231-1900 Cage: EO749

### **Ingredients**

NICKEL (SARA III) CAS: 7440-02-0 RTECS: QR5950000

OSHA PEL1 MG/M3

ACGIH TLV: 1 MG/M3; 9192

CHROMIUM (SARA III)

CAS: 7440-47-3 RTECS: GB4200000 OSHA PEL1 MG/M3

ACGIH TLV: 0.5 MG/M3; 9192 EPA Report Quantity: 1 LB DOT Report Quantity: 1 LB

SILICON CARBIDE

CAS: 409-21-2

RTECS: VW0450000



OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

IRON OXIDE

CAS: 1309-37-1

RTECS: NO7400000

OSHA PEL10 MG/M3 (FE)

ACGIH TLV: 5 MG/M3(FE), B2; 9293

#### Hazards

Effects of Overexposure: IRRITATION TO THE

NOSE/EYES/THROAT/SKIN/NAUSEA/TIGHTNESS OF CHEST/DIZZINESS/SLIGHT

DISCOMFORT.

#### First Aid

First Aid:INHALATION: MOVE TO FRESH AIR. SKIN: WASH AFFECTED AREA W/SOAP & WATER. EYES: IMMEDIATELY WASH W/WATER. INGESTION: SEEK MEDICAL ATTENTION. IN ALL CASES, SEEK MEDICAL ATTENTION FOR FIRST AID.

\_. \_. . . .

# **Fire Fighting**

Unusual Fire/Explosion Hazard: NONFLAMMABLE, ALTHOUGH SPARKS FROM GRINDING OR WELDING MAY IGNITE FLAMMABLE OR COMBUSTABLE MATERIALS

### **Accidental Release**

Spill Release Procedures: GRINDING DUSTS, WELDING FUMES, AND CHEMICAL CLEANING SOLUTION GENERATED FROM THIS MARIAL MUST BE DISPOSED OF IN ACCORDANCE WITH PROPER REGULATING AGENCIES.

### Handling

Handling and Storage Precautions: PRACTICE PROPER INDUSTRIAL HYGIENE TO INSURE THAT THE USE OF THIS MATERIAL DOESN'T GENERATE GRDING DUSTS/WELDING FUMES IN EXCESS OF OSHA LIMITS.

Other Precautions: CONSULT THE FEDERAL REGISTER.

# **Exposure Controls**

Respiratory Protection: USE ONLY NIOSH APPROVED RESPIRATORS.

Ventilation: REQUIRED WHEN THE EXPOSURE LELS EXCEED THOSE ESTABLISHED

Eye Protection: FACESHIELDS

Other Protective Equipment: PROTECT YOURSELF/OTHERS. PROTECTIVE CLOTHING

WHERE REQUIRED.

Supplemental Safety and Health MSDS DATED: 01 NOV 1985.

# **Chemical Properties**

Appearance and Odor: ROD, WIRE, STRIP OR RIBBON

## Stability

Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:

\_

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.