FIXATIVE SPRAY/SMOKED CHARTS 296516-00-7

MSDS Number

BBPCN

National Stock Number

8010-00F003929

Product Name

FIXATIVE SPRAY/SMOKED CHARTS 296516-00-7

Manufacturer

GRAPHIC CONTROLS CORP

Product Identification

Product ID:FIXATIVE SPRAY/SMOKED CHARTS 296516-00-7
MSDS Date:01/01/1987
FSC:8010
NIIN:00F003929
MSDS Number: BBPCN

Responsible Party

GRAPHIC CONTROLS CORP/BUFFALO, NY 14240

Emergency Phone: (716) 853-7500

Cage: 28479

Contractor

GRAPHIC CONTROLS CORP MEDICAL PRODUCTS DIV

1284

BUFFALO, NY 14240

US

716-853-7500

Cage: 28479

Ingredients

PROPANE

CAS: 74-98-6

RTECS: TX2275000

Fraction By Weight: 12.5%

OSHA PEL1000 PPM

ACGIH TLV: ASPHYXIANT; 9192

ISOBUTANE PROPELLANT

CAS: 75-28-5

RTECS: TZ4300000

Fraction By Weight: 12.5%

ACGIH TLV: 1000 PPM

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 35%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

METHYLENE CHLORIDE (SARA III)

CAS: 75-09-2

RTECS: PA8050000

Fraction By Weight: 25%

OSHA PEL500 PPM/C,1000; Z2

ACGIH TLV: 50 PPM, A2; 9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

2-BUTOXYETHANOL

CAS: 111-76-2

RTECS: KJ8575000

Fraction By Weight:

OSHA PELS, 50 PPM

ACGIH TLV: S, 25 PPM; 9293

Hazards

Effects of Overexposure:OVER EXPOSURE MAY RESULT IN LIGHT HEADEDNESS, STAGGERING GAIT, GIDDINESS AND POSSIBLE NAUSEA.

First Aid

First Aid:BREATHING: REMOVE PATIENT TO FRESH AIR. EYES: FLUSH WITH WATER FOR AT LEAST 15 MINUTES. SKIN: WASH WITH SOAP AND WATER. SWALLOWING: CALL PHYSICIAN IMMEDIATELY. DON'T INDUCE VOMITING.

Fire Fighting

Flash Point:Extinguishing Media:CO2, DRY CHEMICAL OR FOAM
Fire Fighting Procedures:WATER MAY BE INEFFECTIVE - WATER COOL CONTAINERS
Unusual Fire/Explosion Hazard:DON'T SPRAY NEAR OPEN FLAME. KEEP AT ROOM TEMP AS EXPOSURE TO SUNLIGHT OR OTHER HEAT MAY BURSTING.

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION, VENTILATE. AVOID BREATHING VAPORS AND REMOVE WITH INT ABSORBENT.

Handling

Handling and Storage Precautions:DON'T STORE ABOVE 120F. KEEP AT ROOM TEMPERATURE AS EXPOSURE TO DIRECT SUNLIGHT OR OTHER HEAT Y CAUSE BURSTING.
Other Precautions:DON'T PUNCTURE OR INCINERATE. DON'T SPRAY NEAR FIRE OR OPEN FLAME. KEEP AWAY FROM CHILDREN.

Exposure Controls

Respiratory Protection:AVOID BREATHING OF VAPOR OR SPRAY MIST.
Ventilation:PROVIDE LOCAL EXHAUST VENTILATION TO KEEP BELOW TLV/LEL.
Protective Gloves:RECOMMENDED
Eye Protection:SAFETY GLASSES

Supplemental Safety and Health
MSDS DATED: NOV 1985.

Chemical Properties

Boiling Pt:B.P. Text:-0F
Vapor Pres:5
Vapor Density:>AIR
Evaporation Rate & Reference:FASTER THAN ETHER
Percent Volatiles by Volume:95%

Stability

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:DON'T STORE ABOVE 120F.
Hazardous Decomposition Products:CO, CO2, HYDROGEN CHLORIDE

Disposal

Waste Disposal Methods:DON'T INCINERATE - DISPOSE IN ACCORDANCE WITH FEDERAL STATE AND LOCAL REGULATIONS REGARDING POLLUTION.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.