

## **HOMELITE 2-CYCLE ENGINE OIL 16:1**

### **MSDS Number**

BBPFN

### **National Stock Number**

9150-00F003973

### **Product Name**

HOMELITE 2-CYCLE ENGINE OIL 16:1

### **Manufacturer**

WESTLAND OIL

### **Product Identification**

Product ID:HOMELITE 2-CYCLE ENGINE OIL 16:1

MSDS Date:01/01/1987

FSC:9150

NIIN:00F003973

MSDS Number: BBPFN

### **Responsible Party**

WESTLAND OIL/SHREVEPORT, LA 71148

Emergency Phone: (318) 688-1300

Cage: EO765

### **Contractor**

WESTLAND OIL/SHREVEPORT, LA 71148

SHREVEPORT, LA 71148

US

318-687-8000

Cage: EO765

### **Ingredients**

MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CAS: 8012-95-1

RTECS: PY8030000

Fraction By Weight: 85%

OSHA PEL5 MG/M3

ACGIH TLV: 5 MG/M3/10 STEL;9192

ADDITIVE

Fraction By Weight: 1-5%

STODDARD SOLVENT

CAS: 8052-41-3

RTECS: WJ8925000

Fraction By Weight: 15%

OSHA PEL500 PPM

ACGIH TLV: 100 PPM; 9293

---

## Hazards

Effects of Overexposure:DROWSINESS/UNCONSCIOUSNESS UPON EXPOSURE TO HIGH CONCENTRATIONS IN POORLY VENT. CONFINED SPACES.

## First Aid

First Aid:EYES: FLUSH WITH PLENTY OF WATER. SKIN: WASH EXPOSED AREAS WITH SOAP AND WATER. INGESTION: DON'T INDUCE VOMITING. CALL A PHYSICIAN. INHALATION: REMOVE FROM CONTAMINATED AREA.

## Fire Fighting

Flash Point:205F (COC)  
Extinguishing Media:USE WATER SPRAY, DRY CHEMICAL, FOAM OR CO2  
Fire Fighting Procedures:USE WATER TO COOL FIRE-EXPOSED CONTAINERS  
Unusual Fire/Explosion Hazard:IF LEAK NOT IGNITED, USE WATER SPRAY TO DISPERSE VAPORS & PROVIDE PERSONNEL PROTECTION.

## Accidental Release

Spill Release Procedures:CONTAIN SPILL IF POSSIBLE. WIPE UP OR ABSORB ON SUITABLE MATERIAL AND SHOVEL UP. IF LEAK OR SPILL HAS NOT IGNITED, USE WATER SPRAY TO DISPERSE THE VAPORS ANTO PROVIDE PROTECTION FOR PERSONS ATTEMPTING TO STOP THE LEAK.

## Handling

Handling and Storage Precautions:DANGER: HARMFUL OF FATAL IF SWALLOWED. COMBUSTIBLE. KEEP AWAY FROM HEAT/FLAME. USE ONLY IN WELVENTILATED LOCATIONS.  
Other Precautions:AVOID PROLONGED BREATHING OF MIST OR VAPOR. AVOID PROLONGED OR REPEATED CONTACT WITH SKIN. CONTAINS PETROLEUM DISTILLATES. KP OUT OF REACH OF CHILDREN.

## Exposure Controls

Ventilation:NORMAL  
Eye Protection:GOGGLES OR FACE SHIELD  
Supplemental Safety and Health  
MSDS DATED: 25 NOV 1985.

## Chemical Properties

Boiling Pt:B.P. Text:300-400F  
Spec Gravity:0.8751  
Appearance and Odor:GREEN LIQUID - AMMONIA

## Stability

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZERS  
Hazardous Decomposition  
Products:CO/CO2/ALDEHYDES/KETONES/NITROGEN/SULFUR.

## Disposal

Waste Disposal Methods:UNDER RCRA, IT'S THE RESPONSIBILITY OF THE USER OF PRODUCTS TO DETERMINE, AT THE TIME OF DISPOSAL, WHETHER PRODUCT MEETS RCRA CRITERIA FOR HAZ. WASTE. PRODUCT USES/TRANSFORMATIONS/MIXTURE/PROCESSES MA Y RENDER THE RESULTING MATERIAL HAZARDOUS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.