

M8-038 GREY AQUA PRIME

MSDS Number

BBPGD

National Stock Number

8010-00F003985

Product Name

M8-038 GREY AQUA PRIME

Manufacturer

CRAWFORD LABORATORIES

Product Identification

Product ID:M8-038 GREY AQUA PRIME

MSDS Date:01/01/1987

FSC:8010

NIIN:00F003985

MSDS Number: BBPGD

Responsible Party

CRAWFORD LABORATORIES/CHICAGO, IL 60609

Emergency Phone: (312) 376-7132

Cage: DO165

Contractor

CRAWFORD LABORATORIES, INC

CHICAGO, IL 60609

US

312-376-7132

Cage: 5V430

Ingredients

GLYCOL ETHERS (VAPOR PRESSURE = .88)

Fraction By Weight: 15%

ACGIH TLV: 25 PPM

Hazards

Effects of Overexposure:HEADACHE, DIZZINESS, NAUSEA, LOSS OF CONSCIOUSNESS. EYE IRRITATION.

First Aid

First Aid:EYE: FLUSH W/WATER FOR 15 MINUTES. INHALATION: REMOVE VICTIM TO FRESH AIR. INGESTION: INDUCE VOMITING. GIVE 1 OR 2 GLASSES OF WATER. SKIN: FLUSH W/WATER WHILE REMOVING CONTAMINATED CLOTHING/SHOES. FOL LOW BY WASHING W/SOAP & WATER. GET MED ATT.

Fire Fighting

Flash Point:168F SETA

Lower Limits:1.1%

Extinguishing Media:FOAM, CO2, DRY CHEMICAL

Fire Fighting Procedures:WATER MAY BE USED TO KEEP EXPOSED CONTAINERS COOL. USE SCBA.

Unusual Fire/Explosion Hazard:WATER PRESSURE MAY SPREAD A FLAMMABLE LIQUID FIRE. SEALED CONTAINERS MAY EXPLODE IF OVERHEATED.

Accidental Release

Spill Release Procedures:WARNING-COMBUSTIBLE. ELIMINATE ALL IGNITION

SOURCES. WEARING THE PROTECTIVE CLOTHING OUTLINED IN SECTION VIII, SOAK UP W/AN ABSORBANT/PLACE IN NON-LEAKING CONTAINERS. SEAL TIGHTLY FOR PROPER DISPOSAL.

Handling

Handling and Storage Precautions: TREAT AS ANY HAZARDOUS COMBUSTIBLE MATERIAL, STORE IN A COOL, DRY PLACE IN BUILDINGS FOR THE STORAGE OF COMBUSTIBLE LIQUIDS.

Exposure Controls

Respiratory Protection: NIOSH APPROVED ORGANIC VAPOR RESP WHERE VENTILATION IS INADEQUATE.
Ventilation: PROVIDE ADEQUATE VENTILATION TO KEEP BELOW TLV.
Protective Gloves: RUBBER
Eye Protection: SAFETY GOGGLES
Other Protective Equipment: HAVE EYE BATH AVAILABLE
Supplemental Safety and Health
MSDS DATED: 18 NOV 1985. WGT PER GALLON: 10.57 PDS. FOR USE IN 2 PART EPOXY, AQUA PRIMER UO-063.

Chemical Properties

Boiling Pt: B.P. Text: 340F
Vapor Density: >AIR
Evaporation Rate & Reference: (N-BU AC = 1) 0.09
Appearance and Odor: GREY LIQUID
Percent Volatiles by Volume: 25.5

Stability

Stability Indicator/Materials to Avoid: YES
INCOMPATIBLE W/STRONG OXIDIZING AGENTS/STRONG ALKALIES_
Stability Condition to Avoid: AVOID HEAT, SPARKS, OPEN FLAMES AND INCOMPATIBILITIES ABOVE.
Hazardous Decomposition Products: CO/UNIDENTIFIED ORGANIC COMPS MAY FORMED DURING COMBUSTION.
Conditions to Avoid Polymerization: _

Disposal

Waste Disposal Methods: DISPOSAL MUST BE IN ACCORDANCE WITH CURRENT LOCAL, STATE AND FEDERAL REGULATION. CONTACT AN APPROVED DISPOSAL FACILITY.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.