

#43 CEILING TILE/WALLBOARD ADHESIVE (8342)

MSDS Number

BBPGK

National Stock Number

8040-00F003990

Product Name

#43 CEILING TILE/WALLBOARD ADHESIVE (8342)

Manufacturer

GIBSON HOMANS

Product Identification

Product ID: #43 CEILING TILE/WALLBOARD ADHESIVE (8342)

MSDS Date: 01/01/1987

FSC: 8040

NIIN: 00F003990

MSDS Number: BBPGK

Responsible Party

GIBSON-HOMANS/BALTIMORE, MD 21237

Emergency Phone: (301) 391-4500

Cage: EO770

Contractor

GIBSON-HOMANS/BALTIMORE, MD 21237

BALTIMORE, MD 21237-5000

US

410-391-4500/216-843-2982

Cage: EO770

Ingredients

ISOPROPYL ALCOHOL (SARA III)

CAS: 67-63-0

RTECS: NT8050000

Fraction By Weight: 10%

OSHA PEL400 PPM/500 STEL

ACGIH TLV: 400 PPM/500STEL;9192

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: SE7555000

Fraction By Weight: 2%

OSHA PEL100 PPM

Hazards

Effects of Overexposure: INHALATION: DIZZINESS/HEADACHE/UNCONSCIOUSNESS.
PROLONGED/REPEATED SKIN CONTACT MAY BE IRRITATION.

First Aid

First Aid: EYES: FLUSH W/WATER FOR AT LEAST 15 MINUTES. SKIN: WASH

AFFECTED AREA W/WATER. INHALATION: IF OVERCOME BY VAPORS, REMOVE FROM EXPOSURE, RESTORE BREATHING. KEEP INDIVIDUAL CALM. CALL A PHYSICIAN. INGESTION: TREAT SYMPTOMATICALLY/CALL PHYSICIAN.

Fire Fighting

Flash Point:84F SCC
Lower Limits:2.0%
Upper Limits:12.0
Extinguishing Media:CO, DRY CHEMICAL OR FOAM
Fire Fighting Procedures:WATER COOL CONTAINERS TO PREVENT PRESSURE BUILDUP/EXPLOSION.
Unusual Fire/Explosion Hazard:KEEP CONTAINERS CLOSED WHEN IN USE. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

Accidental Release

Spill Release Procedures:SCRAPE INTO CONTAINERS FOR DISPOSAL.

Handling

Handling and Storage Precautions:VAPORS MAY IGNITED EXPLOSIVELY. PREVENT BUILD UP OF VAPORS. KEEP AWAY FROM HEAT/SPARKS/OPEN FLME. Other Precautions:AVOID PROLONGED BREATHING OF VAPORS AND REPEATED CONTACT WITH SKIN. DON'T STORE ABOVE 120F. KEEP OUT OF REACH OF CHILDREN.

Exposure Controls

Respiratory Protection:NONE REQUIRED WITH ADEQUATE VENTILATION
Ventilation:PROVIDE VENTILATION TO KEEP BELOW TLV/PEL
Protective Gloves:NONE REQUIRED
Eye Protection:NORMAL
Other Protective Equipment:NONE
Supplemental Safety and Health
MSDS DATED: NOV 1985.

Chemical Properties

Boiling Pt:B.P. Text:180F
Vapor Pres:33
Vapor Density:2.07
Spec Gravity:1.37
Evaporation Rate & Reference:(BU AC = 1) >1
Solubility in Water:INSOLUBLE
Appearance and Odor:BROWN MASTIC WITH MILD ALCOHOL ODOR
Percent Volatiles by Volume:22%

Stability

Stability Indicator/Materials to Avoid:YES
NONE
Hazardous Decomposition Products:CO AND ORGANIC COMPOUNDS OF UNKNOWN STRUCTURE.

Disposal

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.