

LOKWELD 205, 805/806 CONTACT ADHESIVES

MSDS Number

BBPGZ

National Stock Number

8040-00F004004

Product Name

LOKWELD 205, 805/806 CONTACT ADHESIVES

Manufacturer

RALPH WILSON PLASTICS CO

Product Identification

Product ID:LOKWELD 205, 805/806 CONTACT ADHESIVES

MSDS Date:01/01/1987

FSC:8040

NIIN:00F004004

MSDS Number: BBPGZ

Responsible Party

RALPH WILSON PLASTICS CO/TEMPLE, TX 76501

Emergency Phone: (817) 778-2711

Cage: RALPH

Contractor

RALPH WILSON PLASTICS CO/TEMPLE, TX 76501

Cage: RALPH

Ingredients

MAGNESIUM OXIDE

RTECS: OM2457000

Fraction By Weight: 3%

ACGIH TLV: 10 MG/CUM

NEOPRENE

RTECS: EI9660000

Fraction By Weight: 6%

ACGIH TLV: 10 MG/CUM

PHENOLIC RESIN

Fraction By Weight: 3%

METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)

CAS: 71-55-6

RTECS: KJ2975000

Fraction By Weight: 90%

OSHA PEL350 PPM/450 STEL

ACGIH TLV: 350 PPM/450STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

METHYL ALCOHOL (METHANOL) (SARA III)

CAS: 67-56-1

RTECS: PC1400000

Fraction By Weight: TR

OSHA PELS,200PPM/250STEL

ACGIH TLV: S,200PPM/250STEL; 93

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

Hazards

Effects of

Overexposure:HEADACHES/DIZZINESS/DROWSINESS/NAUSEA/VOMITINGEYES/SKIN IRRITATION. INGESTION: BLINDNESS.

First Aid

First Aid:INHALATION: MOVE VICTIM TO FRESH AIR AND SEEK MEDICAL ATTENTION. SKIN & EYES: FLUSH WITH PLENTY OF WATER, SEEK MEDICAL ATTENTION. INGESTION: INDUCE VOMITING IF VICTIM IS CONSCIOUS.

Fire Fighting

Flash Point:NONE

Extinguishing Media:CO2, FOAM, DRY CHEMICAL

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS (SCBA)

Unusual Fire/Explosion Hazard:NONE

Accidental Release

Spill Release Procedures:SMALL SPILLS: MOP, WIPE/SOAP UP W/ABSORBENT MATERIAL. USE PROTECTIVE EQUIPMENT. PLACCONTAMINATED MATERIAL IN CLOSED CONTAINER. LARGE SPILLS: EVACUATE AREA, E PROTECTIVE EQUIPMENT. CONTAIN SPILL W/ABSORBENT MATERIAL. KEEP SPILL FROM WATER.

Handling

Handling and Storage Precautions:HANDLE WITH REASONABLE CARE. AVOID PROLONGED BREATHING OF VAPORS. STORE IN COOL DRY PLACE.

Exposure Controls

Respiratory Protection:ABOVE 200 PPM USE SCBA OR SUPPLIED AIR RESPIRATOR.

Ventilation:PROVIDE LOCAL EXHAUST/MECH VENTILATION TO BELOW TLV/LEL

Protective Gloves:NITRILE

Eye Protection:GOGGLES

Other Protective Equipment:NO SPECIAL PROTECTIVE CLOTHING REQUIRED.

Supplemental Safety and Health

MSDS DATED: 14 NOV 1985.

Chemical Properties

Boiling Pt:B.P. Text:165F

Vapor Pres:100

Vapor Density:4.55

Spec Gravity:1.4

Solubility in Water:NEGLIGIBLE

Appearance and Odor:MILD CHLOROFORM-LIKE ODOR

Stability

WATER-SLOW HYDROLYSIS PRODUCES CORROSIVE ACID

Hazardous Decomposition Products:HIGH TEMP GENERATE HCL & SMALL AMOUNT

OF CL2 & PHOSGENE.

Disposal

Waste Disposal Methods: SPILLED, CONTAMINATED MATERIAL OR WASTE SOLVENT SHOULD BE PUT INTO SUITABLE CONTAINER AND HANDLED ACCORDING TO LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.