

ANCHOR PAINT - 1723-A

MSDS Number

BBPHK

National Stock Number

8010-00F004012

Product Name

ANCHOR PAINT - 1723-A

Manufacturer

ANCHOR PAINT MFG

Product Identification

Product ID: ANCHOR PAINT - 1723-A

MSDS Date: 01/01/1987

FSC: 8010

NIIN: 00F004012

MSDS Number: BBPHK

Responsible Party

ANCHOR PAINT MFG/TULSA, OK 74112

Emergency Phone: (918) 836-4626

Cage: 0E220

Contractor

ANCHOR PAINT MFG CO INC

1305

TULSA, OK 74101

US

918-836-4626

Cage: 0E220

Ingredients

WATER (SEE SUPPLEMENTAL FOR INGREDIENTS)

CAS: 7732-18-5

RTECS: ZC0110000

Fraction By Weight: 10%

PHOSPHORIC ACID (SARA III)

CAS: 7664-38-2

RTECS: TB6300000

Fraction By Weight: 20%

OSHA PEL1 MG/M3/3 STEL

ACGIH TLV: 1 MG/M3/3 STEL; 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

ALCOHOL

Fraction By Weight: 70%

ACGIH TLV: 50 PPM

Hazards

Effects of Overexposure: LIQUID IS HARMFUL/FATAL IF SWALLOWED. EXCESSIVE INHALATION CAUSE HEADACHE, DIZZINESS AND NAUSEA.

First Aid

First Aid: IF OVERCOME BY VAPORS, REMOVE VICTIM FROM CONTAMINATED AREA, KEEP VICTIM WARM/QUIET; IF BREATHING HAS STOPPED, GIVE ARTIFICIAL RESPIRATION. CALL PHYSICIAN IMMEDIATELY. EYE CONTACT: FLUSH W/WATER; WASH SKIN WITH MILD SOAP AND WATER.

Fire Fighting

Flash Point: 99F TOC

Lower Limits: 1.73

Upper Limits: 10.7

Extinguishing Media: DRY CHEMICAL, CO2, CLASS "B" FIRES

Fire Fighting Procedures: NONE

Unusual Fire/Explosion Hazard: IGNITES EASILY - FLAMMABLE

Accidental Release

Spill Release Procedures: MATERIAL IS FLAMM/CARE SHOULD BE EXERCISED TO PREV. FIRE. SPILLED MATERIAL MAY BE PUEDED INTO ANOTHER CONTAINER/ABSORBED/REMOVE FROM THE AREA. ALL SPARKS/FLAM/IGNITION SOURCES SHOULD BE KEPT OUT OF AREA. NON-SPARKING TOOLS SHOULD USED.

Handling

Handling and Storage Precautions: KEEP CONTAINER CLOSED. DON'T STORE OR USE NEAR HEAT, SPARKS OR FLAME. KEEP IN COOL DRY PLACE. OI BREATHING VAPORS.

Other Precautions: GROUND ALL CONTAINERS WHEN TRANSFERRING LIQUID. AVOID PROLONGED CONTACT WITH SKIN.

Exposure Controls

Respiratory Protection: SELF-CONTAINED OR SUPPLY AIR MASKS FOR ENTERING AREA OF CONC. VAPOR.

Ventilation: USE LOCAL EXHAUST VENTILATION TO KEEP BELOW TLV.

Protective Gloves: CHEM. RESISTANT

Eye Protection: GOGGLES

Other Protective Equipment: EYE BATH AND SAFETY SHOWER.

Supplemental Safety and Health

ALSO CONTAINS: LEAD FREE.

Chemical Properties

Boiling Pt: B.P. Text: 244F

Vapor Pres: 5.5

Vapor Density: 2.55

Spec Gravity: 0.8

Evaporation Rate & Reference: (ETHYL ETHER=1) 0.5

Solubility in Water: 7.9%

Percent Volatiles by Volume: 100

Stability

Stability Indicator/Materials to Avoid: YES

REACTS WITH STRONG OXIDIZING AGENTS

Stability Condition to Avoid: EXPLOSIVE/COMBUSTIBLE MIXTURES WITH AIR OR OXYGEN. _

Hazardous Decomposition Products: COMBUSTION PRODUCTS ARE CO2 AND OXYGEN

Conditions to Avoid Polymerization: DOESN'T HEAD SPONTANEOUSLY.

Disposal

Waste Disposal Methods: INCINERATION OR DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.