

ANSULITE 3% (AFC-5-A)

MSDS Number

BBPJQ

National Stock Number

4210-00F004039

Product Name

ANSULITE 3% (AFC-5-A)

Manufacturer

ANSUL

Product Identification

Product ID:ANSULITE 3% (AFC-5-A)

MSDS Date:01/01/1987

FSC:4210

NIIN:00F004039

MSDS Number: BBPJQ

Responsible Party

ANSUL/MARINETTE, WI 54143

Emergency Phone: (715) 735-7411

Cage: EO780

Contractor

ANSUL/MARINETTE, WI 54143

MARINETTE, WI 54143-2542

US

715-735-7411

Cage: EO780

Ingredients

DIETHYLENE GLYCOL MONOBUTYL ETHER (BUTYL CARBITOL)

CAS: 112-34-5

RTECS: KJ9100000

Fraction By Weight: 20%

HYDROCARBON SURFACTANTS

Fraction By Weight:

FLUOROSURFACTANTS

Fraction By Weight:

INORGANIC SALTS

Fraction By Weight:

WATER

CAS: 7732-18-5

RTECS: ZC0110000

Fraction By Weight:

Hazards

Effects of Overexposure:IRRITATION OF THE EYES, SKIN AND MUCOUS

MEMBRANES.

First Aid

First Aid:EYE CONTACT: FLUSH/WATR; IF IRRITATION PERSISTS, SEEK MEDICAL ATTENTION. SKIN CONTACT: WASH WITH SOAP/WATER. INHALATION: REMOVE VICTIM TO FRESH AIR. INGESTION: IF PATIENT IS CONSCIOUS, GIVE WATER AND INDUCE VOMITING. SEEK MEDICAL HELP.

Fire Fighting

Flash Point:NONE TO BOILING

Fire Fighting Procedures:THIS IS AN EXTINGUISHING AGENT

Unusual Fire/Explosion Hazard:NONE

Accidental Release

Spill Release Procedures:RINSE FLOOR THOROUGHLY WITH WATER AS MATERIAL IS SLIPPERY. PREVENT MATERIAL FROM REAING SEWERS OR WATERWAYS TO AVOID NUISANCE FOAMING.

Handling

Handling and Storage Precautions:STORE IN ORIGINAL CONTAINER.

Other Precautions:DON'T MIX AGENTS. AVOID SKIN AND EYE CONTACT. AVOID INGESTION.

Exposure Controls

Respiratory Protection:NOT NORMALLY NECESSARY

Ventilation:MECHANICAL: RECOMMENDED

Eye Protection:CHEMICAL GOGGLES

Other Protective Equipment:EYE WASH AND SAFETY SHOWERS ARE GOOD SAFETY PRACTICE.

Supplemental Safety and Health

MSDS DATED: 01 JUN 1986.

Chemical Properties

Boiling Pt:B.P. Text:97F

Vapor Density:1

Spec Gravity:1.02

Evaporation Rate & Reference:(BU AC = 1) 0.47

Solubility in Water:100%

Appearance and Odor:CLEAR STRAW COLORED LIQUID, MILD SWEET ODOR.

Percent Volatiles by Volume:85

Stability

Stability Indicator/Materials to Avoid:YES

REACTIVE METALS/MATERIALS REACTIVE WITH WATER _

Stability Condition to Avoid:ELECTRICALLY ENERGIZED EQUIPMENT

Disposal

Waste Disposal Methods:DISPOSE OF IN COMPLIANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.