

## **MILD LACQUER WASHUP, T-925**

### **MSDS Number**

BBPKV

### **National Stock Number**

8010-00F004066

### **Product Name**

MILD LACQUER WASHUP, T-925

### **Manufacturer**

ADVANCE PROCESS SUPPLY

### **Product Identification**

Product ID:MILD LACQUER WASHUP, T-925

MSDS Date:01/01/1987

FSC:8010

NIIN:00F004066

MSDS Number: BBPKV

### **Responsible Party**

ADVANCE PROCESS SUPPLY/CHICAGO, IL 60622

Emergency Phone: (312) 829-1400

Cage: 29431

### **Contractor**

ADVANCE PROCESS SUPPLY CO.

CHICAGO, IL 60622-6383

US

312-942-8504

Cage: 29431

### **Ingredients**

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 50.0%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

ISOPROPYL ALCOHOL (SARA III)

CAS: 67-63-0

RTECS: NT8050000

Fraction By Weight: 25.0%

OSHA PEL400 PPM/500 STEL

ACGIH TLV: 400 PPM/500STEL;9192

ACETONE (SARA III)

CAS: 67-64-1

RTECS: AL3150000

Fraction By Weight: 20.0%

OSHA PEL1000PPM

ACGIH TLV: 750PPM/1000STEL;9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

DIACETONE ALCOHOL (4-HYDROXY-4-METHYL-2-PENTANONE)

CAS: 123-42-2

RTECS: SA9100000

Fraction By Weight: 5.00%

OSHA PEL50 PPM

ACGIH TLV: 50 PPM; 9192

## Hazards

Effects of Overexposure:PROLONGED EXPOSURE MAY CAUSE HEADACHE/NAUSEA/VOMITING/DIZZINESS. SKIN WILL BECOME RED & DRY.

## First Aid

First Aid:INHALATION: MOVE TO FRESH AIR. APPLY ARTIFICIAL RESPIRATION IF NECESSARY. SKIN: FLUSH W/SOAP/WATER. REMOVE CONTAMINATED CLOTHING. CALL PHYSICIAN IMMEDIATELY. INGESTION: DON'T INDUCE VOMITING/DRINK WATER. EYES: FLUSH W/WATER FOR 15 MIN. GETMED ATT.

## Fire Fighting

Flash Point:16.0F

Lower Limits:1.2%

Extinguishing Media:ALCOHOL FOAM, CO2, DRY CHEMICAL

Fire Fighting Procedures:WATER COOL CONTAINERS. USE SCBA. \_

Unusual Fire/Explosion Hazard:VAPORS MAY FORM EXPLOSIVE MIX W/AIR.

VAPOR IS >AIR, MAY TRAVEL/IGNITE/FLASHBACK.

## Accidental Release

Spill Release Procedures:ABSORB W/SAND & DISPOSE OF IN APPROVED MANNER. REMOVE ALL SOURCES OF IGNITION. DIKE EA W/SAND TO CONTAIN SPILLED LIQUID. LARGE SPILLS-EVACUATE AREA, OPEN ALLWINDOWS/DOORS. PUMP INTO SALVAGE TANK. KEEP MATERIAL OUT OF SEWERS/STREA ETC.

## Handling

Handling and Storage Precautions:EMPTY CONTAINERS CONTAINING RESIDUE MAY CAUSE A HAZARD. WASH THOROUGHLY AFTER HANDLING. DON'T KE INTERNALLY. AVOID CONTACT W/SKIN/EYES/CLOTHING.

Other Precautions:AVOID BREATHING DUST OR MIST. KEEP AWAY FROM FEED & FOOD PRODUCTS. KEEP CONTAINERS COOL, DRY & AWAY FROM IGNITION SOURCES. AID PROLONGED BREATHING OR CONTACT WITH SKIN.

## Exposure Controls

Respiratory Protection:MESA/NIOSH APPROVED RESPIRATOR.

Ventilation:PROVIDE LOCAL EXHAUST VENTILATION TO KEEP BELOW TLV

Protective Gloves:NITRILE RUBBER

Eye Protection:SAFETY GOGGLES/FACE SHIEL

Other Protective Equipment:IMPERVIOUS CLOTHING AND BOOTS

Supplemental Safety and Health

MSDS DATE: 30 JAN 1986.

## Chemical Properties

Boiling Pt:B.P. Text:133F

Spec Gravity:0.840  
Evaporation Rate & Reference:SLOWER THAN N-BUAC  
Solubility in Water:NEG (Appearance and Odor:CLEAR LIQUID MILD ODOR.  
Percent Volatiles by Volume:100%

## **Stability**

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZING AGENTS/BASES/ALKALIES/MINERAL ACIDS  
Stability Condition to Avoid:SOURCES OF IGNITION  
Hazardous Decomposition Products:OXIDES OF CARBON/VARIOUS  
HYDROCARBONS/NOXIOUS GASES

## **Disposal**

Waste Disposal Methods:LANDFILL IN ACCORDANCE WITH LOCAL, STATE AND  
FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.