

---

## **01800 OSHA GLOSS WHITE, 45940**

### **MSDS Number**

BBPLB

### **National Stock Number**

8010-00F004071

### **Product Name**

01800 OSHA GLOSS WHITE, 45940

### **Manufacturer**

SPRAYON PRODUCTS

### **Product Identification**

Product ID:01800 OSHA GLOSS WHITE, 45940

MSDS Date:01/01/1987

FSC:8010

NIIN:00F004071

MSDS Number: BBPLB

### **Responsible Party**

SPRAYON PRODUCTS/BEDFORD HTS, OH 44146

Emergency Phone: (216) 292-7400

Cage: DO662

### **Contractor**

SPRAYON PRODUCTS; SHERWIN WILLIAMS

BEDFORD HEIGHTS, OH 44146

216-292-7400

Cage: DO662

### **Ingredients**

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 15%

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 5 - 10%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight: 10 - 20%

OSHA PEL200 PPM/300 STEL

ACGIH TLV: 200 PPM/300STEL 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

METHYLENE CHLORIDE (SARA III)

CAS: 75-09-2

RTECS: PA8050000

Fraction By Weight: 10 - 20%

OSHA PEL500 PPM/C,1000; Z2

ACGIH TLV: 50 PPM, A2; 9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

TITANIUM DIOXIDE

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight: 11.2%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

## Hazards

Effects of Overexposure:LIGHT-HEADEDNESS/STAGGERING  
GAIT/GIDDINESS/NAUSEA. HARMFUL OR FATAL IF SWALLOWED.

## First Aid

First Aid:BREATHING: REMOVE PATIENT TO FRESH AIR. EYES: FLUSH WITH  
WATER FOR AT LEAST 15 MINUTES. SKIN: WASH WITH SOAP AND WATER.  
SWALLOWING: DON'T INDUCE VOMITING. CALL PHYSICIAN IMMEDIATELY.

## Fire Fighting

Flash Point:20F (TOC)

Lower Limits:1.1%

Extinguishing Media:CO2, DRY CHEMICAL OR FOAM

Fire Fighting Procedures:WATER MAY INEFFECTIVE. WATER COOL CONTAINERS.

Unusual Fire/Explosion Hazard:DON'T SPRAY NEAR OPEN FLAME. KEEP ROOM  
TEMP. AS EXPOSURE TO DIRECT SUNLIGHT/HEAT MAY CAUSE BURSTING.

## Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE  
AVOID BREATHING VAPORS AND REMOVE WITH INE ABSORBENT.

## Handling

Handling and Storage Precautions:DON'T STORE ABOVE 120F. KEEP AT ROOM  
TEMPERATURE AS EXPOSURE TO DIRECT SUNLIGHT OR HEAT MAY CAE  
BURSTING.

Other Precautions:KEEP AWAY FROM CHILDREN. DON'T PUNCTURE OR  
INCINERATE. DON'T SPRAY NEAR FIRE OR OPEN FLAME.

---

## Exposure Controls

Respiratory Protection: AVOID BREATHING VAPOR OR SPRAY MIST

Ventilation: PROVIDE LOCAL EXHAUST VENTILATION TO KEEP BELOW TLV/LEL

Eye Protection: SAFETY GLASSES

Other Protective Equipment: GLOVES RECOMMENDED FOR PROLONGED OR REPEATED CONTACT.

Supplemental Safety and Health

MSDS DATE: 09 SEPT 1986. ALSO CONTAINS: ETHYL-ETHOXYPROPIONATE ISOBUTANE (TZ4300000)

## Chemical Properties

Vapor Density: >AIR

Evaporation Rate & Reference: FASTER THAN ETHER

Percent Volatiles by Volume: 77%

## Stability

Stability Indicator/Materials to Avoid: YES

NONE

Stability Condition to Avoid: DON'T STORE ABOVE 120F

Hazardous Decomposition Products: CO, CO<sub>2</sub>, HYDROGEN CHLORIDE & PHOSGENE GAS

## Disposal

Waste Disposal Methods: DON'T INCINERATE - DISPOSE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS REGARDING POLLUTION.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.