

SCOTCH SPRAY MOUNT ARTIST'S ADHESIVE

MSDS Number

BBPLM

National Stock Number

8040-00-171-1535

Product Name

SCOTCH SPRAY MOUNT ARTIST'S ADHESIVE

Manufacturer

3M CENTER

Product Identification

Product ID: SCOTCH SPRAY MOUNT ARTIST'S ADHESIVE

MSDS Date: 01/01/1987

FSC: 8040

NIIN: 00-171-1535

MSDS Number: BBPLM

Responsible Party

3M CENTER/ST. PAUL, MN 55144

Emergency Phone: (612) 733-1110

Cage: 76381

Contractor

MINNESOTA MINING AND MFG CO, DBA 3M

SAINT PAUL, MN 55144-1000

US

866-556 5712 / 612-733-1110

Cage: 76381

Ingredients

ACRYLIC RESIN (SEE SUPPLEMENTAL FOR INGREDIENTS)

Fraction By Weight:

TERPENE RESIN BLEND

Fraction By Weight:

ISOBUTANE

CAS: 75-28-5

RTECS: TZ4300000

Fraction By Weight: 37.0%

METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)

CAS: 71-55-6

RTECS: KJ2975000

Fraction By Weight: 55.0%

OSHA PEL350 PPM/450 STEL

ACGIH TLV: 350 PPM/450 STEL; 9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

1,4-DIOXANE (DIETHYLENE DIOXIDE) (SARA III)

CAS: 123-91-1

RTECS: JG8225000

OSHA PELS, 100 PPM

ACGIH TLV: S, 25 PPM; 9293

EPA Report Quantity: 100 LBS

DOT Report Quantity: 100 LBS

Hazards

Effects of

Overexposure:DIZZINESS/NAUSEA/HEADACHE/UNCONSCIOUSNESS/DEATH.

EYE/SKIN CONTACT: MAY CAUSE IRRITATION.

First Aid

First Aid:EYE: FLUSH W/WATER FOR AT LEAST 15 MINUTES. SKIN: WASH WITH SOAP/WATER. INHALATION: MOVE VICTIM TO FRESH AIR. RESTORE OR SUPPORT BREATHING AS NECESSARY. IF SWALLOWED: DON'T INDUCE VOMITING. DRINK 2 GLASSES MILK OR WATER. CALL A PHYSICIAN.

Fire Fighting

Flash Point:-50F

Extinguishing Media:CO2, FOAM, DRY CHEMICAL

Fire Fighting Procedures:SCBA WHEN FIGHTING FIRES INVOLVING THIS MATERIAL.

Unusual Fire/Explosion Hazard:FLAMMABLE. OVERHEATED, CLOSED CONTAINERS ADJACENT TO FIRE COULD EXPLODE DUE TO PRESSURE BUILDUP.

Accidental Release

Spill Release Procedures:IF ANY CANS RUPTURE, EXTINGUISH ALL IGNITION SOURCES/VENTILATE THE AREA. USE ABSORBENT MATERIAL AS NEEDED IN CLEANUP PROCEDURE. PLACE CAN IN AN APPROVED U.S. PT. OF TRANSPORTATION CONTAINERS.

Handling

Handling and Storage Precautions:AVOID PROLONGED BREATHING OF VAPORS AND OVERSPRAY DURING APPLICATION. AVOID CONTACT WITH EYE/SKIN.

Other Precautions:AVOID VAPOR CONTACT W/OPEN FLAMES, WELDING ARCS OR HIGH TEMP SOURCES WHICH MIGHT CAUSE VAPOR DECOMPOSITION TO PRODUCE HARMFUL GASES.

Exposure Controls

Respiratory Protection:USE ONLY IN AREAS ADEQUATELY VENTILATED

Ventilation:PROVIDE LOCAL EXHAUST VENTILATION TO KEEP BELOW TLV/LEL

Protective Gloves:RUBBER

Eye Protection:SAFETY GLASSES

Supplemental Safety and Health

MSDS DATE: 16 DEC 1985. ALSO CONTAINS: PLASTICIZER (1000264PL)

Chemical Properties

Vapor Density:4.6

Evaporation Rate & Reference:(ETHER = 1): .4

Solubility in Water:NIL

Appearance and Odor:TRANSLUCENT LIQUID: SWEET ODOR.

Percent Volatiles by Volume:92%

Stability

Stability Indicator/Materials to Avoid:YES

DON'T PUNCTURE OR INCINERATE

Stability Condition to Avoid:DON'T STORE AT TEMPERATURES ABOVE 120F.

Hazardous Decomposition Products:HCL/CHLORINE/PHOSGENE WHEN SUBJECTED

TO EXCESS. HEAT/FLAME

Disposal

Waste Disposal Methods:DON'T PUNCTURE IN INCINERATE CAN IN HOUSEHOLD INCINERATOR. INCINERATE PROPERLY IN ACCORDANCE W/APPLICABLE REGULATIONS AS THE PRODUCT CONTAINS HALOGENS. EMPTY CONTAINERS MAY BE DISPOSED IN A SANITARY LANDFILL IN ACCORDANCE W/LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.