

WHITE STREET MARKING PAINT, #04676

MSDS Number

BBPQT

National Stock Number

8010-00F004171

Product Name

WHITE STREET MARKING PAINT, #04676

Manufacturer

JONES BLAIR

Product Identification

Product ID: WHITE STREET MARKING PAINT, #04676

MSDS Date: 01/01/1987

FSC: 8010

NIIN: 00F004171

MSDS Number: BBPQT

Responsible Party

JONES BLAIR/DALLAS, TX 75235

Emergency Phone: (214) 353-1600

Cage: EO806

Contractor

JONES BLAIR/DALLAS, TX 75235

DALLAS, TX 75235

US

214-353-1600

Cage: EO806

Ingredients

TALC (CONTAINING NO ASBESTOS)

CAS: 14807-96-6

RTECS: WW2710000

Fraction By Weight: 11.3%

OSHA PEL2 MG/M3 RDUST

ACGIH TLV: 2 MG/M3 RDUST; 9192

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: SE7555000

Fraction By Weight: 21.5%

OSHA PEL100 PPM

Hazards

Effects of Overexposure: EXCESSIVE INHALATION MAY RESULT IN HEADACHES/NAUSEA/EYE/LUNG IRRITATION/NARCOSIS.

First Aid

First Aid: EYES: FLUSH W/WATER FOR 5-10 MINUTES. IF EYE IRRITATION

PERSISTS, GET MED ATT. SKIN: WIPE MATERIAL OFF/WASH CONTACTED AREA.
IF INGESTED: DON'T INDUCE VOMITING. GET PATIENT TO FRESH
AIR/CONSULT PHYS. R EMOVE CONTAMINATED CLOTHING/WASH BEFOREREUSE.

Fire Fighting

Flash Point:21F
Lower Limits:.70%
Extinguishing Media:FOAM, CO2, DRY CHEMICAL OR SAND
Fire Fighting Procedures:GENERAL PRECEDURES RECOMMENDED. AVOID USE OF
WATER.
Unusual Fire/Explosion Hazard:CONTAINERS MAY RUPTURE DUE TO VERY HIGH
TEMPERATURE INDUCED PRESSURE.

Accidental Release

Spill Release Procedures:ELIMINATE IGNITION SOURCES. STOP SPILL OR LEAK
AT ONCE, BY CREATING DIKE, ETC. COVERITH INERT ABSORBANT MATERIAL.
SHOVEL OR SWEEP INTO DISPOSABLE CONTAINER.

Handling

Handling and Storage Precautions:KEEP AWAY FROM SPARKS/HEAT/OPEN
FLAMES.
Other Precautions:DON'T TAKE INTERNALLY. AVOID PROLONGED CONTACT OR
INHALATION.

Exposure Controls

Respiratory Protection:PROVIDE ADEQUATE VENTILATION FOR CONFINED
AREAS/WHEN USING SPRAY.
Ventilation:LOCAL EXHAUST PREFERABLE TO NATURAL DILUTION
Protective Gloves:RECOMMENDED
Eye Protection:FACESHIELD/GOGGLES
Other Protective Equipment:USE DUST RESP WHEN SANDING/MILLING/SAWING
ANY ITEMS PAINTED.
Supplemental Safety and Health
MSDS DATE: 24 JUN 1986. WT/GAL: 12.44.

Chemical Properties

Boiling Pt:B.P. Text:198-400F
Vapor Density:>AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:46%

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING MATERIALS
Stability Condition to Avoid:HEAT, OPEN FLAMES AND SPARKS

Disposal

Waste Disposal Methods:SHOVEL INTO DRUMS. INCINERATE AS LOCAL LAWS
PERMIT.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.