

## **CARRIAGE FLAT ACRYLIC HOUSE PAINT / #24 BLAC**

### **MSDS Number**

BBPWR

### **National Stock Number**

8010-00F004270

### **Product Name**

CARRIAGE FLAT ACRYLIC HOUSE PAINT / #24 BLAC

### **Manufacturer**

BRUNING PAINT

### **Product Identification**

Product ID: CARRIAGE FLAT ACRYLIC HOUSE PAINT / #24 BLAC

MSDS Date: 01/01/1987

FSC: 8010

NIIN: 00F004270

MSDS Number: BBPWR

### **Responsible Party**

BRUNING PAINT / BALTIMORE, MD 21224

Emergency Phone: (301) 342-3641

Cage: EO841

### **Contractor**

KYANIZE PAINT

BALTIMORE, MD 21224

US

800-368-2076

Cage: 85520

### **Ingredients**

SILICON DIOXIDE

RTECS: VV7320000

Fraction By Weight: 35%

ACGIH TLV: .10 MG/CUM

ETHYLENE GLYCOL (SARA III)

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight: 1-5%

OSHA PELC 50 PPM

ACGIH TLV: C 50 PPM, VAPOR; 9192

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

### **Hazards**

Effects of Overexposure: CONTACT WITH EYES OR SKIN MAY CAUSE IRRITATION.

### **First Aid**

First Aid: INHALATION: REMOVE TO FRESH AIR. EYES: FLUSH W/WATER FOR AT

LEAST 15 MINUTES. SKIN: REMOVE WITH SOAP/WATER. REMOVE CONTAMINATED CLOTHING. INGESTION: DRINK 1 OR 2 GLASSES OF WATER. DON'T INDUCE VOMITIN G, CONSULT PHYSICIAN IMMEDIATELY.

## Fire Fighting

Fire Fighting Procedures:WATER COOL CONTAINERS TO PREVENT PRESSURE BUILDUP/EXPLOSION.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE DUE TO PRESSURE BUILD-UP WHEN EXPOSED TO EXTREME HEAT.

## Accidental Release

Spill Release Procedures:DIKE/ABSORB SPILL WITH INERT MATERIAL (SAND/VERMICULITE, ETC). AND TRANSFER TO CONTAER FOR DISPOSAL. WASH UP RESIDUE WITH SOAP AND WATER.

## Handling

Handling and Storage Precautions:KEEP FROM FREEZING. DON'T STORE >120F. Other Precautions:CLOSE CONTAINER AFTER EACH USE. KEEP OUT OF REACH OF CHILDREN.

## Exposure Controls

Respiratory Protection:APPROVED MECH FILTER RESP TO REMOVE SOLID AIRBORNE OF OVERSPRAY

Ventilation:PROVIDE LOCAL EXHAUST VENTILATION TO KEEP BELOW TLV.

Protective Gloves:IMPERVIOUS

Eye Protection:GOGGLES/SAFETY EYEWEAR

Other Protective Equipment:USE PETROLEUM JELLY WHERE PROLONGED SKIN CONTACT IS LIKELY.

Supplemental Safety and Health

MSDS DATE: 20 AUG 86. WT/GAL: 10.6.

## Chemical Properties

Boiling Pt:B.P. Text:490F

Vapor Pres:.08

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN BU AC

Percent Volatiles by Volume:62.4

## Stability

Stability Indicator/Materials to Avoid:YES

NONE REASONABLY FORESEEABLE

Stability Condition to Avoid:HIGH TEMPERATURES.

Hazardous Decomposition Products:CO AND CO2 WHEN BURNED.

## Disposal

Waste Disposal Methods:LANDFILL ACCORDING TO FEDERAL, STATE AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.