

E-260, TT-E-508C COLOR 20122

MSDS Number

BBPXB

National Stock Number

8010-00F004278

Product Name

E-260, TT-E-508C COLOR 20122

Manufacturer

CROWN PAINT COMPANY

Product Identification

Product ID:E-260, TT-E-508C COLOR 20122

MSDS Date:01/01/1987

FSC:8010

NIIN:00F004278

MSDS Number: BBPXB

Responsible Party

CROWN PAINT COMPANY

1400 N.E. 4TH STREET

OKLAHOMA CITY , OK 73117

Emergency Phone: (405) 232-8580

Info Phone: (405) 232-8580

Cage: OG5U8

Contractor

CROWN PAINT COMPANY

350

OKLAHOMA CITY, OK 73106

US

(105) 232-8580

Cage: OG5U8

Ingredients

HYDROTREATED LIGHT DISTILLATE, PETROLEUM; C12-C15

CAS: 64742-47-8

OSHA PEL500 PPM

ACGIH TLV: 100 PPM

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

Hazards

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:INHALATION: NERVOUS SYSTEM DEPRESSION,
HEADACHE, DIZZINESS, STAGGERING GAIT, CONFUSION, UNCONSCIOUSNESS OR
COMA. SKIN/EYE: IRRITATION/DERMATITIS. INGESTION: HARMFUL OR FATAL.
Explanation of Carcinogenicity:NONE
Effects of Overexposure:INHALATION: HEADACHE, DIZZINESS, STAGGERING
GAIT, CONFUSION, UNCONSCIOUSNESS, COMA, CONFUSION. SKIN:
DERMATITIS. INGESTION: HARMFUL OR FATAL.
Medical Cond Aggravated by Exposure:DERMATITIS/LIVER ADNORMALITIES

First Aid

First Aid:EYES/SKIN: FLUSH W/WATER FOR AT LEAST 15 MINUTES. GET MED
ATT. INHALATION: REMOVE FROM EXPOSURE. RESTORE BREATHING. GET MED
ATT.

Fire Fighting

Flash Point:103F
Lower Limits:1.0%
Upper Limits:7.0%
Extinguishing Media:FOAM, CO2, DRY CHEMICAL
Fire Fighting Procedures:WATER SPRAY MAY BE INEFFECTIVE. IF WATER IS
USED, FOG NOZZLES ARE PREFERABLE.
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE IF EXPOSED
TO EXTREME HEAT.

Accidental Release

Spill Release Procedures:ABSORB SPILL ON PAPER VERMICULITE FLOOR
ABSORBENT, OR OTHER ABSORBENT MATERIAL.

Handling

Handling and Storage Precautions:CONTAINERS OF THIS PRODUCT MAY BE
HAZARDOUS WHEN EMPTIED. EMPTIED CONTAINERS RETAINS PRODUCT
RESIDUALS.

Exposure Controls

Respiratory Protection:COMBINATION DUST/VAPOR RESPIRATOR.
Ventilation:PROVIDE MECHANICAL VENTILATION TO KEEP Protective Gloves:RUBBER, BUNA-N
Eye Protection:CHEMICAL SPLASH GOGGLES
Other Protective Equipment:IMPERVIOUS CLOTHING/BOOTS
Supplemental Safety and Health

Chemical Properties

Boiling Pt:B.P. Text:279F
Vapor Pres:5.1
Vapor Density:4.9
Spec Gravity:1.36
Evaporation Rate & Reference:(BU AC = 1): 0.10
Solubility in Water:NEGLIGIBLE
Appearance and Odor:BROWN LIQUID, MINERAL SPIRITS ODOR.

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS
Hazardous Decomposition Products:CO, CO2

Disposal

Waste Disposal Methods:DESTROY BY LIQUID INCINERATION OR TOXIC
SUBSTANCE LANDFILL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their particular situation.