

COLOR 36622, M-100

MSDS Number

BBPXC

National Stock Number

8010-00F004279

Product Name

COLOR 36622, M-100

Manufacturer

CROWN PAINT

Product Identification

Product ID: COLOR 36622, M-100

MSDS Date: 01/01/1987

FSC: 8010

NIIN: 00F004279

MSDS Number: BBPXC

Responsible Party

CROWN PAINT/OKLAHOMA CITY, OK 73117

Emergency Phone: (405) 232-8580

Cage: EO844

Contractor

CROWN PAINT/OKLAHOMA CITY, OK 73117

350

HEBRON, IL 60034

US

815-648-2424

Cage: EO844

Ingredients

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 52%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

ALCOHOL (VAPOR PRESSURE = .3)

Fraction By Weight: 4%

ACGIH TLV: 50 PPM

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 4.5%
OSHA PEL100 PPM/150 STEL
ACGIH TLV: 100 PPM/150STEL;9192
EPA Report Quantity: 1000 LBS
DOT Report Quantity: 1000 LBS

ESTER (VAPOR PRESSURE = .09)

Fraction By Weight: 2.9%
ACGIH TLV: 100 PPM

Hazards

Effects of
Overexposure:HEADACHE/DIZZINESS/STAGGERING/CONFUSION/UNCONSCIOUSNES
S/COMA. SKIN/EYE CONT: PRIMARY IRRITATION.

First Aid

First Aid:EYE/SKIN: FLUSH WITH WATER FOR AT LEAST 15 MINUTES. IF
IRRITATED GET MEDICAL ATTENTION. VAPORS: REMOVE FROM EXPOSURE
RESTORE BREATHING. SWALLOWING: CALL PHYSICIAN IMMEDIATELY. DON'T
INDUCE VOMITING.

Fire Fighting

Flash Point:45F
Lower Limits:1.1%
Extinguishing Media:FOAM, CO2
Fire Fighting Procedures:WATER MAY BE INEFFECTIVE. WATER COOL
CONTAINERS.
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE IF EXPOSED
TO EXTREME HEAT.

Accidental Release

Spill Release Procedures:ABSORB SPILL ON PAPER VERMICULITE FLOOR
ABSORBENT, OR OTHER ABSORBENT MATERIAL.

Handling

Handling and Storage Precautions:FLAMMABLE LIQUID DON'T USE NEAR
SPARKS/FIRE OR OPEN FLAMES.
Other Precautions:EMPTY CONTAINERS MAY BE HAZARDOUS WHEN EMPTIED.
GROUND CONTAINERS IN EXPLOSIVE ATMOSPHERE WHEN POURING LIQUID.

Exposure Controls

Respiratory Protection:IF TLV IS EXCEEDED WEAR APPROVED SCBA W/FULL
FACE PIECE.
Ventilation:PROVIDE LOCAL EXHAUST/MECH VENTILATION TO KEEP BELOW TLV
Protective Gloves:RESISTANT
Eye Protection:GOGGLES OR SAFETY GLASSES
Other Protective Equipment:TO PREV PROLONGED SKIN CONT WEAR IMPERVIOUS
CLOTHING/BOOTS.
Supplemental Safety and Health
MSDS DATE: 25 AUG 86. WT PER GAL: 8.5

Chemical Properties

Boiling Pt:B.P. Text:229-329F
Vapor Density:>AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:63.4

Stability

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:AVOID CONTACT WITH STRONG OXIDIZERS

Disposal

Waste Disposal Methods:DESTROY BY LIQUID INCINERATION OR TOXIC SUBSTANCE LANDFILL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.