https://msdsreport.com/msds/BBPXH

# **CLEANER CONCENTRATE, 00-013**

### **MSDS Number**

BBPXH

### **National Stock Number**

7930-00F004284

#### **Product Name**

CLEANER CONCENTRATE, 00-013

## Manufacturer

CRAWFORD

### **Product Identification**

Product ID:CLEANER CONCENTRATE, 00-013 MSDS Date:01/01/1987 FSC:7930 NIIN:00F004284 MSDS Number: BBPXH

### **Responsible Party**

CRAWFORD/CHICAGO, IL 60609

Emergency Phone: (312) 433-1307

Cage: EO848

### Contractor

CRAWFORD/CHICAGO, IL 60609

CHICAGO, IL 60609

US

312-376-7132

Cage: EO848

#### Ingredients

CYANURIC ACID

CAS: 108-80-5

RTECS: XZ1800000

Fraction By Weight: 30%

GLYCOL ETHERS (VAPOR PRESSURE = .88)

Fraction By Weight: 5%

ACGIH TLV: 25 PPM

### Hazards

Effects of Overexposure:HEADACHE/DIZZINESS/DEFATTING/DRYING OF THE SKIN/IRRITATION OF THE MUCOUS MEMBRANES.

### **First Aid**

First Aid:EYE: FLUSH W/WATER FOR 15 MINS. GET MED ATT. INHALATION: REMOVE VICTIM TO FRESH AIR/PROVIDE OXYGEN IF BREATHING IS DIFFICULT. INGESTION: DON'T INDUCE VOMITING. GIVE WATER/MILK. CALL PHYS. IF VOMITING OCCURS SPONTANEOUSLY, ADMINISTER FLUIDSAGAIN.

## **Fire Fighting**

Flash Point:148F SETA



#### Lower Limits:1.1%

Extinguishing Media:FOAM, CO2, OR DRY CHEMICAL Fire Fighting Procedures:WEAR SCBA. WATER TO COOL CONTAINERS/KEEP STRUCTURES WET. Unusual Fire/Explosion Hazard:WATER PRESSURE MAY SPREAD/FLAMMABLE LIQUID FIRE. SEALED CONTAINERS MAY EXPLODE IF OVERHEATED.

•

#### **Accidental Release**

Spill Release Procedures:WARNING-COMBUSTIBLE. ELIMINATE ALL IGNITION SOURCES. HANDLING EQUIPMENT MUST BE GROUED TO PREVENT SPARKING. WEAR THE PROTECTIVE CLOTHING. SOAK UP W/AN ABSORNT/PLACE IN NON-LEAKING CONTAINERS. SEAL TIG HTLY FOR PROPER DISPOSAL.

#### Handling

Handling and Storage Precautions:TREAT AS ANY HAZARDOUS-COMBUSTIBLE MATERIAL; STORE IN A COOL, DRY PLACE IN BLDGS DESIGNED FOR E STORAGE OF COMBUSTIBLE LIQUIDS.

#### **Exposure Controls**

Respiratory Protection:USE NIOSH APPROVED ORGANIC VAPOR RESP WHERE VENT. IS INADEQUATE. Ventilation:PROVIDE LOCAL EXHAUST VENTILATION TO KEEP BELOW TLV Protective Gloves:RUBBER Eye Protection:SAFETY GLASSES Other Protective Equipment:HAVE EYE BATH AND SAFETY SHOWER AVAILABLE. Supplemental Safety and Health MSDS DATE: 20 JAN 86. WGT PER GAL: 9.74 PDS.

#### **Chemical Properties**

Boiling Pt:B.P. Text:212F-340F Vapor Density:>AIR Evaporation Rate & Reference:(N-BUAC = 1) 0.09 Appearance and Odor:CLEAR LIQUID. Percent Volatiles by Volume:7.2%

#### Stability

Stability Indicator/Materials to Avoid:YES ALKALIES/ALUMINUM/LEATHER/WOOL/TIN/ZINC. \_ Stability Condition to Avoid:AVOID HEAT/SPARKS/OPEN FLAMES/INCOMPATABILITIES. \_ Hazardous Decomposition Products:HYDROGEN GAS MAY BE FORMED DURING COMBUSTION.

#### Disposal

Waste Disposal Methods: DISPOSAL MUST BE IN ACCORDANCE WITH CURRENT LOCAL, STATE AND FEDERAL REGULATION. CONTACT AN APPROVED DISPOSAL FACILITY.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.