

CUPRINOL SOLID-COLOR STAIN/WOOD PRESERV

MSDS Number

BBPXT

National Stock Number

8010-00F004294

Product Name

CUPRINOL SOLID-COLOR STAIN/WOOD PRESERV

Manufacturer

DARWORTH

Product Identification

Product ID: CUPRINOL SOLID-COLOR STAIN/WOOD PRESERV

MSDS Date: 01/01/1987

FSC: 8010

NIIN: 00F004294

MSDS Number: BBPXT

Responsible Party

DARWORTH/AVON, CT 06001

Emergency Phone: (203) 677-7721

Cage: EO851

Contractor

DARWORTH/AVON, CT 06001

MEDFIELD, MA 02052-2308

US

508-359-7711/ 800-255-8769

Cage: EO851

Ingredients

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: SE7555000

Fraction By Weight: 50%

OSHA PEL100 PPM

BIS (TRIBUTYL TIN) OXIDE

CAS: 56-35-9

RTECS: JN8750000

Fraction By Weight: 0.5%

OSHA PELS, 0.1 MG/M3 (SN)

ACGIH TLV: S, 0.1 MG/M3 (SN); 8990

N-(TRICHLOROMETHYLTHIO) PHTHALIMIDE

CAS: 133-07-3

RTECS: TI5685000

Fraction By Weight: 0.7%

Hazards

Effects of Overexposure:SKIN/EYE: PRIMARY IRRITATION. HEADACHE, DIZZINESS, CONFUSION OR UNCONSCIOUSNESS.

First Aid

First Aid:EYE: FLUSH W/WATER FOR AT LEAST 15 MINUTES. CONSULT A PHYS. SKIN: WASH AFFECTED AREAS WITH SOAP/WATER. REMOVE CONTAMINATED CLOTHING. CONSULT A PHYS. INHALATION: MOVE TO FRESH AIR. RESTORE BREATHING. INGESTION: DON'T INDUCE VOMITING. OBTAIN MED ATT.

Fire Fighting

Flash Point:104F
Extinguishing Media:FOAM, CO2, DRY CHEMICAL
Fire Fighting Procedures:WATER COOL CONTAINERS TO PREV PRESSURE BUILD-UP/EXPLOSION.
Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. VENTILATE AREA. CONTAIN/REMO WITH INERT ABSORBANT AND NON-SPARKING TOOLS.

Handling

Handling and Storage Precautions:CAUTION: COMBUSTIBLE. KEEP AWAY FROM HEAT/OPEN FLAME. USE W/ADEQUATE VENTILATION. AVOID PROLONGED INHALATION OF VAPORS. HARMFUL IF SWALLOWED.

Exposure Controls

Respiratory Protection:IF EXCEED TLV, USE NIOSH APPROVED RESP FOR PETROLEUM VAPORS.
Ventilation:LOCAL EXHAUST: INDOORS: DON'T USE IN A CONFINED SPACE.
Protective Gloves:RUBBER
Eye Protection:USE SAFETY EYEWEAR
Supplemental Safety and Health
MSDS DATE: 21 SEPT 84.

Chemical Properties

Boiling Pt:B.P. Text:305-410F
Vapor Pres:2
Vapor Density:>AIR
Spec Gravity:1.19
Evaporation Rate & Reference:SLOWER THAN ETHER
Solubility in Water:NEGLIGIBLE
Appearance and Odor:MINERAL SPIRITS ODOR
Percent Volatiles by Volume:61%

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDANTS
Hazardous Decomposition Products:CO, CO2

Disposal

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DON'T INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.