

# **MYSTIK JT-8 MOTOR OILS, C-1289**

## **MSDS Number**

**BBPYS** 

#### **National Stock Number**

9150-00F004314

#### **Product Name**

MYSTIK JT-8 MOTOR OILS, C-1289

#### Manufacturer

CATO OIL AND GREASE

## **Product Identification**

Product ID:MYSTIK JT-8 MOTOR OILS, C-1289 MSDS Date:01/01/1987 FSC:9150 NIIN:00F004314 MSDS Number: BBPYS

## **Responsible Party**

CATO OIL & GREASE/OKLAHOMA CITY, OK 73126

Emergency Phone: (405) 424-3311

Cage: EO800

## Contractor

CATO OIL AND GREASE CO INC

26868

OKLAHOMA CITY, OK 73126

US

Cage: 3F020

# Ingredients

PETROLEUM OIL

Fraction By Weight: 99.5% ACGIH TLV: 5 MG/CUM

**ADDITIVES** 

Fraction By Weight: 1.5%

## **Hazards**

Effects of Overexposure: EYE/SKIN: IRRITATION W/PROLONGED OR REPEATED CONTACT. POSSIBLE IRRITATION/NAUSEA/DIARRHEA.

## First Aid

First Aid:INHALATION: MOVE TO FRESH AIR. IF BREATHING HAS STOPPED, ARTIFICIAL RESP. EYE: FLUSH W/WATER FOR 15 MINUTES. SKIN: IF CLOTHING IS SOAKED, REMOVE CLOTHING/ WASH W/SOAP & WATER. LAUNDER CLOTHING BEFORE WEARING. INGESTION: DON'T INDUCE VOMITING.

# Fire Fighting

Flash Point:400F (COC)
Extinguishing Media:CO2, DRY CHEMICAL OR FOAM.
Fire Fighting Procedures:WATER STREAM MAY SPREAD FIRE, USE WATER COOL CONTAINERS.
Unusual Fire/Explosion Hazard:CAN FORM FLAMMABLE MIXTURES W/AIR WHEN



HEATED TO APPROXIMATELY 400F. WILL NOT FLASH SPONTANEOUSLY.

#### **Accidental Release**

Spill Release Procedures: EVACUATE AREA/REMOVE IGNITION SOURCES. BUILD DIKE TO CONTAIN FLOW. REMOVE FREE LIQUI DON'T FLUSH TO SEWER OR OPEN WATER. PICK UP WITH INERT ABSORBENT AND PLE IN CLOSED CONTAINER FOR DISPOSAL.

## Handling

Handling and Storage Precautions: DO NOT STORE WITH STRONG OXIDIZERS.

# **Exposure Controls**

Respiratory Protection:IF >TLV, ORGANIC VAPOR RESP OR FULL-FACE

SUPPLIED AIR RESP.

Ventilation: PROVIDE LOCAL EXHAUST VENTILATION TO KEEP BELOW 5MG/CUM.

Protective Gloves: NEOPRENE/NITRIL

Eye Protection: GLASSES/GOGGLES/FACESHIEL

Supplemental Safety and Health

MSDS DATE: 23 OCT 85. MELTING POINT: -30F-5F.

## **Chemical Properties**

Boiling Pt:B.P. Text:>600F Vapor Pres:Spec Gravity:0.90

Evaporation Rate & Reference: SLOWER THAN ETHER

Solubility in Water: NEGLIGIBLE

Appearance and Odor: AMBER LIQUID; MILD PETROLEUM ODOR.

## **Stability**

Stability Indicator/Materials to Avoid:YES DON'T STORE WITH STRONG OXIDIZERS. Hazardous Decomposition Products:CO AND VARIOUS HYDROCARBONS.

# **Disposal**

Waste Disposal Methods: UTILIZE LICENSED WASTE DISPOSAL COMPANY. CONSIDER RECYCLING OR INCINERATION. UTILIZE PERMITTED INDUSTRIAL WASTE DISPOSAL SITE.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.