

## **DRAM T-BL THALO BL, #1756**

### **MSDS Number**

BBPYY

### **National Stock Number**

8010-00F004319

### **Product Name**

DRAM T-BL THALO BL, #1756

### **Manufacturer**

GLIDDEN DIV

### **Product Identification**

Product ID:DRAM T-BL THALO BL, #1756

MSDS Date:01/01/1987

FSC:8010

NIIN:00F004319

MSDS Number: BBPYY

### **Responsible Party**

GLIDDEN DIV/SCM CORP/CLEVELAND, OH 44115

Emergency Phone: (216) 826-5566

Cage: EO860

### **Contractor**

GLIDDEN DIV/SCM CORP

15049

CLEVELAND, OH 44115

US

(216) 826-5566

Cage: EO860

### **Ingredients**

ETHYLENE GLYCOL (SARA III)

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight: 25%

OSHA PELC 50 PPM

ACGIH TLV: C 50 PPM,VAPOR; 9192

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

ALUMINUM SILICATE (AS NUISANCE DUST OR PARTICULATES NOT

CAS: 1302-76-7

RTECS: BD1450000

Fraction By Weight: 37%

OSHA PEL15 MG/M3 TOTAL DUST

ACGIH TLV: 10 MG/M3 TDUST;8990

### **Hazards**

Effects of Overexposure:EYES/SKIN: IRRITATION. INHALATION: DIZZINESS, LIGHTHEADEDNESS, NAUSEA, VOMITING.

## First Aid

First Aid:INHALATION: REMOVE PERSON TO WELL VENTILATED AREA. ADMINISTER OXYGEN. SKIN: WATER W/WATER. THEN WASH W/SOAP & WATER. REMOVE CONTAMINATED CLOTHING. WASH CONTAMINATED CLOTHING BEFORE RE-USE. EYES: FLUSH W/WATER FOR AT LEAST 15 MINUTES. GET MED ATT.

## Fire Fighting

Flash Point:>200F  
Extinguishing Media:DRY CHEMICAL OR FOAM  
Fire Fighting Procedures:WATER MAY BE USED TO COOL/PROTECT EXPOSED CONTAINERS.  
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY BURST IF EXPOSED TO EXTREME HEAT OR FIRE.

## Accidental Release

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. VENTILATE AREA. SMALL SPILLS MAY BE COLLECTED WITH ABSORBENT MATERIALS.

## Handling

Handling and Storage Precautions:STORE TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN. AVOID CONTACT W/SKIN/EYES/BREATHING OF VAPORS.  
Other Precautions:WASH HANDS AFTER HANDLING, BEFORE EATING OR SMOKING. KEEP CONTAINERS TIGHTLY CLOSED/UPRIGHT WHEN NOT IN USE. AVOID BREATHING AND DUST. EMPTY CONTAINERS MAY CONTAIN HAZARDOUS RESIDUES.

## Exposure Controls

Respiratory Protection:USE ONLY NIOSH/MSHA APPROVED RESPIRATORS.  
Ventilation:PROVIDE LOCAL EXHAUST VENT TO PREVENT BUILD-UP OF VAPORS  
Protective Gloves:IMPERVIOUS  
Eye Protection:SAFETY GLASSES/GOGGLES  
Other Protective Equipment:EYE WASH/SAFETY SHOWER.  
Supplemental Safety and Health  
MSDS DATE: 25 MAR 86. WGT PER GAL: 11.67

## Chemical Properties

Percent Volatiles by Volume:59.1

## Stability

Stability Indicator/Materials to Avoid:YES  
OXIDIZERS  
Hazardous Decomposition Products:CO, CO2

## Disposal

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS. AVOID DISCHARGE TO NATURAL WATERS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.