

## **DRAMATONE WHITE, #1760**

### **MSDS Number**

BBPYZ

### **National Stock Number**

8010-00F004320

### **Product Name**

DRAMATONE WHITE, #1760

### **Manufacturer**

GLIDDEN DIV

### **Product Identification**

Product ID:DRAMATONE WHITE, #1760

MSDS Date:01/01/1987

FSC:8010

NIIN:00F004320

Status Code:A

MSDS Number: BBPYZ

### **Responsible Party**

GLIDDEN DIV/SCM CORP/CLEVELAND, OH 44115

Emergency Phone: (216) 826-5566

Cage: EO860

### **Contractor**

GLIDDEN PAINT, ICI PAINTS NORTH AMERICA

CLEVELAND, OH 44115

US

800-545-2643/216-344-8207

Cage: 01PD6

### **Ingredients**

TITANIUM DIOXIDE

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight: 58%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

ETHYLENE GLYCOL (SARA III)

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight: 14%

OSHA PELC 50 PPM

ACGIH TLV: C 50 PPM,VAPOR; 9192

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

ALUMINUM SILICATE (AS NUISANCE DUST OR PARTICULATES NOT

CAS: 1302-76-7

RTECS: BD1450000

Fraction By Weight: 9%

OSHA PEL15 MG/M3 TOTAL DUST

ACGIH TLV: 10 MG/M3 TDUST;8990

## Hazards

Effects of Overexposure:EYES/SKIN: IRRITATION. INHALATION: DIZZINESS, LIGHTHEADEDNESS, NAUSEA, VOMITING.

## First Aid

First Aid:INHALATION: REMOVE PERSON TO WELL VENTILATED AREA. ADMINISTER OXYGEN. SKIN: FLUSH W/WATER, THEN WASH W/SOAP & WATER. REMOVE CONTAMINATED CLOTHING. WASH CONTAMINATED CLOTHING BEFORE RE-USE. EYES: FLUSH W/WATER FOR AT LEAST 15 MINUTES. GET MED ATT.

## Fire Fighting

Flash Point:>200F

Extinguishing Media:DRY CHEMICAL OR FOAM

Fire Fighting Procedures:WATER MAY BE USED TO COOL/PROTECT EXPOSED CONTAINERS.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY BURST IF EXPOSED TO EXTREME HEAT OR FIRE.

## Accidental Release

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. VENTILATE AREA. SMALL SPILLS MAY BE COLLECTED WITH ABSORBENT MATERIALS.

## Handling

Handling and Storage Precautions:STORE BELOW FREEZING. DON'T TAKE INTERNALLY. KEEP OUT OF REACH OF CHILDREN. OI D CONTACT WITH SKIN/EYES/BREATHING OF VAPORS.

Other Precautions:WASH HANDS AFTER HANDLING, BEFORE EATING OR SMOKING.

KEEP CONTAINERS TIGHTLY CLOSED/UPRIGHT WHEN NOT IN USE. AVOID BREATHING AND DUST. EMPTY CONTAINERS MAY CONTAIN HAZARDOUS RESIDUES.

## Exposure Controls

Respiratory Protection:USE ONLY NIOSH/MSHA APPROVED RESPIRATORS.

Ventilation:PROVIDE LOCAL EXHAUST VENT TO PREVENT BUILD-UP OF VAPORS

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY GLASSES OR GOGGLES

Other Protective Equipment:EYE WASH/SAFETY SHOWER.

Supplemental Safety and Health

MSDS DATE: 25 MAR 86. WGT PER GAL: 17.09

## Chemical Properties

Percent Volatiles by Volume:45.5

## Stability

Stability Indicator/Materials to Avoid:YES

OXIDIZERS

Hazardous Decomposition Products:CO, CO2

## Disposal

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS. AVOID DISCHARGE TO NATURAL WATERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.