

SPRED LATEX GLOSS HOUSE PAINT-WHITE, #3900

MSDS Number

BBPZH

National Stock Number

8010-00F004326

Product Name

SPRED LATEX GLOSS HOUSE PAINT-WHITE, #3900

Manufacturer

GIDDEN DIV

Product Identification

Product ID:SPRED LATEX GLOSS HOUSE PAINT-WHITE, #3900

MSDS Date:01/01/1987

FSC:8010

NIIN:00F004326

MSDS Number: BBPZH

Responsible Party

GIDDEN DIV/SCM CORP/CLEVELAND, OH 44115

Emergency Phone: (216) 826-5566

Cage: EO863

Contractor

GLIDDEN CO MEMBER OF ICI WORLD PAINTS

15049

CLEVELAND, OH 44115

US

216-344-8000

Cage: 72818

Ingredients

ETHYLENE GLYCOL (SARA III)

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight: 5%

OSHA PELC 50 PPM

ACGIH TLV: C 50 PPM,VAPOR; 9192

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

ESTER ALCOHOL (VAPOR PRESSURE = 1.00)

CAS: 25265-77-4

RTECS: UF6000000

Fraction By Weight: 2%

TITANIUM DIOXIDE

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight: 24%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

Hazards

Effects of Overexposure:EYES/SKIN: IRRITATION. INHALATION:
DIZZINESS/LIGHTHEADEDNESS/NAUSEA/VOMITING.

First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. RESTORE BREATHING. GIVE
OXYGEN. SKIN: WASH W/WATER & SOAP. REMOVE CONTAMINATED CLOTHING.
WASH CONTAMINATED CLOTHING BEFORE RE-USE. EYE: FLUSH W/WATER FOR AT
LEAST 15 M INS. INGESTION: IF SWALLOWED: GET MED TREATMENT

Fire Fighting

Flash Point:>200F
Extinguishing Media:DRY CHEMICAL OR FOAM
Fire Fighting Procedures:WATER MAY BE USE TO COOL/PROTECT EXPOSED
CONTAINERS.
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY BURST IF EXPOSED TO
EXTREME HEAT OR FIRE.

Accidental Release

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. VENTILATE
AREA. SMALL SPILLS MAY BE COLLECTED WITH ABSORBENT MATERIALS.

Handling

Handling and Storage Precautions:STORE BELOW INTERNALLY. KEEP OUT OF REACH OF CHILDREN. AVOID CONTACT WITH
SK/EYES/BREATHING OF VAPORS.
Other Precautions:WASH HANDS AFTER HANDLING, BEFORE EATING OR SMOKING.
KEEP CONTAINERS TIGHTLY CLOSED/UPRIGHT WHEN NOT IN USE. AVOID
BREATHING AND DUST.

Exposure Controls

Respiratory Protection:USE ONLY NIOSH/MSHA APPROVED RESPIRATORS.
Ventilation:PROVIDE LOCAL EXHAUST VENT TO PREVENT BUILD-UP OF VAPORS
Protective Gloves:IMPERVIOUS
Eye Protection:SAFETY GLASSES OR GOGGLES
Other Protective Equipment:EYE WASH/SAFETY SHOWER.
Supplemental Safety and Health
MSDS DATE: 31 JUN 1986. WEIGHT PER GAL: 10.56

Chemical Properties

Percent Volatiles by Volume:65.4

Stability

Stability Indicator/Materials to Avoid:YES
OXIDIZERS
Stability Condition to Avoid:ELEVATED TEMPERATURES. CONTACT WITH
OXIDIZING AGENT
Hazardous Decomposition Products:CO, CO2

Disposal

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH ALL APPLICABLE
REGULATIONS. AVOID DISCHARGE TO NATURAL WATERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their

particular situation.