

SPRED LATEX GLOSS H.P. BLACK, #3979

MSDS Number

BBPZJ

National Stock Number

8010-00F004327

Product Name

SPRED LATEX GLOSS H.P. BLACK, #3979

Manufacturer

GLIDDEN DIV

Product Identification

Product ID:SPRED LATEX GLOSS H.P. BLACK, #3979

MSDS Date:01/01/1987

FSC:8010

NIIN:00F004327

MSDS Number: BBPZJ

Responsible Party

GLIDDEN DIV/SCM CORP/CLEVELAND, OH 44115

Emergency Phone: (216) 826-5566

Cage: EO860

Contractor

GLIDDEN DIV/SCM CORP

15049

CLEVELAND, OH 44115

US

(216) 826-5566

Cage: EO860

Ingredients

ETHYLENE GLYCOL (SARA III)

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight: 3%

OSHA PELC 50 PPM

ACGIH TLV: C 50 PPM,VAPOR; 9192

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

ESTER ALCOHOL (VAPOR PRESSURE = 1.00)

CAS: 25265-77-4

RTECS: UF6000000

Fraction By Weight: 3%

Hazards

Effects of Overexposure:EYES IRRITATION. INHALATION:
DIZZINESS/LIGHTHEADEDNESS/NAUSEA/VOMITING.

First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. RESTORE BREATHING. SKIN: WASH W/WATER & SOAP. REMOVE CONTAMINATED CLOTHING. WASH CONTAMINATED CLOTHING BEFORE RE-USE. EYE: FLUSH W/WATER FOR AT LEAST 15 MINUTES. INGES TION: IF SWALLOWED, OBTAIN MEDICAL TREATMENT.

Fire Fighting

Flash Point:>200F
Extinguishing Media:DRY CHEMICAL OR FOAM
Fire Fighting Procedures:WATER MAY BE USED TO COOL/PROTECT EXPOSED CONTAINERS.
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY BURST IF EXPOSED TO EXTREME HEAT OR FIRE.

Accidental Release

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. VENTILATE AREA. SMALL SPILLS MAY BE COLLECTED WITABSORBENT MATERIALS.

Handling

Handling and Storage Precautions:STORE BELOW ADEQUATE VENTILATION. DON'T TAKE INTERNALLY. KEEP OUT OF REACOF CHILDREN.
Other Precautions:AVOID CONTACT WITH SKIN/EYES/BREATHING OF VAPORS. WASH AFTER HANDLING, BEFORE EATING OR SMOKING. KEEP CONTAINERS TIGHTLY CLOD AND UPRIGHT WHEN NOT IN USE.

Exposure Controls

Respiratory Protection:USE ONLY NIOSH/MSHA APPROVED RESPIRATORS
Ventilation:PROVIDE LOCAL EXHAUST VENT TO PREVENT BUILD-UP OF VAPORS
Protective Gloves:IMPERVIOUS
Eye Protection:SAFETY GLASSES OR GOGGLES
Other Protective Equipment:EYE WASH/SAFETY SHOWER.
Supplemental Safety and Health
MSDS DATE: 31 JUN 86. WGT PER GAL: 8.71.

Chemical Properties

Percent Volatiles by Volume:71.7

Stability

Stability Indicator/Materials to Avoid:YES
OXIDIZERS
Stability Condition to Avoid:ELEVATED TEMPERATURES. CONTACT WITH OXIDIZING AGENT
Hazardous Decomposition Products:CO, CO2

Disposal

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH ALL APPLICABLE REGULATIONS. AVOID DISCHARGE TO NATURAL WATERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.