

CONVENTIONAL TRAFFIC PAINT-YELLOW, #63228

MSDS Number

BBQBD

National Stock Number

8010-00F004344

Product Name

CONVENTIONAL TRAFFIC PAINT-YELLOW, #63228

Manufacturer

GLIDDEN DIV

Product Identification

Product ID: CONVENTIONAL TRAFFIC PAINT-YELLOW, #63228

MSDS Date: 01/01/1987

FSC: 8010

NIIN: 00F004344

MSDS Number: BBQBD

Responsible Party

GLIDDEN DIV/SCM CORP/CLEVELAND, OH 44115

Emergency Phone: (216) 826-5566

Cage: EO860

Contractor

GLIDDEN DIV/SCM CORP

15049

CLEVELAND, OH 44115

US

(216) 826-5566

Cage: EO860

Ingredients

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: SE7555000

Fraction By Weight: 20%

OSHA PEL100 PPM

SILICA, CRYSTALLINE - QUARTZ

CAS: 14808-60-7

RTECS: VV7330000

Fraction By Weight: 16%

OSHA PELSEE TABLE Z3

ACGIH TLV: 0.1 MG/M3 RDUST;9293

CALCIUM CARBONATE

RTECS: EU9580000

Fraction By Weight: 15%

ACGIH TLV: 10 MG/CUM

ALUMINUM SILICATE (AS NUISANCE DUST OR PARTICULATES NOT

CAS: 1302-76-7

RTECS: BD1450000

Fraction By Weight: 8%

OSHA PEL15 MG/M3 TOTAL DUST

ACGIH TLV: 10 MG/M3 TDUST;8990

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 5 - 10%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

Hazards

Effects of Overexposure:EYES/SKIN: IRRITATION/RESP TRACT. INHALATION:
DIZZINESS/LIGHTHEADEDNESS/HEADACHE/NAUSEA.

First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. RESTORE BREATHING. SKIN:
WASH W/WATER & SOAP. REMOVE CONTAMINATED CLOTHING/WASH CLOTHING
BEFORE RE-USE. EYE: FLUSH W/WATER FOR 15 MINUTES. INGESTION: IF
SWALLOWED, OBTAIN MEDICAL TREATMENT.

Fire Fighting

Flash Point:25F

Lower Limits:.9%

Extinguishing Media:DRY CHEMICAL OR FOAM

Fire Fighting Procedures:WATER MAY BE USED TO COOL/PROTECT EXPOSED
CONTAINERS.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN
EXPOSED TO EXTREME HEAT OR FIRE. VAPORS MAY IGNITE EXPLOSIVELY.

Accidental Release

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. VENTILATE
AREA W/EXPLOSION-PROOF EQUIPMENT. SMALLPILLS MAY BE COLLECTED WITH
ABSORBENT MATERIALS. USE NON-SPARKING TOOLS. ACUATE ALL UNNECESSARY
PERSONNEL. SHUT OFF LEAK IF SAFE TO DO SO.

Handling

Handling and Storage Precautions:STORE BELOW 80F. DON'T TAKE
INTERNALLY. KEEP OUT OF REACH OF CHILDREN. AVOID CONTACT WITH
SKINEYES & BREATHING OF VAPORS.

Other Precautions:WASH HANDS AFTER HANDLING, BEFORE EATING OR SMOKING.
KEEP CONTAINERS TIGHTLY CLOSED AND UPRIGHT WHEN NOT IN USE.

Exposure Controls

Respiratory Protection:USE ONLY NIOSH/MSHA APPROVED RESPIRATORY.

Ventilation:PROVIDE LOCAL EXHAUST VENT TO PREVENT BUILD-UP OF VAPORS

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY GLASSES/GOGGLES

Other Protective Equipment:EYE WASH/SAFETY SHOWER

Supplemental Safety and Health

MSDS DATE: 30 JUL 86. WGT PER GAL: 12.30. CONTAIN ALSO: CHROMIUM
(GB4200000) .60%/LEAD (OF7525000) 3%.

Chemical Properties

Boiling Pt:B.P. Text:231-290F

Percent Volatiles by Volume:50.0

Stability

Stability Indicator/Materials to Avoid:YES

OXIDIZERS, ACIDS, BASES, AMINES

Stability Condition to Avoid:ELEVATED TEMPERATURES. CONTACT WITH
OXIDIZING AGENT

Hazardous Decomposition Products:CO, CO2

Disposal

Waste Disposal Methods:DIKE AND CONTAIN SPILL. PUMP TO STORAGE OR
SALVAGE VESSELS. USE ABSORBENT TO PICK UP EXCESS RESIDUE. KEEP
SALVAGE MATERIAL/RINSE WATER OUT OF SEWERS OR WATER COURSES. COMPLY
WITH ALL APPLICABLE REGULATIONS FOR HEALTH AND POLLUTION CONTROL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.