

STRATA BLUE ACRYLIC ENAMEL, SE-111

MSDS Number

BBQBL

National Stock Number

8010-00F004350

Product Name

STRATA BLUE ACRYLIC ENAMEL, SE-111

Manufacturer

CROWN PAINT

Product Identification

Product ID:STRATA BLUE ACRYLIC ENAMEL, SE-111

MSDS Date:01/01/1987

FSC:8010

NIIN:00F004350

MSDS Number: BBQBL

Responsible Party

CROWN PAINT/OKLAHOMA CITY, OK 73117

Emergency Phone: (405) 232-8580

Cage: EO844

Contractor

CROWN PAINT/OKLAHOMA CITY, OK 73117

350

HEBRON, IL 60034

US

815-648-2424

Cage: EO844

Ingredients

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: SE7555000

Fraction By Weight: 40%

OSHA PEL100 PPM

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 8%

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

NAPHTA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: DE3030000

Fraction By Weight: 5%

OSHA PEL100 PPM

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: SE7555000

Fraction By Weight: 14%

OSHA PEL100 PPM

Hazards

Effects of

Overexposure:HEADACHE/DIZZINESS/STAGGERING/CONFUSION/UNCONSCIOUSNES
S/COMA. SKIN/EYE CONT: PRIMARY IRRITATION.

First Aid

First Aid:EYE/SKIN: FLUSH W/WATER FOR AT LEAST 15 MINUTES. IF IRRITATED
GET MEDICAL ATTENTION. VAPORS: REMOVE FROM EXPOSURE RESTORE
BREATHING. SWALLOWING: CALL PHYSICIAN IMMEDIATELY. DON'T INDUCE
VOMITING.

Fire Fighting

Flash Point:55F

Lower Limits:0.9%

Extinguishing Media:FOAM, CO2, FOG NOZZLES FOR COOLING.

Fire Fighting Procedures:WATER MAY BE INEFFECTIVE. WATER COOL
CONTAINERS.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE IF EXPOSED
TO EXTREME HEAT.

Accidental Release

Spill Release Procedures:ABSORB SPILL ON PAPER VERMICULITE FLOOR
ABSORBENT, OR OTHER ABSORBENT MATERIAL.

Handling

Handling and Storage Precautions:FLAMMABLE LIQUID DON'T USE NEAR
SPARKS, FIRE OR OPEN FLAME.

Other Precautions:OVER EXPOSURE HAS BEEN SUGGESTED CAUSE OF THE
FOLLOWING IN HUMANS: SEVERE ABNORMALITIES. EMPTY CONTAINERS MAY BE
HAZ. WHEN PTED. GROUND CONTAINERS IN EXPLOSIVE ATMOSPHERE WHEN
POURING.

Exposure Controls

Respiratory Protection:IF TLV IS EXCEEDED WEAR APPROVED SCBA W/A FULL
FACE PIECE.

Ventilation:PROVIDE LOCAL EXHAUST/MECH VENTILATION TO KEEP BELOW TLV

Protective Gloves:RESISTANT

Eye Protection:GOGGLES OR SAFETY GLASSES

Other Protective Equipment:TO PREV. PROLONGED SKIN CONT WEAR IMPERVIOUS
CLOTHING/BOOTS.

Supplemental Safety and Health

MSDS DATE: 05 NOV 86. WGT PER GAL: 8.0

Chemical Properties

Boiling Pt:B.P. Text:245-391F

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:67%

Stability

Stability Indicator/Materials to Avoid: YES

N/K _

Stability Condition to Avoid: AVOID CONTACT WITH STRONG OXIDIZERS

Disposal

Waste Disposal Methods: DESTROY BY LIQUID INCINERATION OR TOXIC SUBSTANCE LANDFILL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.