

KRYLON INT/EXT EN/ENGINE COLOR, 1501-2505

MSDS Number

BBQBP

National Stock Number

8010-00F004353

Product Name

KRYLON INT/EXT EN/ENGINE COLOR, 1501-2505

Manufacturer

BORDEN

Product Identification

Product ID:KRYLON INT/EXT EN/ENGINE COLOR, 1501-2505

MSDS Date:01/01/1987

FSC:8010

NIIN:00F004353

MSDS Number: BBQBP

Responsible Party

BORDEN/COLUMBUS, OH 43215

Emergency Phone: (614) 431-6600

Cage: EO867

Contractor

KRYLON PRODUCTS

SOLON, OH 44139

US

800-832-2541/216-566-2917

Cage: 87187

Ingredients

ACETONE (SARA III)

CAS: 67-64-1

RTECS: AL3150000

Fraction By Weight: 37%

OSHA PEL1000PPM

ACGIH TLV: 750PPM/1000STEL;9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight: 17%

OSHA PEL200 PPM/300 STEL

ACGIH TLV: 200 PPM/300STEL 9192

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

METHYL ISOBUTYL KETONE (SARA III)

CAS: 108-10-1

RTECS: SA9275000

Fraction By Weight: 2-4%

OSHA PEL100 PPM/75 STEL

ACGIH TLV: 50 PPM/75 STEL; 9293

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight: 2-3%

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 14%

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

Hazards

Effects of

Overexposure: DIZZINESS/HEADACHES/NAUSEA/VOMITING/UNCONCIOUSNESS/ASP
HYXIATION. EYES/SKIN: CAUSES IRRITATION.

First Aid

First Aid: INGESTION: IF SWALLOWED, DON'T INDUCE VOMITING. EYES CONTACT:
FLUSH W/WATER FOR 15 MINUTES. SKIN CONTACT: FLUSH W/WATER. IF
IRRITATION PERSISTS, CALL A PHYS. INHALATION: REMOVE TO FRESH AIR.
IF BREATHING IS DIFFICULT/GIVE OXYGEN. CALL A PHYSICIAN.

Fire Fighting

Extinguishing Media: USE DRY CHEMICAL, FOAM OR CO2, WATER MAY BE
INEFFECTIVE

Fire Fighting Procedures: EXPOSURE TO HIGH TEMP MAY CAUSE BURSTING.

Unusual Fire/Explosion Hazard: DON'T PUNCTURE/INCINERATE CONTAINER.
WATER COOL CONTAINERS.

Accidental Release

Spill Release Procedures: ELIMINATE ALL IGNITION SOURCES. SOAK UP WITH
ABSORBENT MATERIAL AND REMOVE TO A CHEMICAL DISPOSAL AREA. PREVENT
ENTRY INTO NATURAL BODIES OF WATER.

Handling

Handling and Storage Precautions:SKIN ABSORPTION. AVOID PROLONGED/REPEATED CONTACT W/EYES/SKIN/CLOTHING. AVOID BREATHING VAPOR MIST. WASH THOROUGHLY AFTER HANDLING.
Other Precautions:DO NOT STORE AT TEMPERATURES OVER 120F.

Exposure Controls

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATORY PROTECTION EQUIPMENT.
Protective Gloves:IMPERVIOUS
Eye Protection:GOGGLES
Supplemental Safety and Health
MSDS DATE: 30 JUN 86. ALSO CONTAINS: BUTYL ALCOHOL (EO1400000) 0.2-2.5%/PROPANE (TX2275000) 16.-17.%/2-PROPANOL 1-METHOXY-ETATE (AI8925000) 7.-8.%

Chemical Properties

Vapor Density:>AIR
Spec Gravity:Evaporation Rate & Reference:FASTER THAN BU AC
Solubility in Water:SLIGHT
Percent Volatiles by Volume:89%

Stability

Stability Indicator/Materials to Avoid:YES
Hazardous Decomposition Products:CO, CO2

Disposal

Waste Disposal Methods:DISPOSE OF ACCORDANCE TO LOCAL, STATE AND FEDERAL REQUIREMENTS. EMPTY CONTAINER, MAY CONTAIN EXPLOSIVE VAPORS. DON'T CUT, PUNCTURE OR WELD ON OR NEARBY. INCINERATION WILL CAUSE CONTAINER TO BURST VIOL ENTLY.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.