

## **KRYLON UPSIDE DOWN, 7101-7106; 7110-7112**

### **MSDS Number**

BBQBQ

### **National Stock Number**

8010-00F004354

### **Product Name**

KRYLON UPSIDE DOWN, 7101-7106; 7110-7112

### **Manufacturer**

BORDEN

### **Product Identification**

Product ID:KRYLON UPSIDE DOWN, 7101-7106; 7110-7112

MSDS Date:01/01/1987

FSC:8010

NIIN:00F004354

MSDS Number: BBQBQ

### **Responsible Party**

BORDEN/COLUMBUS, OH 43215

Emergency Phone: (614) 457-5200

Cage: EO867

### **Contractor**

KRYLON PRODUCTS

OLON, OH 44139

US

800-832-2541/216-566-2917

Cage: 87187

### **Ingredients**

METHYL ALCOHOL (METHANOL) (SARA III)

CAS: 67-56-1

RTECS: PC1400000

Fraction By Weight: 3.7%

OSHA PELS,200PPM/250STEL

ACGIH TLV: S,200PPM/250STEL; 93

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

HEXANE (N-HEXANE)

CAS: 110-54-3

RTECS: MN9275000

Fraction By Weight: 8.6%

OSHA PEL500 PPM

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 18.3%

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: SE7555000

Fraction By Weight: 3.2%

OSHA PEL100 PPM

ETHYLENE GLYCOL (SARA III)

CAS: 107-21-1

RTECS: KW2975000

Fraction By Weight: 4%

OSHA PELC 50 PPM

ACGIH TLV: C 50 PPM,VAPOR; 9192

EPA Report Quantity: 1 LB

DOT Report Quantity: 1 LB

## Hazards

Effects of

Overexposure:HEADACHE/DIZZINESS/NAUSEA/VOMITING/UNCONSCIOUSNESS/EVEN ASPHYXIATION/DROWSINESS.

## First Aid

First Aid:INTERNAL: IF SWALLOWED, DON'T INDUCE VOMITING. CALL A PHYSICIAN. INHALATION: REMOVE TO FRESH AIR. SKIN CONTACT: FLUSH W/WATER. IF IRRITATION PERSISTS, CALL A PHYSICIAN. EYE CONTACT: FLUSH W/WATER FOR AT LEAST 15 MINUTES. CALL A PHYSICIAN.

## Fire Fighting

Fire Fighting Procedures:EXPOSURE TO HIGH TEMP MAY CAUSE BURSTING. Unusual Fire/Explosion Hazard:DON'T PUNCTURE OR INCINERATE CONTAINER. DON'T SPRAY NEAR OPEN FLAME.

## Accidental Release

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. SOAK UP WITH ABSORBENT MATERIAL AND REMOVE TO A CHEMICAL DISPOSAL AREA. PREVENT ENTRY INTO NATURAL BODIES OF WATER.

## Handling

Handling and Storage Precautions:INHALATION: AVOID BREATHING VAPOR OR MIST. USE W/ADEQUATE VENTILATION. AVOID CONTACT WITH SKIN/YES. WASH THOROUGHLY AFTER HANDLING.

Other Precautions:DON'T STORE AT TEMPERATURES >120F.

---

## Exposure Controls

Respiratory Protection:RESP PROTECTION REQUIRED IN ABSENCE OF PROPER ENVIRONMENTAL CONTROL.  
Protective Gloves:IMPERVIOUS  
Eye Protection:SAFETY GLASSES  
Other Protective Equipment:SAFETY SHOES/HARD HATS/SUITABLE CLOTHING  
Supplemental Safety and Health  
MSDS DATE: 04 DEC 85. ALSO CONTAINS: PROPANE (TX2275000)  
17.4-18.3%/ISOBUTANE (TZ4300000) 11.6-12.2%/TOLUENE (XS5250000)  
016.%.

## Chemical Properties

Vapor Density:>AIR  
Spec Gravity:Evaporation Rate & Reference:FASTER THAN BU AC  
Solubility in Water:SLIGHT  
Percent Volatiles by Volume:83%

## Stability

Stability Indicator/Materials to Avoid:YES  
Stability Condition to Avoid:AVOID RADIATORS/STOVES/DIRECT SUNLIGHT/OTHER HEAT SOURCE.  
Hazardous Decomposition Products:CO, CO2

## Disposal

Waste Disposal Methods:DISPOSE OF ACCORDING TO LOCAL, STATE, AND FEDERAL REQUIREMENT. EMPTY CONTAINER: MAY CONTAIN EXPLOSIVE VAPORS. DON'T CUT, PUNCTURE OR WELD ON OR NEARBY. INCINERATION WILL CAUSE CONTAINER TO BURST VIOLE NTLY.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.