

PC-83 METALLIC ALUMINUM (ALUMINUM FINISH)

MSDS Number

BBQCS

National Stock Number

8010-00F004377

Product Name

PC-83 METALLIC ALUMINUM (ALUMINUM FINISH)

Manufacturer

BEECHAM HOME IMPROVEMENT PROD

Product Identification

Product ID:PC-83 METALLIC ALUMINUM (ALUMINUM FINISH)

MSDS Date:01/01/1987

FSC:8010

NIIN:00F004377

MSDS Number: BBQCS

Responsible Party

BEECHAM HOME IMPROVEMENT PROD/DAYTON, OH 45401

Emergency Phone: (513) 253-7154

Cage: 1BL51

Contractor

BEECHAM HOME IMPROVEMENT PRODUCTS INC

277

TIPP CITY, OH 45371-3014

US

Cage: 1BL51

Ingredients

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: SE7555000

Fraction By Weight: 60%

OSHA PEL100 PPM

TITANIUM DIOXIDE

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight: 20 - 25%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

CARBON BLACK

CAS: 1333-86-4

RTECS: FF5800000

Fraction By Weight: 5 - 10%

OSHA PEL3.5 MG/M3

ACGIH TLV: 3.5 MG/M3; 9192

RESIN

PIGMENTS

Hazards

Effects of Overexposure:HEADACHE/DIZZINESS/NAUSEA/UNCONSCIOUSNESS. IF INGESTED CAUSE VOMITING/DIARRHEA/DEPRESS RESPIRATION

First Aid

First Aid:INHALATION: REMOVE TO FRESH AIR. RESTORE BREATHING IF NECESSARY. EYES: FLUSH WITH WATER FOR 15 MINUTES. SKIN: WASH W/SOAP & WATER. INGESTION: DON'T INDUCE VOMITING. IF VICTIM IS CONSCIOUS, GIVE WATER OR MILK. CONTACT A PHYSICIAN IMMEDIATELY.

Fire Fighting

Flash Point:105F (CC)

Lower Limits:1.0%

Upper Limits:7.0%

Extinguishing Media:FOAM, CO2, DRY CHEMICALS

Fire Fighting Procedures:FULL PROTECTIVE EQUIP, INCLUDING SCBA. WATER COOL CONTAINERS

Unusual Fire/Explosion Hazard:CONTAINERS MAY EXPLODE IF EXPOSED TO EXTREME HEAT. DO NOT PUT IN CONTACT WITH OXIDIZING MATERIALS.

Accidental Release

Spill Release Procedures:ABSORB LIQUID ON PAPER/OIL DRY/OTHER ABSORBENT MATERIAL/ALLOW TO DRY/EVAPORATE UNDER HOOD. WEAR PROTECTIVE EQUIPMENT. ELIMINATE ALL SOURCES OF IGNITION(OPENFLAMES/PILOT LIGHTS/ELECTRICAL SPARKS)/VENTILATE AREA. CONTAIN SPILL BY DE.

Handling

Handling and Storage Precautions:KEEP CONTAINERS FROM EXCESSIVE HEAT/FREEZING. PROVIDE CROSS VENTILATION IN STORAGE AREA. KEEP CONTAINERS TIGHTLY CLOSED WHEN NOT IN USE.

Other Precautions:KEEP OUT OF REACH OF CHILDREN. HARMFUL/FATAL IF SWALLOWED. USE ONLY W/ADEQUATE VENT/ELIMINATE SOURCES OF IGNITION WHEN PRODUCT IS USED. REMOVE/WASH CONTAMINATED CLOTHING BEFORE REUSE.

Exposure Controls

Respiratory Protection:IF TLV IS EXCEEDED USE AN APPROVED NIOSH/MSHA RESPIRATOR.

Ventilation:PROVIDE MECH/LOCAL EXHAUST VENTILATION TO KEEP BELOW TLV

Protective Gloves:IMPERVIOUS

Eye Protection:GOGGLES/SAFETY GLASSES

Other Protective Equipment:PROVIDE EYEWASH/SOLVENT IMPERVIOUS APRON. USE BARRIER CREAM.

Supplemental Safety and Health

MSDS DATE: 15 MAY 1986. ALSO CONTAINS: INERT ADDITIVES (1000972AS).

Chemical Properties

Boiling Pt:B.P. Text:310-395F

Vapor Pres:2

Vapor Density:5.0

Spec Gravity:1.6

Evaporation Rate & Reference:(TOLUENE = 1):0.06

Solubility in Water:NEGLIGIBLE

Appearance and Odor:OPAQUE LIQ, VARIOUS COLORS; GASOLINE-LIKE ODOR

Percent Volatiles by Volume:55%

Stability

Stability Indicator/Materials to Avoid: YES
STRONG OXIDIZERS
Stability Condition to Avoid: EXCESSIVE HEAT
Hazardous Decomposition Products: NORMAL COMBUSTION PRODUCTS, COX, NOX

Disposal

Waste Disposal Methods: PREVENT RUN-OFF TO SEWERS/STREAMS/LAKES/OTHER BODIES OF WATER; NOTIFY LOCAL HEALTH/WILDLIFE OFFICIALS IF RUN-OFF OCCURS. DON'T INCINERATE SEALED CONTAINERS. DISPOSE ACCORDING TO FEDERAL/STATE/LOCAL REGULATIONS. LIQ CAN'T BE DISPOSED OF IN A LANDFILL.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.