
DELSTAR ACRYLIC ENAMEL, DAR 71654

MSDS Number

BBQCT

National Stock Number

8010-00F004378

Product Name

DELSTAR ACRYLIC ENAMEL, DAR 71654

Manufacturer

PPG INDUSTRIES

Product Identification

Product ID:DELSTAR ACRYLIC ENAMEL, DAR 71654

MSDS Date:01/01/1987

FSC:8010

NIIN:00F004378

MSDS Number: BBQCT

Responsible Party

PPG INDUSTRIES/CLEVELAND, OH 44111

Emergency Phone: (304) 843-1300

Cage: EO498

Contractor

PPG INDUSTRIES/CLEVELAND, OH 44111

ST JOSEPH, MI 49085

US

616-982-3215

Cage: EO498

Ingredients

ACRYLONITRILE (SARA III)

CAS: 107-13-1

RTECS: AT5250000

Fraction By Weight:

OSHA PELSEE 1910.1045

ACGIH TLV: S, 2 PPM;A2 9394

EPA Report Quantity: 100 LBS

DOT Report Quantity: 100 LBS

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight: 45%

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

CADMIUM SULFOSELENIDE (PIGMENT)

CAS: 12626-36-7

RTECS: EV2350000

Fraction By Weight: 10%

ACGIH TLV: 0.05 MG/CUM

TOLUENE (SARA III)

CAS: 108-88-3

RTECS: XS5250000

Fraction By Weight:

OSHA PEL200 PPM/150 STEL

ACGIH TLV: 50 PPM; 9293

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

Hazards

Effects of Overexposure:INHALATION: HEADACHE/DIZZINESS/STAGGERING
GAIT/CONFUSION/UNCONSCIOUSNESS/COMA. EYE/SKIN IRRITATION

First Aid

First Aid:FUMES: REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP
WARM/QUIET. NOTIFY A PHYSICIAN. EYES: FLUSH W/WATER FOR AT LEAST 15
MINUTES. SKIN: WASH AFFECTED AREAS W/WATER. REMOVE CONTAMINATED
CLOTHING. CONSU LT A PHYSICIAN.

Fire Fighting

Flash Point:81F (PMCC)

Lower Limits:1.1%

Extinguishing Media:CO2, DRY CHEMICAL OR FOAM

Fire Fighting Procedures:WATER COOL CONTAINERS TO PREV PRESSURE
BUILD-UP/EXPLOSION.

Unusual Fire/Explosion Hazard:KEEP CONTIANERS TIGHTLY CLOSED. CLOSED
CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION(FLAME/HOT
SURFACES/ELECTRICAL/STATIC/FRICITIONAL SPAR). AVOID BREATHING
VAPORS. VENTILATE AREA. REMOVE WITH INERT ABSORBENT/N-SPARKING
TOOLS.

Handling

Handling and Storage Precautions:DON'T STORE >120F. STORE LARGE
QUANTITIES IN BUILDINGS DESIGNED/PROTECTED FOR STORAGE OF FLAMMLES.
Other Precautions:DON'T TAKE INTERNALLY. CONTAINERS SHOULD BE GROUNDED
WHEN POURING. AVOID FREE FALL OF LIQ. IN EXCESS OF A FEW INCHES.
DON'T AME CUT/BRAZE OR WELD W/OUT NIOSH APPROVED RESP/VENTILATION.

Exposure Controls

Respiratory Protection:CONFINED AREAS: USE SUPPLIED AIR RESPIRATORS OR
HOODS

Ventilation:PROVIDE LOCAL EXHAUST VENTILATION TO KEEP BELOW TLV

Eye Protection:SAFETY EYEWEAR

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT
W/CONTAMINATED CLOTHING.

Supplemental Safety and Health

MSDS DATE: 12 MAR 85. WT/GAL: 9.03

Chemical Properties

Boiling Pt:B.P. Text:110-194C
Vapor Density:>AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:58.7

Stability

Stability Indicator/Materials to Avoid:YES
Hazardous Decomposition Products:FUMES MAY CONTAIN: CO/ACRYLONITRILE

Disposal

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DON'T INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.