

## **DYNASOLVE 700**

### **MSDS Number**

BBRPC

### **National Stock Number**

7930-00F005026

### **Product Name**

DYNASOLVE 700

### **Manufacturer**

DYNALOY INC

### **Product Identification**

Product ID:DYNASOLVE 700

MSDS Date:01/01/1987

FSC:7930

NIIN:00F005026

MSDS Number: BBRPC

### **Responsible Party**

DYNALOY, INC/HANOVER, NJ 07936

Emergency Phone: (201) 887-9270

Cage: EO982

### **Contractor**

DYNALOY, INC/HANOVER, NJ 07936

INDIANAPOLIS, IN 46203

US

317-788-9925;703-527-3887

Cage: EO982

### **Ingredients**

PROPYLENE GLYCOL MONOMETHYL ETHER

CAS: 107-98-2

RTECS: UB7700000

Fraction By Weight: 70%

OSHA PEL100 PPM/150 STEL

ACGIH TLV: 100 PPM/150STEL;9192

METHYL ALCOHOL (METHANOL) (SARA III)

CAS: 67-56-1

RTECS: PC1400000

Fraction By Weight: 2-5%

OSHA PELS,200PPM/250STEL

ACGIH TLV: S,200PPM/250STEL; 93

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

POTASSIUM HYDROXIDE (SARA III)

CAS: 1310-58-3

RTECS: TT2100000

Fraction By Weight: 2-5%

OSHA PELC, 2 MG/M3

ACGIH TLV: C 2 MG/M3; 9192

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

## Hazards

Effects of Overexposure: ANESTHETIC OR NARCOTIC EFFECT. EYE IRRITATION. SKIN IRRITATION. NAUSEA.

## First Aid

First Aid: INHALATION: REMOVE TO FRESH AIR. EYES: FLUSH WITH WATER FOR 15 MINUTES. SKIN: WASH OFF IN FLOWING WATER OR SHOWER. WASH CLOTHING BEFORE REUSE. INGESTION: INDUCE VOMITING IF LARGE AMOUNTS ARE INGESTED. CALL A PHYSICIAN.

## Fire Fighting

Flash Point: 95F (CC)

Lower Limits: 2.28

Upper Limits: 24.5

Extinguishing Media: WATER FOG, ALCOHOL FOAM, CO2, DRY CHEMICAL

Unusual Fire/Explosion Hazard: KEEP VAPORS FROM POSSIBLE IGNITION SOURCES.

## Accidental Release

Spill Release Procedures: ADD ABSORBENT. REMOVE WITH RUBBER SHOVEL. POTASSIUM HYDROXIDE REPORTABLE QUANTITY IS 000 POUNDS.

## Handling

Handling and Storage Precautions: KEEP AWAY FROM SOURCES OF IGNITION. GROUND ALL EQUIPMENT. AVOID BREATHING VAPORS.

## Exposure Controls

Respiratory Protection: RESPIRATORY PROTECTION REQ IN ABSENCE OF PROPER ENVIRONMENTAL CTRL.

Ventilation: PROVIDE LOCAL EXHAUST/MECHANICAL VENT TO KEEP BELOW TLV.

Protective Gloves: IMPERMEABLE

Eye Protection: SAFETY GLASSES

Other Protective Equipment: IMPERMEABLE APRON.

Supplemental Safety and Health

MSDS DATE: 3/86.

## Chemical Properties

Boiling Pt: B.P. Text: 248F

Vapor Pres: 12.

Vapor Density: 3.12

Spec Gravity: 0.92

Solubility in Water: COMPLETE

Appearance and Odor: BLUE - GREEN LIQUID, SLIGHT PLEASANT ODOR.

Percent Volatiles by Volume: 100%

## Stability

Stability Indicator/Materials to Avoid: YES

OXIDIZING MATERIALS

Stability Condition to Avoid: FLAME, IGNITION SOURCES

Hazardous Decomposition Products: CO, CO2

## Disposal

Waste Disposal Methods: DISPOSE OF IN COMPLIANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS. DILUTE SPENT SOL 20 X VOL OF WATER, IT WON'T BE

A HAZARDOUS WASTE, FLASH PT WILL BE >140F (CC).

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.