

<u>036GY89, GRAY, 36375</u>

MSDS Number

BBSBP

National Stock Number

8010-01-017-2480

Product Name

036GY89, GRAY, 36375

Manufacturer

DEFT INC

Product Identification

Product ID:036GY89, GRAY, 36375 MSDS Date: 01/01/1987 FSC:8010 NIIN:01-017-2480 Kit Part:Y MSDS Number: BBSBP

Responsible Party

DEFT, INC/IRVINE, CAL 92714

Emergency Phone: (714) 474-0400

Cage: EO744 Contractor

DEFT, INC/IRVINE, CAL 92714

IRVINE, CA 92614

US

949-474-0400 Cage: EO744

Ingredients

2-ETHOXYETHYL ACETATE (CELLOSOLVE ACETATE) (EGEEA)

CAS: 111-15-9 RTECS: KK8225000 Fraction By Weight: 20% OSHA PELS, 100 PPM

ACGIH TLV: S, 5 PPM; 9192

TOLUENE (SARA III)

CAS: 108-88-3 RTECS: XS5250000 Fraction By Weight:

OSHA PEL200 PPM/150 STEL ACGIH TLV: 50 PPM; 9293 EPA Report Quantity: 1000 LBS DOT Report Quantity: 1000 LBS



METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight: 10 - 20% OSHA PEL200 PPM/300 STEL

ACGIH TLV: 200 PPM/300STEL 9192

EPA Report Quantity: 5000 LBS DOT Report Quantity: 5000 LBS

ETHYL ACETATE (SARA III)

CAS: 141-78-6

RTECS: AH5425000

Fraction By Weight: 10%

OSHA PEL400 PPM

ACGIH TLV: 400 PPM; 9192 EPA Report Quantity: 5000 LBS DOT Report Quantity: 5000 LBS

DIBUTYL TIN DILAURATE (AS TIN)

CAS: 77-58-7

RTECS: WH7000000 Fraction By Weight:

OSHA PELS, 0.1 MG/M3

ACGIH TLV: S, 0.1 MG/M3; 8990

Hazards

Effects of Overexposure: INHALATION: RESP TRACT

IRRIT/HEADACHE/DIZZINESS/STAGGERING GAIT/CONFUSION/UNCONSCIOUSNESS

OR COMA.

First Aid

First Aid: INHALATION: REMOVE FROM EXPOSURE, RESTORE BREATHING, KEEP WARM & QUIET. EYES: FLUSH W/WATER FOR 15 MINS, TAKE TO A PHYSICIAN FOR MEDICAL ATTENTION. SKIN: WASH AFFECTED AREAS WITH WATER. REMOVE CONTAMI NATED CLOTHING, CONSULT A PHYSICIAN.

Fire Fighting

Flash Point: 24F (TCC)

Extinguishing Media: FOAM, CO2, DRY CHEMICAL, WATER FOG.

Fire Fighting Procedures: USE PROTECTIVE EQUIPMENT & SCBA. WATER COOL

CONTAINERS.

Unusual Fire/Explosion Hazard: KEEP CONTAINERS TIGHTLY CLOSED. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT.

Accidental Release

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION (FLAMES, HOT SURFACES, SPARK SOURCES) AVOID BREATHINGAPORS. CONTAIN & REMOVE WITH INERT OBSORBENT & NON-SPARKING TOOLS.

Handling

Handling and Storage Precautions: STORE IN BUILDINGS DESIGNED TO COMPLY WITH OSHA 1910.106. KEEP CONTAINERS TIGHT & UPRIGHT TO PVENT LEAKAGE.



Other Precautions: DON'T STORE OR USE NEAR HEAT, SPARKS, OR FLAME. STORE ONLY IN WELL VENTILATED AREAS. PREVENT PROLONGED OR REPEATED BREATHINGF VAPOR OR SPRAY MIST.

Exposure Controls

Respiratory Protection: APPROVED MECH FILTERS DESIGNED TO REMOVE A

COMBINATION OF VAPOR.

Ventilation:VENT FUMES ON HEATING. Protective Gloves:NEOPRENE/RUBBER Eye Protection:SAFETY EYEWEAR

Other Protective Equipment: REMOVE & WASH CONTAMINATED CLOTHING BEFORE

REUSE.

Supplemental Safety and Health

MSDS DATE: 04/28/86. WT/GAL: 10.57

Chemical Properties

HCC:F2

Boiling Pt:B.P. Text:168-313F

Vapor Density:>AIR

Evaporation Rate & Reference: SLOWER THAN ETHER

Percent Volatiles by Volume: 58.3

Stability

Stability Indicator/Materials to Avoid:YES ACIDS AND BASES Stability Condition to Avoid:ELEVATED TEMERATURES.

Disposal

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS. INCINERATE IN APPROVED FACILITY. DON'T INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.