

ALKYD LO-SHEEN ENL MIDTONE BASE, 6-105

MSDS Number

BBSFY

National Stock Number

8010-00F005318

Product Name

ALKYD LO-SHEEN ENL MIDTONE BASE, 6-105

Manufacturer

PPG INDUSTRIES INC

Product Identification

Product ID:ALKYD LO-SHEEN ENL MIDTONE BASE, 6-105

MSDS Date:01/01/1987

FSC:8010

NIIN:00F005318

MSDS Number: BBSFY

Responsible Party

PPG INDUSTRIES, INC/PITTSBURGH, PA 15238

Emergency Phone: (304) 843-1300

Cage: DO894

Contractor

PPG INDUSTRIES, INC.

9

ALLISON PARK, PA 15101

US

412-592-5555

Cage: DO894

Ingredients

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: SE7555000

Fraction By Weight: 10%

OSHA PEL100 PPM

ALIPHATIC SOLVENT (VAPOR PRESSURE = 0.1)

Fraction By Weight:

XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS: 1330-20-7

RTECS: ZE2100000

Fraction By Weight:

OSHA PEL100 PPM

ACGIH TLV: 100 PPM/150STEL;9394

EPA Report Quantity: 1000 LBS

DOT Report Quantity: 1000 LBS

METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS: 78-93-3

RTECS: EL6475000

Fraction By Weight:

OSHA PEL200 PPM

ACGIH TLV: 200 PPM/300STEL;9394

EPA Report Quantity: 5000 LBS

DOT Report Quantity: 5000 LBS

Hazards

Effects of Overexposure:INHALATION: RESP TRACT
IRRITATION/HEADACHE/DIZZINESS/STAGGERING
GAIT/CONFUSION/UNCONSCIOUSNESS.

First Aid

First Aid:REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM & QUIET.
NOTIFY A PHYS. EYES: FLUSH W/COPIOUS QTYS OF WATER AT LEAST 15
MINS. TAKE TO A PHYS FOR MED TREATMENT. SKIN: WASH AFFECTED AREAS
W/WATER. RE MOVE CONTAMINATED CLOTHING. CONSULT A PHYS.

Fire Fighting

Flash Point:118F PMCC

Lower Limits:1.0

Extinguishing Media:CO2, DRY CHEMICAL OR FOAM.

Fire Fighting Procedures:WATER COOL CONTAINERS. IF FOG NOZZLES ARE
PREFERABLE.

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS TIGHTLY MAY EXPLODE &
AUTO-IGNITE WHEN EXPOSED TO EXTREME HEAT.

Accidental Release

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAMES, HOT
SURFACES, & ELECTRICAL, STATIC, OR FRICTNAL SPARKS). AVOID
BREATHING VAPORS. VENTILATE AREA. REMOVE WITH INERT AORBENT AND
NON-SPARKING TOOLS.

Handling

Handling and Storage Precautions:DON'T STORE >120F. STORE LARGE
QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NA
CLASS II COMBUSTIBLE LIQUIDS.

Other Precautions:DON'T TAKE INTERNALLY. CONTAINERS SHOULD BE GROUNDED
WHEN POURING. AVOID FREE FALL OF LIQUID. DON'T FLAME CUT, BRAZE OR
WELD/OUT NIOSH APPROVED RESPIRATORS OR APPROPRIATE VENTILATION.

Exposure Controls

Respiratory Protection:VENTILATION AREAS: USE COMBINATION ORGANIC
VAPOR-FILTER RESPIRATORS.

Ventilation:PROVIDE LOCAL EXHAUST VENTILATION TO KEEP BELOW LEL.

Eye Protection:SAFETY EYEWEAR

Other Protective Equipment:GLOVES FOR PROLONGED & REPEATED CONTACT.

Supplemental Safety and Health

MSDS DATE: 12/11/81. WT/GAL: 10.28

Chemical Properties

HCC:F4

Boiling Pt:B.P. Text:100-273F

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:51.2

Stability

Stability Indicator/Materials to Avoid: YES
Hazardous Decomposition Products: MAY PRODUCE HAZARDOUS FUMES WHEN HEATED, & MAY CONTAIN CO.

Disposal

Waste Disposal Methods: DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DON'T INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.