

## **VELOUR INT SEMI-GLOSS ENL, 2653 DEEP BASE**

### **MSDS Number**

BBSQC

### **National Stock Number**

8010-00F005498

### **Product Name**

VELOUR INT SEMI-GLOSS ENL, 2653 DEEP BASE

### **Manufacturer**

DEVOE AND RAYNOLDS CO

### **Product Identification**

Product ID:VELOUR INT SEMI-GLOSS ENL, 2653 DEEP BASE

MSDS Date:01/01/1987

FSC:8010

NIIN:00F005498

MSDS Number: BBSQC

### **Responsible Party**

DEVOE & RAYNOLDS CO/LOUISVILLE, KY 40207

Emergency Phone: (502) 589-9340

Cage: EO559

### **Contractor**

DEVOE COATINGS CO DIV OF GROW GROUP INC

RIVERSIDE, CA 92507-2606

US

Cage: 70506

### **Ingredients**

NAPHTHA, ALIPHATIC PETROLEUM DISTILLATES (VAPOR PRESSURE =

Fraction By Weight: 30%

ACGIH TLV: 100 PPM

TITANIUM DIOXIDE

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight: 5-25%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

CALCIUM CARBONATE (MARBLE) (LIMESTONE)

CAS: 1317-65-3

RTECS: EV9580000

Fraction By Weight: 35%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9192

SILICA, AMORPHOUS, DIATOMACEOUS EARTH, CONTAINING LESS THAN

CAS: 61790-53-2

RTECS: HL8600000

Fraction By Weight:

OSHA PEL20 MPPCF

ACGIH TLV: 10 MG/M3 TDUST; 9293

## Hazards

Effects of Overexposure: BREATHING: SKIN/EYE/RESP TRACT  
IRRITATION/HEADACHE/NAUSEA/DIZZINESS/UNCONSCIOUSNESS/VOMITING.

## First Aid

First Aid: BREATHED: REMOVE TO FRESH AIR. EYES: FLUSH W/WATER FOR AT  
LEAST 15 MINS. GET MED ASSISTANCE. SKIN: WASH AREA THOROUGHLY  
W/SOAP & WATER. REMOVE SOILED CLOTHING. GET MED ASSISTANCE IF IRRIT  
PERSISTS. SW ALLOWED: DON'T INDUCE VOMITING. CONSULT PHYS.

## Fire Fighting

Flash Point: 112F SCC

Lower Limits: 1.0%

Extinguishing Media: IN CASE OF FIRE USE CO2, DRY CHEMICAL, FOAM.

Fire Fighting Procedures: USE FULL PROTECTIVE EQUIPMENT & SCBA.

Unusual Fire/Explosion Hazard: WATER TO COOL CONTAINERS & PREVENT  
PRESSURE BUILD-UP OR POSSIBLE AUTO-IGNITION TO HEAT.

## Accidental Release

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION (HEAT, FLAME)  
DON'T SMOKE. AVOID BREATHING VAPORS. VEILATE AREA. CONTAIN SPILLED  
MATERIAL & REMOVE W/INERT ABSORBENT & NON-SPKING TOOLS. STORE IN  
CLOSED CONTAINERS UNTIL PROPERLY DISPOSED OF.

## Handling

Handling and Storage Precautions: KEEP AWAY FROM HEAT & FLAME. DON'T  
SMOKE. PREVENT BUILD-UP OF VAPORS BY MAINTAINING CONTINUOUS FLOW OF  
FRESH AIR. DON'T STORE > 120F OR NEAR FLAME.

Other Precautions: STORE LARGE QTY'S IN BUILDINGS DESIGNED TO COMPLY  
W/1910.106. KEEP CONTAINER CLOSED WHEN NOT IN USE. DON'T TRANSFER  
CONTENTS OTHER UNLABELLED CONTAINERS. KEEP OUT OF REACH OF  
CHILDREN.

## Exposure Controls

Respiratory Protection: USE NIOSH APPROVED MECH RESP TO REMOVE SOLID  
AIRBORNE OR OVERSPRAY.

Ventilation: PROVIDE LOCAL EXHAUST VENTILATION TO KEEP BELOW TLV

Protective Gloves: SOLV IMPERMEABLE

Eye Protection: SAFETY EYEWEAR/SIDESHIELD

Other Protective Equipment: DON'T GET ON SKIN. SOLVENT IMPERMEABLE  
CLOTHING/BOOTS

Supplemental Safety and Health

MSDS DATE: 7/85. PDS PER GALLON: 10.24-11.66.

## Chemical Properties

Boiling Pt: B.P. Text: 300-405F

Evaporation Rate & Reference: SLOWER THAN ETHER

Percent Volatiles by Volume: 49.9

## Stability

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS

Hazardous Decomposition Products: FUMES MAY CONTAIN CO, CO2

## Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. INCINERATE ONLY IN APPROVED FACILITY. DON'T INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.