

2670 SAIL WHITE

MSDS Number

BBSQW

National Stock Number

8010-00F005516

Product Name

2670 SAIL WHITE

Manufacturer

DEVOE AND RAYNOLDS CO

Product Identification

Product ID:2670 SAIL WHITE

MSDS Date:01/01/1987

FSC:8010

NIIN:00F005516

MSDS Number: BBSQW

Responsible Party

DEVOE & RAYNOLDS CO/LOUISVILLE, KY 40207

Emergency Phone: (502) 589-9340

Cage: EO559

Contractor

DEVOE COATINGS CO DIV OF GROW GROUP INC

RIVERSIDE, CA 92507-2606

US

Cage: 70506

Ingredients

ALIPHATIC NAPHTHA, PETROLEUM (15-30%)

Fraction By Weight: 30%

ACGIH TLV: 100 PPM

NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS: 8030-30-6

RTECS: SE7555000

Fraction By Weight: 10%

OSHA PEL100 PPM

TITANIUM DIOXIDE

CAS: 13463-67-7

RTECS: XR2275000

Fraction By Weight: 5-25%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9293

CALCIUM CARBONATE (MARBLE) (LIMESTONE)

CAS: 1317-65-3

RTECS: EV9580000

Fraction By Weight: 35%

OSHA PEL15 MG/M3 TDUST

ACGIH TLV: 10 MG/M3 TDUST; 9192

SILICA, AMORPHOUS, DIATOMACEOUS EARTH, CONTAINING LESS THAN

CAS: 61790-53-2

RTECS: HL8600000

Fraction By Weight:

OSHA PEL20 MPPCF

ACGIH TLV: 10 MG/M3 TDUST; 9293

Hazards

Effects of Overexposure: BREATHING: SKIN & EYE/RESP TRACT
IRRITATION/HEADACHE/DIZZINESS/WEAKNESS/FATIGUE/UNCONSCIOUSNESS.

First Aid

First Aid: BREATHED: REMOVE TO FRESH AIR. EYES: FLUSH W/WATER FOR AT
LEAST 15 MINS. GET MEDICAL ASSISTANCE. SKIN: WASH W/SOAP & WATER.
REMOVE SOILED CLOTHING. GET MEDICAL ASSISTANCE IF IRRITATION
PERSISTS. IF SW ALLOWED: DON'T INDUCE VOMITING. CONSULT PHYS.

Fire Fighting

Flash Point: 112F SETAFLASH

Extinguishing Media: CO₂, DRY CHEMICAL, FOAM

Fire Fighting Procedures: USE FULL PROTECTIVE EQUIPMENT SCBA. IF NOZZLES
IS PREFERABLE

Unusual Fire/Explosion Hazard: DUE TO PREV. PRESSURE BUILD-UP OR
AUTO-IGNITE, CLOSED CONTAINERS EXPOSED TO EXTREME HEAT MAY EXPLODE

Accidental Release

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION (HEAT, FLAME).
DON'T SMOKE. AVOID BREATHING VAPORS. VILATE AREA. CONTAIN SPILLED
MATERIAL & REMOVE WITH INERT ABSORBENT & NOSPARKING TOOLS. STORE IN
CLOSED CONTAINERS UNTIL PROPERLY DISPOSED OF.

Handling

Handling and Storage Precautions: REMOVE/WASH SOILED CLOTHING BEFORE
REUSE. WASH HANDS BEFORE EATING, SMOKING OR USING THE WASHRM. KEEP
AWAY FROM HEAT & FLAME. DON'T SMOKE.

Other Precautions: PREVENT BUILD-UP OF VAPORS BY MAINTAINING CONTINUOUS
FLOW OF FRESH AIR. DON'T STORE >120F NEAR FLAME. STORE LARGE QTYS
IN BUDINGS TO COMPLY W/OSHA 1910.106. KEEP OUT OF REACH OF CHILDREN

Exposure Controls

Respiratory Protection: HEAVY SOLVENT VAPORS SHOULD BE REMOVED FROM
LOWER LEVELS OF THE AREA

Ventilation: PROVIDE LOCAL EXHAUST VENTILATION TO KEEP BELOW TLV.

Protective Gloves: IMPERMEABLE

Eye Protection: SAFETY EYEWEAR/SIDESHIELD

Other Protective Equipment: SOLVENT IMPERMEABLE CLOTHING & BOOTS TO
PREVENT CONTACT.

Supplemental Safety and Health

7/85. 2601 WHITE/2602 OFF WHITE/2649 HIGH HIDE BASE/2651 MEDIUM
BASE/2653 DEEP BASE/2655 ULTRA DEEP BASE/2664 OYSTER WHITE/2670 SAIL
WHITE/2671 ANTIQUE WHITE/2692 BAY WHITE/2693 SOFT WHITE

Chemical Properties

Boiling Pt:B.P. Text:300-405F
Vapor Density:>AIR
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:49.9

Stability

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS
Hazardous Decomposition Products:CO,CO2
SITION MAY CO, CO2.

Disposal

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND
FEDERAL REGULATIONS. INCINERATE ONLY IN APPROVED FACILITY. DON'T
INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.